

ORDER NO. VSD9404M245
D4

Service Manual


Volume 2

Panasonic **S** **VHS** **Hi-Fi**

Editing Video Cassette Recorder

AG-DS850P

- Sec. 6** *Mechanism*
- Sec. 7** *Electrical Adjustment*
- Sec. 8** *Block Diagrams*
- Sec. 9** *Supplement (Voltage table)*



The Operating Instructions (Sec. 1), Disassembly Procedures (Sec. 2), Schematic Diagrams (Sec. 3), Circuit Board Diagrams (Sec. 4), and Exploded Views & Replacement Parts Lists (Sec. 5), please refer to the Service Manual Volume 1 (Order No. VSD9404M244).

The detail circuit description for this model, please refer to the Supplement Service Manual (Order No. VSD9404D209).

Panasonic®

© 1994 Matsushita Electric Industrial Co., Ltd. All rights reserved.
Unauthorized copying and distribution is a violation of law.

⚠ WARNING

This service information is designed for experienced repair technicians only and is not designed for use by the general public. It does not contain warnings or cautions to advise non-technical individuals of potential dangers in attempting to service a product. Products powered by electricity should be serviced or repaired only by experienced professional technicians. Any attempt to service or repair the product or products dealt with in this service manual by anyone else could result in serious injury or death.

SPECIFICATIONS

ITEM			SPECIFICATION			ITEM			SPECIFICATION		
Power	Source	AC 120V ± 10%, 50-60Hz		Audio	Heads	Normal Audio Control; 1 stationary head Hi-Fi Audio; 2 rotary heads (42 μ m× 2) Erase;1 full track erase, 1 Audio track erase					
	Consumption	Approx. 87Watts (with AG-A750)				Tracks	Normal audio; 2 track (stereo) Hi-Fi Audio; 2 channels (stereo)				
Television Format	EIA Standard (525 lines, 60fields) NTSC color signal				Input level		LINE IN Hi-Fi (XLR): + 4/0/ - 6dBs, Hi-imp. balanced LINE IN NORM/ Hi-Fi (XLR): + 4/0/ - 6dBs, Hi-imp. balanced MICROPHONE IN (1/4" PHONE× 2); - 50dBv, 4.7kΩ unbalanced				
Tape Speed	33.35mm/ s (1-15/ 16 i.p.s)					Output level	LINE OUT Hi-Fi (XLR): + 4/0/ - 6dBs, Hi-imp. balanced LINE OUT NORM/ Hi-Fi (XLR): + 4/0/ - 6dBs, Hi-imp. balanced HEADPHONES (1/4" PHONE) - 60dBv to - 20dBv, 8Ω unbalanced AUDIO MONITOR OUT (PHONO); 0dBv, 600Ω unbalanced				
Tape Format	S-VHS, VHS						Frequency Response	Normal; 50Hz to 12kHz Hi-Fi; 20Hz to 20kHz			
FF/ REW	Approx. 2.5min. (with 120min. tape)							Dynamic Range	Hi-Fi; more than 90 dB		
Video	Head	2 rotary heads, helical scanning system 58 μ m (NOR) × 2, 58 μ m (SS) × 2 2 flying (rotary) erase heads 56 μ m × 2			Time Code		S/ N Ratio		48dB (Normal) (with NR switch ON)		
	Luminance	FM azimuth recording				Input Level		1.0Vp-p, 10kΩ unbalanced			
	Color signal	Converted subcarrier phase shift recording					Output level	2.4Vp-p, low impedance unbalanced			
	Input level	LINE (BNC); 1.0Vp-p, 75Ω unbalanced S-VIDEO (4P); Y: 1.0Vp-p, 75Ω unbalanced C: 0.286Vp-p (burst), 75Ω unbalanced REF IN (BNC): 1.0Vp-p, 75Ω unbalanced				Standard Accessories		Power Cable VJA0472			
	Output level	LINE (BNC× 2); 1.0Vp-p, 75Ω unbalanced S-VIDEO (4P× 2); Y: 1.0Vp-p, 75Ω unbalanced C: 0.286Vp-p (burst), 75Ω unbalanced COMPONENT OUT (BNC× 3): Y: 1.0Vp-p, 75Ω unbalanced Pr: 0.486Vp-p, 75Ω unbalanced Pb: 0.486Vp-p, 75Ω unbalanced VIDEO MONITOR OUT (BNC): 1.0Vp-p 75Ω unbalanced		Optional Accessories			S-VIDEO cable (4P)AG-C71 (5m) VW-CV2 (2m) VW-CV1 (1.5m)				
	Signal-to-Noise Ratio	VHS; 46dB (color)				Editing controller	AG-A350 AG-A800 AG-A770 AG-A750				
	Horizontal Resolution	S-VHS; more than 400 lines VHS; 240 lines		AG-A300 AG-A505 AG-A600 AG-M730E AG-IA834 AU-ER65							
	Operating Condition	Temperature	5°C - 40°C (41°F to 104°F)								
	Humidity	35% - 80%									
Dimensions	16 - 11/16" (W) × 5 - 3/16" (H) × 16 - 5/16" (D) 424 mm(W) × 131.5 mm(H) × 415mm(D)										
Weight	Approx. 12kg (Approx. 26.4 lbs)										

Weight and dimensions shown are approximate.
Specifications are subject to change without notice.

INTRODUCTION

This Service Manual contains all the technical information which will allow service personnel to understand and service the Panasonic S-VHS editing video cassette recorder model AG-DS 850P.

This model is video cassette recorder for editing applications which was developed for applications in industry, educational establishments, studios and CATV transmissions.

By the use of S-VHS system, a sharp picture quality with high resolution is obtained, and advanced editing by easy operation is realized by the introduction of highly dependable mechanisms.

Panasonic

CONTENTS

SPECIFICATIONS	1
SAFETY PRECAUTIONS	3
SECTION 6 MECHANISM	6-1
SECTION 7 ELECTRICAL ADJUSTMENTS	7-1
SECTION 8 BLOCK DIAGRAMS	8-1
SECTION 9 SUPPLEMENT	9-1

SAFETY PRECAUTIONS

GENERAL GUIDELINES

1. When servicing observe the original lead dress. If a short circuit is found, replace all parts which have been overheated or damaged by the short circuit.
2. After servicing, see to it that all the protective devices such as insulation barriers, insulation papers shields are properly installed.
3. After servicing make the following leakage current checks to prevent the customer from being exposed to shock hazards.

LEAKAGE CURRENT COLD CHECK

1. Unplug the AC cord and connect a jumper between the two prongs on the plug.
2. Measure the resistance value, with an ohm meter, between the jumpered AC plug and each exposed metallic cabinet part on the equipment such as screwhead connectors, control shafts, etc. When the exposed metallic part has a return path to the chassis, the reading should be between $1\text{M}\Omega$ and $5.2\text{M}\Omega$. When the exposed metal does not have a return path to the chassis, the reading must be ∞ .




Figure 1

LEAKAGE CURRENT HOT CHECK (See Figure 1)

1. Plug the AC cord directly into the AC outlet. Do not use an isolation transformer for this check.
2. Connect a $1.5\text{K}\Omega$, 10W resistor, in parallel with $0.15\mu\text{F}$ capacitor, between each exposed metallic part on the set and a good earth ground such as a water pipe, as shown in Figure 1.
3. Use an AC voltmeter, with 1000 ohms/volt or more sensitivity, to measure the potential across the resistor.
4. Check each exposed metallic part, and measure the voltage at each point.
5. Reverse the AC plug in the AC outlet repeat each of the above measurements.
6. The potential at any point should not exceed 0.75 volts RMS. A leakage current tester (Simpson Model 229 equivalent) may be used to make the hot checks, leakage current must not exceed $1/2$ milliamp. In case a measurement is outside of the limits specified, there is a possibility of a shock hazard, and the equipment should be repaired and rechecked before it is returned to the customer.

ELECTROSTATICALLY SENSITIVE(ES) DEVICES

Some semiconductor (solid state) devices can be damaged easily by static electricity. Such components commonly are called Electrostatically sensitive (ES) Devices. Examples of typical ES devices are integrated circuits and some field-effect transistors and semiconductor "chip" components. The following techniques should be used to help reduce the incidence of component damage caused by static electricity.

1. Immediately before handling any semiconductor component or semiconductor-equipped assembly, drain off any electrostatic charge on your body by touching a known earth ground. Alternatively, obtain and wear a commercially available discharging wrist strap device, which should be removed for potential shock reasons prior to applying power to the unit under test.
2. After removing an electrical assembly equipped with ES devices, place the assembly on a conductive surface such as aluminum foil, to prevent electrostatic charge buildup or exposure of the assembly.
3. Use only a grounded tip soldering iron to solder or unsolder ES devices.
4. Use only an anti-static solder removal device classified as "anti-static" can generate electrical charges sufficient to damage ES devices.
5. Do not use freon-propelled chemicals. These can generate electrical charges sufficient to damage ES devices.
6. Do not remove a replacement ES device from its protective package until immediately before you are ready to install it. (Most replacement ES devices are packaged with leads electrically shorted together by conductive foam, aluminum foil or comparable conductive material).
7. Immediately before removing the protective material from the leads of replacement ES device, touch the protective material to the chassis or circuit assembly into which the device will be installed.
CAUTION: Be sure no power is applied to the chassis or circuit, and observe all other safety precautions.
8. Minimize bodily motions when handling unpackaged replacement ES devices. (Otherwise harmless motion such as the brushing together of your clothes fabric or the lifting of your foot from a carpeted floor can generate static electricity sufficient to damage an ES device).

SECTION 6

MECHANISM

CONTENTS

6-1. Parts Location	6-3
6-2. Servicing Fixtures and Tools	6-4
6-3. How To Eject Manually	6-5
6-4. Maintenance Procedures	6-6
6-4-1. Regular Maintenance	6-6
6-4-2. Maintenance Chart	6-6
6-4-3. Lubrication Procedures of the Capstan Shaft	6-7
6-4-4. Procedures for Cleaning of the Cylinder Unit	6-7
6-4-5. Adjustments After Re-installing the Upper Cylinder, Lower Cylinder	6-8
6-4-6. Adjustments After Re-installing the A/C Head Unit	6-8
6-5. Mechanical Parts Replacement Procedures	6-9
6-5-1. Replacement of the Upper Cylinder Unit	6-9
6-5-2. Replacement of the Lower Cylinder Unit	6-10
6-5-3. Replacement of the A/C Head (1) Unit	6-10
6-5-4. Replacement of the Full Erase Head	6-10
6-5-5. Replacement of the Capstan Rotor and Capstan Stator	6-10
6-5-6. Replacement of the Capstan Housing Unit	6-11
6-5-7. Replacement of the Inclined Base (S), (T)	6-12
6-5-8. Replacement of the P5 Post	6-12
6-5-9. Replacement of the Reel Unit	6-13
6-5-10. Replacement of the Main Brake (S), (T) Unit	6-13
6-5-11. Replacement of the Pressure Roller Unit	6-13
6-5-12. Replacement of the Mode Switch	6-14
6-5-13. Replacement of the Pinch Solenoid	6-14
6-5-14. Replacement of the Head Cleaning Pad	6-15
6-6. Adjustment Procedures	6-16
6-6-1. Floe Chart of Tape Interchangeability Adjustment	6-16
6-6-2. Coarse Adjustment of the Tape Guide Post Heights (P2 and P3)	6-17
6-6-3. Fine Adjustment of the Guide Post Height (P2 and P3) (Linearity)	6-18
6-6-4. Adjustment of the Pull-out Post (P5) Height	6-18
6-6-5. Adjustment of the A/C Head	6-19
6-6-6. Coarse Adjustment of the A/C Horizontal Position (X-Value)	6-21
6-6-7. Fine Adjustment of the A/C Horizontal Position (X-Value)	6-21
6-6-8. Adjustment of Inclined Base (T)	6-22
6-6-9. Adjustment of Thrust Gap	6-22
6-6-10. Adjustment of FG Gap	6-22
6-6-11. Measurement and Adjustment of Back Tension	6-23
6-6-12. Height Adjustment of the Reel Tables	6-23
6-6-13. Measurement and Adjustment of the Brake Torque	6-24
6-6-14. Pressing Force Confirmation of Pressure Roller Unit	6-25
6-6-15. Adjustment of Rev Tension Sensor Position	6-25
6-7. Assembly and Adjustment of Mechanism	6-27
6-7-1. Confirmation of Alignment Condition	6-27
6-7-2. Assembly Procedures of Sub Cam Gear, Ring Gear and Detent Arm	6-28
6-7-3. Assembly Procedures of Main Cam Gear and Pinch Speed Down Gear	6-28
6-7-4. Assembly Procedures of Loading Cam Gear and Retainer Gear	6-28
6-7-5. Assembly Procedures of Center Gear	6-29
6-7-6. Assembly Procedures of Main Lever and Cam Follower Arm Unit	6-29
6-7-7. Assembly Procedures of Loading Gear (T), Loading Gear (S) Sector Gear	6-29
6-7-8. Assembly Procedures of Connection Gear	6-30
6-7-9. Assembly Procedures of Mode Switch and P5 Pull Out Sector Gear	6-30
6-7-10. Assembly Procedures of Pinch Cam and Pressure Roller Unit	6-30
6-7-11. Assembly Procedures of Gear Base Unit	6-31
6-7-12. Re-installation of Cassette Compartment	6-31

6-1. PARTS LOCATION




Figure M1
























Figure M2

6-2. SERVICING FIXTURES AND TOOLS

The specified servicing fixture must be used to conduct adjustment.

The following fixtures, tools and measuring equipments are required to conduct complete Mechanical Adjustments.

VFM8080HQFP ; VHS Alignment Tape 	VFK1012 ; Post Adjustment Plate 	VFK0335 ; Retaining Ring Remover 
VFK0329 ; Post Adj. Screwdriver 	VFK0328 ; H-Position Adj. Screwdriver 	VFK0330 ; Fine Adj. Screwdriver (3mm) 
VFK0132 ; Back Tension Meter (Tentelometer, Made in U.S.A) 	VFK0190 ; Reel Table Height Fixture 	VFK0950 ; Centering Fixture 
VFK0133 ; Dial Torque Gauge VFK0180 ; Plastic Clamper Only  0133 0180	VFK0134 ; Adaptor for VFK0133 	VFK0326 ; Hex. Wrench Set (0.7, 0.9, 1.2, 1.5, 1.6, 2, 2.4, 3 mm) 
VFK0236 ; Tension Post Adj. Plate 	VFK0806 ; Tension Sensor Adj. Fixture 	VFK27 ; Head Cleaning Stick 
VFK0269 ; L Type Screwdriver 	VFM0948 ; Check Light 	VFK66 ; Fan Type Tension Gauge 
VFK0680 ; S.C.R. Grease (White) (for plastic part) 	MOR265 ; Morlytone Grease (Black) (for metal part) 	VFK0906 ; High Quality Oil (for Capstan and P5 Post) Cleaning Liquid (Alcohol) (Tape Transport Rubber Parts etc.) << PURCHASE LOCALLY >>

6-3. HOW TO EJECT MANUALLY

If the electrical circuit is defective and the action of unloading and front unloading don't work properly, it is possible to eject manually as follows.

1. Take out the Main AC.
2. Release the direction as shown in Figure M3.
3. Release the Wormshaft to clockwise unit cassette is ejected.




Figure M3 How to Eject Manually

6-4. MAINTENANCE PROCEDURES

6-4-1. REGULAR MAINTENANCE

The purpose of periodic maintenance is to preserve the functioning of this machine throughout its useful life. The user or service dealer should perform these maintenance regularly to ensure that maximum utility is obtained from the machine.

The VCR is a complicated piece of equipment. It contains many belts, rollers, heads etc., which become worn, and deteriorate as time goes by, causing trouble. Dust and dirt will also impede the proper functioning of the machine. In light of this, it is very important that overall maintenance be done according to the maintenance chart to maintain the functions of the VCR, and to avoid accidental problems. This maintenance should also be performed after any repairs are done on the equipment.

The VCR used for business applications requires particular attention for several reasons. The installation conditions and applications are not always the best. Long use times, or poor environmental conditions may adversely affect the lifespan and performance of the machine. Regular maintenance assures that the purchaser obtains the maximum value for his expenditure. Accordingly, the necessity of regular maintenance should be fully explained at the time of sale, as well as during after-sale repairs.

6-4-2. MAINTENANCE CHART

The following periodic maintenance is required to prolong the life of the machine.

Ref. No. IN P/L	Parts Name	Hour										Ref. No. IN P/L	Parts Name	Hour									
		500	1000	1500	2000	2500	3000	3500	4000	4500	5000			500	1000	1500	2000	2500	3000	3500	4000	4500	5000
	Tape Transporter	●	●	●	●	●	●	●	●	●	●	2-1	Worm Shaft								▲		
1-7	Loading Motor U								◎			2-2	Loading Belt				◎				◎		
1-19	A/C Head U	●	●	●	●	●	●	●	◎	●	●	2-3	Worm Wheel								▲		
1-25	Pressure Roller U	●	●	●	◎	●	●	●	◎	●	●	2-8	Stator Base Unit								◎		
1-36	Mode Switch								◎			2-16	Main Brake (S)				◎				◎		
1-39	P5 Arm U								▲			2-18	Main Brake (T)				◎				◎		
1-41	Upper Cylinder	●	◎	●	◎	●	◎	●	◎	●	◎	2-23	Takeup Reel Table U								◎		
1-42	Lower Cylinder U	●	●	●	●	●	●	●	◎	●	●	2-24	Supply Reel Table U								◎		
1-45	Inclined (T) U								▲		◎	2-28	Capstan Rotor U	●	●	●	△	●	●	●	△	●	●
1-48	Inclined (S) U								▲		◎	2-33	Main Cam Gear								▲		
1-56	FE Head	●	●	●	●	●	●	●	◎	●	●	2-39	Loading Cam Gear								▲		
1-66	Head Cleaning U		◎		◎		◎		◎		◎												

*NOTE :

Symbol	Maintenance	Requirement	Remark
●	Cleaning	Ethyl-alcohol or Cleaning Liquid (Purchase locally)	Wipe dirt from the parts using soft cloth impregnated with Ethyl-Alcohol. Note: When cleaning rubber parts, avoid using excessive alcohol since it may accelerate deterioration of these parts. After cleaning with alcohol, wipe the alcohol quickly and thoroughly.
◎	Replacement		
△	Lubrication	High Quality Spindle Oil (Purchase locally)	Supply one or two drops of oil.
▲	Greasing	Molytone Grease (MOR265)	Wipe the old grease and apply new grease.
×	Greasing	S.C.R. Grease (VFK0680)	Wipe the old grease and apply new grease.

6-4-3. LUBRICATION PROCEDURES OF THE CAPSTAN SHAFT

1. Remove the Pressure roller Unit.
2. Remove the Thrust Screw.
3. Apply two drops of the oil (VFK0906) on the top of Capsutan Shaft as shown in Fig M6-A.





Figure M6-A


4. Turn the Thrust Adjustment Screw slowly to clockwise until the Capstan Rotor just starts turning (separate from the Capstan Stator).
5. Turn the Thrust Adjustment Sscrew another 180° clockwise as shown in Figure M6-B.
6. Install the Pressure Roller Unit.
7. Wipe the extra oil.



FiguerM6-B

6-4-4. PROCEDURES FOR CLEANING OF THE CYLINDER UNIT

1. Position the Video Head to permit access for cleaning and hold the upper cylinder to keep it from turning while cleaning.
 2. Gently rub the Video Head in direction of tape travel with Head Cleaning Stick moistened with Cleaning.
 3. Repeat for the other video heads (FigureM7).
- Note: 1.Do not rub vertically.
2.Do not apply any pressure to heads.



FigureM7

6-4-5. ADJUSTMENTS AFTER RE-INSTALLING THE UPPER CYLINDER, LOWER CYLINDER

AFTER RE-INSTALLING THE UPPER CYLINDER OR LOWER CYLINDER

6-6-3. FINE ADJUSTMENT OF THE TAPE GUIDE POST HEIGHT (P2 AND P3) LINEARITY

7-3-2. TRACKING FIX ADJUSTMENT

6-6-6. COARSE ADJUSTMENT OF THE A/C HEAD HORIZONTAL POSITION (X-VALUE)

6-6-7. FINE ADJUSTMENT OF THE A/C HEAD HORIZONTAL POSITION (X-VALUE)

7-3-1. PG SHIFTER ADJUSTMENT

7-4-5. CHROMA REC CORRENT ADJUSTMENT

7-4-6. S-VHS Y REC CURRENT ADJUSTMENT

7-4-7. VHS Y REC CURRENT ADJUSTMENT

7-5-1. PB RF CHROMA LEVEL ADJUSTMENT

7-5-2. PB Y LEVEL ADJUSTMENT

7-5-3. S-VHS NORMAL EQUALIZER ADJUSTMENT

7-5-4. S-VHS SS EQUALIZER ADJUSTMENT

7-5-5. VHS EQUALIZER ADJUSTMENT

7-5-6. VIDEO TRACKING METER ADJUSTMENT

7-7-11. Hi-Fi AUDIO HEAD SWITCHING SHIFTER ADJUSTMENT

7-5-15. Hi-Fi AUDIO REC CURRENT ADJUSTMENT

7-8-3. FLYING ERASE CORRENT ADJUSTMENT

6-4-6. ADJUSTMENTS AFTER RE-INSTALLING THE A/C HEAD UNIT

AFTER RE-INSTALLING THE A/C HEAD UNIT

MECHANICAL ADJUSTMENT

6-6-5. ADJUSTMENT OF A/C HEAD

- A. COARSE ADJUSTMENT OF THE A/C HEAD HEIGHT
- B. COARSE ADJUSTMENT OF THE A/C HEAD TILT
- C. ADJUSTMENT OF THE A/C HEAD AZIMUTH
- D. ADJUSTMENT OF THE A/C HEAD TILT & AZIMUTH
- E. ADJUSTMENT OF LOOK SCREW
- F. FINE ADJUSTMENT OF THE A/C HEAD HEIGHT

6-6-3. FINE ADJUSTMENT OF THE TAPE GUIDE POST HEIGHT (P2 AND P3) LINEARITY

6-6-6. COARSE ADJUSTMENT OF THE A/C HEAD HORIZONTAL POSITION (X-VALUE)

6-6-7. FINE ADJUSTMENT OF THE A/C HEAD HORIZONTAL POSITION (X-VALUE)

7-7-5. NORMAL AUDIO PLAYBACK FREQUENCY RESPONSE ADJUSTMENT

7-7-6. NORMAL AUDIO PB GAIN ADJUSTMENT

7-7-7. NORMAL AUDIO ERASE CURRENT ADJUSTMENT

7-7-8. NORMAL AUDIO BIAS CURRENT ADJUSTMENT

7-7-14. NORMAL AUDIO REC CURRENT ADJUSTMENT

6-5. MECHANICAL PARTS REPLACEMENT PROCEDURES

6-5-1. REPLACEMENT OF THE UPPER CYLINDER UNIT

1. First remove two screws as shown in Figure M10-A. Then unsolder of the soldered portions indicated by arrows on the Upper Cylinder, and finally remove the Upper Cylinder.

Note: Soldered portion can be easily removed by using solder sucking wire, etc.




Figure M10-A

2. The Upper Cylinder unit can be reinstalled by reversing the removal procedure. However, when Upper Cylinder is installed, be extremely carefully so that white portion of P.C.Board of Upper Cylinder correctly matches the white portion of bottom cylinder as shown in Figure M10-A.

Note: If the Upper Cylinder Unit is reversal installed, no color will appear when playing back pre-recorded tapes.




Figure M10-B

6-5-2. REPLACEMENT OF THE LOWER CYLINDER UNIT

1. Unscrew the 2 screws and remove the Head Amp.
2. Remove the Cleaning rod from bottom side.
3. Unscrew 3 screws (A). Since there is very little clearance between DD Cylinder (Lower Cylinder) Unit and Chassis, remove the Cylinder gently and carefully (Figure M11).




Figure M11

4. Reinstall the new DD Cylinder (Lower Cylinder) Unit in the chassis, tighten the 3 screws (A). Then connect a connectors and reinstall the Cleaning Rod.
5. Re-install the Head Amp C.B.A.

Note: After reinstall the Upper Cylinder Unit should be perform Mechanical and Electrical adjustment (Refer to 3-4-5. Maintenance Procedures).

6-5-3. REPLACEMENT OF THE A/C HEAD (1) UNIT

1. Disconnect a connector (H)(Figure M12).




Figure M12

2. Unscrew 3 (B)(C)(D) screws with spring and then remove the A/C Head Unit (Figure M12).
3. The A/C Head (1) Unit can be reinstalled by reversing the removal procedure.

Note: After reinstall the Upper Cylinder Unit should be perform Mechanical and Electrical adjustment (Refer to 6-4-6. Maintenance Procedures).

6-5-4. REPLACEMENT OF THE FULL ERASE HEAD

1. Disconnect a connector (J) and unscrew a screw (E) and remove the Full Erase Head (Figure M13).




Figure M13

3. The new Full Erase Head can be reinstalled by reversing the removal procedure.

6-5-5. REPLACEMENT OF THE CAPSTAN ROTOR & STATOR

When replacing the Capstan stator unit the Center Fixing Tool must be used to fix the center of Capstan Stator Unit.

1. Remove the loading belt.
2. Unscrew the 4 (F) screws and remove Gear base Unit.
3. Carefully lift up the capstan rotor from the capstan housing, taking care so as not loose the 2 oil seals as shown in Figure M14-A.




Figure M14-A

4. Remove the 2 oil seals.
5. Unscrew the 3 (G) screws and remove Capstan Stator.
6. Place the capstan stator unit into position.
7. Loosely tighten the 3 (G) screws.
8. Insert the Center Fixing Tool as shown in Figure M14-B.




Figure M14-B

9. Tighten the 3 screws (G).
10. Remove the center fixing tool.
11. The new capstan rotor unit can be reinstalled by reversing the removal procedure.




Figure M14-C

6-5-6. REPLACEMENT OF THE CAPSTAN HOUSING UNIT

1. Remove the pressure Roller Unit.
2. Remove the Sub post spring from the hook of Capstan Housing.
3. Unscrew the 3 screws (H) and remove Capstan Housing.
4. Remove the 2 oil seals and thrust screw.
5. Replace the new Capstan Housing, 2 oil seals and thrust screw at same time.
6. Re-install the Capstan Housing Unit by reversing the remove procedure.

Note: After re-installing the thrust screw adjustment of the thrust screw are required. Replace the new Capstan Rotor, 2 oil seals and thrust screw at same time. After re-installing the capstan rotor or capstan stator confirmation of FG out put level and adjustment of FG head gap are required.




Figure M15

6-5-7. REPLACEMENT OF THE INCLINED BASE (S),(T)

《SUPPLY SIDE》

1. Unscrew a screw (I) and remove the head cleaning plate unit as shown in Figure M16-A.
2. Unscrew the 2 screws (J) and remove the post stopper.




Figure M16-A

3. Remove the P2 post unit from loading arm (S) as shown in Figure M16-B.




Figure M16-B

4. Pull out the Inclined base (S) from loading base.
5. The new inclined base unit can be reinstalled by reversing the removal procedure.

Note: Install post stopper pushing the arrow direction (A), (B) as shown in Figure M16-A. After re-installing the inclined base (S) confirmation of tape interchangeability and P2, P3 posts adjustments are required.

《TAKE-UP SIDE》

1. Unscrew a screw (K) and remove the inclined base (T) as show in Figure M16-C.
2. Install the inclined base (T) so that the tip of inclined base is center on the Plate Hole and then tighten screw (K).

Note: After re-installing the inclined base (T) confirmation of tape interchangeability and inclined base adjustment are required.




Figure M16-C

6-5-8. REPLACEMENT OF THE P5 POST

1. Remove the top cover and cassette holder.
2. Rotate the loading motor to clockwise, until the stop mode.
3. Remove the pressure roller unit.
4. Remove the pinch cam (Ref. to Replacement of the mode switch) and P5 pull out sector gear as shown in Figure M17.




Figure M17

5. Unscrew a Nut (A) and Remove the P5 Post.
6. The new P5 post can be reinstalled by reversing the removal procedure.

Note: After-reinstalling the P5 post confirmation of tape waving and P5 post height adjustment are required.

6-5-9. REPLACEMENT OF THE REELUNIT

1. Remove 6 screws (L) and carefully lift the DD Reel Unit.
2. Disconnect a connector.




Figure M18-A

3. The Reel Motor Unit can be re-installed by reversing the removal procedure.




Figure M18-B

Note: When assembling the DD Reel Motor Unit, side the Main Rod to far left side by rotating a center Gear.

6-5-10. REPLACEMENT OF THE MAIN BRAKE (S),(T) UNIT

1. Remove the Reel Unit (Refer to Replacement of the Reel Unit).
2. Remove a Retaining Ring (A).
3. Remove the Main Brake (S),(T) with a spring.




Figure M19

4. The new Main Brake (S),(T) Unit can be reinstalled by reversing the removal procedure.

Note: When assembling the DD Reel Motor Unit, slide the Main Rod to far left side by rotating a Center Gear (Figure M19).

6-5-11. REPLACEMENT OF THE PRESSURE ROLLER UNIT

1. Place the deck in or EJECT mode.
2. Remove the Pinch Can Cap.
3. Remove the Pressure Roller Unit.




Figure M20

4. The new Pressure Roller Unit can be re-installed by reversing the removal procedure.

6-5-12. REPLACEMENT OF THE MODE SWITCH

1. Place the deck in the STOP mode.
2. Remove the Cassette Compartment Unit. (Refer to Disassembly Procedures).
3. Remove the Pinch Cam Cap and Pressure Roller Unit.
4. Unscrew the 2 screws and remove the Head Amp.
5. Remove the Pinch Cam.
6. Unscrew 2 screws (M) and remove the Loading Motor Base.
7. Unscrew a screw (N) and unsolder 5 of soldered portions.
8. Finally remove the Mode Switch.




Figure M21-A




Figure M21-B

9. Install a Mode Switch and tighten screw (N), then solder 5 soldering portions.
10. Install the Pinch Cam and Pressure Roller Unit. (Refer to "Assembly Procedures of Pinch Cam & Pressure Roller Unit.")
11. Install the Loading Motor Base and tighten screw (M).
12. Install the Head Amp and tighten 2 screws.
13. Install the Cassette Compartment. (Refer to Reinstallation of Cassette Compartment.)

6-5-13. REPLACEMENT OF THE PINCH SOLENOID

1. Unscrew 2 screws (M) and remove the Loading Motor Base (Figure M21-A).
2. Unscrew 2 screws (O), Remove the Motor Pulley and Loading Motor (Figure M22-A).
3. Disconnect a connector (red) on the Motor Base C.B.A.
4. Unscrew 2 screws (P)(Figure M22-B) and remove the Pinch Solenoid.
5. Install the Pinch Solenoid on to the Motor Base so that the hole of the Motor Base should be the large hole of the Solenoid Base (Figure M22-C).
6. Tighten 2 screws (P).
7. Install a Loading Motor and tighten 2 screws (O).
8. Install the Loading Motor Base and tighten 2 screws (M)(Figure M21-A).




Figure M22-A




Figure M22-B




Figure M22-C

Note: Pressure Adjustment of the Pinch Roller (Refer to Mechanical Adjustment procedures) should be performed after completion of reinstalling the Pinch Solenoid.

6-5-14. REPLACEMENT OF THE HEAD CLEANING PAD

1. Remove a Cut Washer (N) and the Head Cleaning Pad Unit.
2. The Head Cleaning Pad Unit can be reinstalled by reversing the removal procedure.





Figure M23

6-6. MECHANICAL ADJUSTMENT PROCEDURES

6-6-1. FLOW CHART OF TAPE INTERCHANGEABILITY ADJUSTMENT



6-6-2. COARSE ADJUSTMENT OF THE TAPE GUIDE POST HEIGHTS (P2 and P3)

Note: The Tape Guide Posts have been precisely adjusted at the factory. Therefore, normally do not change the height of the P2 and P3 Posts.

To prevent the alignment tape from being damaged, use a normal cassette tape for this procedure.

<< TOOL >>

Post Adjustment Plate	VFK1012
Reel Table Height Gauge	VFK0190
Post Adjustment Screwdriver	VFK0329
Check Light	VFK0948
L Type Screwdriver	VFK0269

1. Remove the cassette compartment (Refer to Disassembly Procedures).
2. Place the Post Adjustment Plate over the reel tables. Confirm that the Post Adjustment Plate is firmly seated as shown in Figure M25-A.




Figure M25-A

3. Lower 2 tape guide posts (P2 and P3) by turning the Post Adjustment screwdriver so that the condition of post becomes as shown in Figure M25-B. That is the lower edge of Tape guide should be lower than surface of AdjustmentPlate.




Figure M25-B

Note: Before turning P2 and P3 slightly loosen the Lock Screw using the L Type Screwdriver.

4. Place the scraper of Reel Table height Gauge as shown in Figure M25-C.
Set the gauge to zero, then raise the post slowly until the

lower tape guide just touches the bottom of the scraper. Use the gauge to determine the exact point at which the lower tape guide touches the scraper.




Figure M25-C

5. After the adjustment, install the cassette compartment referring to Reinstallation of cassette compartment.
6. Play back the beginning portion of NV-T160 cassette tape, and confirm that tape travel as shown in Figure M25-D.




Figure M25-D

7. Make sure that the edges of the tape are not curling or waving at the bottom or top end of the posts P2, P3 by using the Check Light.
8. If there are waving or filling at the lower or upper edge of the P2 and P3 posts, readjust the heights of P2 and P3 Posts correctly as shown in Figure M25-E.




Figure M25-E

9. And confirm that the tape runs along the Cylinder Lead Correctly.

6-6-3. FINE ADJUSTMENT OF THE TAPE GUIDE POST HEIGHT (P2 and P3)(LINEARITY)

<< TOOL >>

Alignment Tape VFM8080HQFP

Post Adjustment ScrewdriverVFK0329

Note: Before playing back the alignment tape playback a normal cassette tape and confirm correct transport.

1. Connect the oscilloscope to the TP2 of the Video I/O C.B.A. (Video RF Envelope and the head switching pulse as a triggering signal).
2. Play back the 2-nd portion (Monoscope 2) of the alignment tape (VFM8080HQFP).
3. Adjust the tracking control on the front panel so that the RF envelope becomes maximum.
4. If the RF envelope appears like example A or B in Figure M26-B then adjustment of the tape guide post (P2 ; Entrance) is necessary.




Figure M26-A




Figure M26-B




Figure M26-C

5. Adjust the tape guide post (P2) with the post adjustment screwdriver so that the RF envelope waveform at the entrance portion becomes flat as shown in Figure M26-B.
6. If the RF envelope appears like example D or E in Figure M26-C, then adjustment of the tape guide post (P3 ; Exit) is necessary.
7. Adjust the tape guide post (P3) in the same manner as the P2 post so that the exit portion becomes flat as shown in Figure M26-C.
8. The output envelope should vary nearly parallel with other condition as shown in Figure M26-D.




Figure M26-D

9. If the RF envelope does not meet these specification,

$$V1/V0 \geq 0.7$$

$$V2/V0 \geq 0.8$$

$$V3/V0 \geq 0.7$$

then repeat steps 4-9 again.




Figure M26-F

6-6-4. ADJUSTMENT OF THE PULL-OUTPOST (P5) HEIGHT

<< TOOL >>

Post Adjustment PlateVFK1012

Reel Table Height GaugeVFK0190

Nut DriverPurchase locally

<< SPEC >>

0.03mm 0.01mm

Note: Unless the replacement or adjustment this post is required, the adjustment nut should not be turned.

1. Remove the cassette compartment (Refer to Disassembly procedures).
2. Place the Post Adjustment Plate over the reel tables as shown in Figure M27-A.
3. Turn the Worm Shaft counterclockwise (loading direction) until the mechanical condition becomes as shown in Figure M27-A.
4. Place the Reel Table Height Gauge on the Post Adjustment Plate and set the gauge to zero 0 as shown in Figure M27-B.




Figure M27-A

5. Place the Reel Table Height Gauge as shown in Figure M27-C and turn the nut slowly until the gauge reads.




Figure M27-B




Figure M27-C




Figure M27-D

Note: There is easy method to check Waving of Filling. If there is Waving or Filling in the lower edge, the white black pattern which is reflected on the tape will curve or not linear as shown in Figure M27-E.




Figure M-27-E

6-6-5. ADJUSTMENT OF THE A/C HEAD

A. COARSE ADJUSTMENT OF THE A/C HEAD HEIGHT

Note: This procedure should be performed only when the A/C Head is replaced.

<< TOOL >>

Check LightVFK0948
Nut DriverPurchase locally
VHS video Tape

1. With the tape running, look at the lower edge of the control head by using the check light.
2. Adjust the Nut (A) as shown in Figure M28-A by turning the Nut (A) clockwise to lower the head, and counterclockwise to raise it.




Figure M28-A

6. After the adjustment, install the cassette compartment (Refer to reinstallation of Cassette Compartment).
7. Play back a normal cassette tape on Review search mode, and make sure that the edges of the tape are not curling or waving at the bottom end of the P4 post by using the Check Light as shown in Figure M27-E.

B. COARSE ADJUSTMENT OF THE A/C HEAD TILT

Note: This procedure should be performed only when the A/C Head is replaced or posts heights are readjusted.

<< TOOL >>

Alignment Tape VFM8080HQFP
 Check LightVFK0948
 Screwdriver (+) Purchase locally
 VHS Vide Tape

1. Play back a VHS video tape which the amount of tape winding of a Take up Reel, Turn a screw (B) to clockwise until waving or Filling appears in the Lower edge of P4 post as Figure M28-B.

Note: There is easy method to check waving or Filling if there is waving or Filling in the lower edge. ZEBRA pattern which is reflected on the tape will curve or not linear (Figure M27-D).

2. Turn the screw (B) to counter-clockwise until waving or filling do not appear in the in the lower edge of P4 post.




Figure M28-B

C. ADJUSTMENT OF A/C HEAD AZIMUTH

1. Connect the scope CH1 to TP40005 (Normal Audio out put CH1) and the scope CH2 to TP40007 (Normal Audio output CH2) on the Rear Jack.
2. Play back the 2-nd portion (Normal Audio 10KHz) of the alignment tape (VFM8080HQFP).
3. Adjust the screw (C) so that these phases of both channels match as shown in Figure M28-C.




Figure M28-C

D. TILT and AZIMUTH ADJUSTMENT OF A/C HEAD

1. Adjust the screw (C) and (B) so that CH1 and CH2 output levels become maximum, these phase of both channels much at the same time (Figure M28-D). During this adjustment the Lock screw (D) dose not touch the A/C Head Base as shown in Figures M28-E.




Figure M28-D




Figure M28-E

E. ADJUSTMENT OF LOCK SCREW

1. Turn the screw (C) to clockwise so that the difference of phase of both channels become 180 degrees as shown in Figure M28-F.
2. Tighten the Lock screw (D) so that these phase of both channels match as shown in Figure M28-F.




Figure M28-F

F. FINE ADJUSTMENT OF A/C HEAD HEIGHT

Note: Before this adjustment Coarse Adjustment of the A/C Head Height should be performed.

<< TOOL >>

Alignment Tape VFM8080HQFP
Nut DriverPurchase locally

1. Connect a scope CH1 to TP40005 (Normal Audio output CH1) and the scope CH2 to TP40007 (Normal Audio output CH2) on the Rear Jack C.B.A.
2. Play back the 2-nd portion (Normal Audio 10kHz) of the Alignment Tape (VFM8080HQFP).
3. Adjust the Nut (A)(Figure M28-A) so that the CH2 output level becomes maximum as shown in Figure M28-G.




Figure M28-G

6-6-6. COARSE ADJUSTMENT OF THE A/C HEAD HORIZONTAL POSITION (X-VALUE)

Note: This procedure should be performed only when the A/C head is replaced, and after performing the tape interchangeability adjustment.

<< TOOL >>

H-Position Adjustment ScrewdriverVFK0328
Alignment Tape VFM8080HQFP

1. Connect a scope CH1 to Video RF Test Terminal (TP2 of the Video I/O C.B.A.) and a scope CH2 to Normal Audio CH2 output on the Rear Jack.
2. Play back the 4-the position (Monoscope 3 and Audio/Every 10-the field is skipped) of the Alignment tape VFM8080HQFP.
3. Adjust the A/C head horizontal position screw so that the phase of audio drop out and video RF envelope drop-out becomes the same as shown in Figure M29.




Figure M29

Note: After completion the fine adjustment of the A/C head horizontal position, the phase of Audio drop-out and Video RF envelope drop-out may be changed slightly.

6-6-7. FINE ADJUSTMENT OF THE A/C HEAD HORIZONTAL POSITION (X-VALUE)

Note: This procedure should be performed only when the A/C head is replaced, and after performing the tape interchangeability adjustment.

<< TOOL >>

H-Position Adjustment ScrewdriverVFK0328
Alignment Tape VFM8080HQFP

1. Set the Tracking Control VR to the center fix position.
2. Connect a oscilloscope to Video RF Test Terminal(TP2 of the Video I/O C.B.A.).
3. Play back the 2-nd portion (Monoscope 2) of the alignment tape (VFM8080HQFP).
4. Adjust the Horizontal Position Screw (Figure M29) of A/C head so that the RF signal becomes maximum level as shown in Figure M30.




Figure M30

6-6-8. ADJUSTMENT OF INCLINED BASE (T)

<< TOOL >>

Check LightVFM0948
Screwdriver (+) Purchase locally
VHS Video Tape

1. Play back the beginning portion of 120 minute normal cassette tape and confirm that waving or filling of P3 post is as shown in Figure M31-A.




Figure M31-A

2. If there are waving at the lower and upper edge of the P3 post, Adjust the inclined base of P3 post as shown in Figure M31-B.




Figure M31-B

[When the inclined base is adjust to an arrow direction (B) tape becomes to lower edge.]

3. Confirm that tape position P3 post is upper edge and then tighten screw as shown in Figure M31-B.
4. Confirm that waving is occurred between upper side of P3 post and A/C head. If there is waving adjust step 2.

Note: After adjust inclined base tape interchangeability and A/C head adjustment must be required.

6-6-9. ADJUSTMENT OF THRUST GAP

1. Turn the thrust adjustment screw clockwise to until the capstan rotor just separate from the capstan stator whit rotating the capstan rotor by hand.
2. Turn the thrust adjustment screw clockwise to 180 degrees from paint at step 1.

3. Set the 2 oil seal to edge of the capstan housing as shown in Figure M32.




Figure M32

6-6-10. ADJUSTMENT OF FG GAP

<< TOOL >>

Fine Adj. screwdriver.....VFK0330
ScrewdriverPurchase locally

<< SPEC >>

0.13mm 0.02mm

1. Loosen screw (Q) and set the Fine Adjustment screw driver in the hole on the Capstan Stator Unit.
2. Adjust the gap between FG head and the Capstan Stator unit.
3. After adjustment tighten a screw (Q).




Figure M33-A

Note: After adjust FG head gap, FG output level confirmation must be required.
Do not touch the surface of rotor and keep any magnetizable material away.

CONFIRMATION OF FG OUTPUT LEVEL

1. Connect a oscilloscope to TP8009 (CAP FG output) on the Video 3 C.B.A.
2. Confirm that FG output level is within specification during PLAY/REC or PLAY mode.
3. If FG output level is out of specification Readjust the step 1 to 3 of FG GAP Adjustment.




Figure M33-B

6-6-11. MEASUREMENT AND ADJUSTMENT OF BACK TENSION

<< TOOL >>

Back Tension MeterVFK0132
VHS Cassette Tape (120min. tape except S-VHS tape)

A. FWD TENSION ADJUSTMENT

<< SPEC >>

23g ~ 27g

1. Play back the cassette tape from the beginning and wait until the tape movement get the stabilization (for approx. 10 to 20 seconds).
2. Pull the Impedance Roller in the direction indicated the arrow in Figure M34-A secure it with a piece of adhesive tape.
3. Insert the Back Tension Meter into the path of a tape, and measure the back tension.
4. If it is out of specification, replace the Tension spring.




Figure M34-A

B. REV TENSION ADJUSTMENT

<< SPEC >>

30g ~ 60g

1. Play back the cassette tape on SP Reverse Play mode from the beginning and wait until the tape movement get the stabilization (for approx. 10 to 20 seconds).
2. Pull the Impedance Roller in the direction indicated by the arrow in Figure M34-A secure it with a piece of adhesive tape.
3. Insert the Back Tension Meter into the path of a tape, and measure the back tension.
4. If it is out of specification, replace the Tension spring.

Note: While measuring, make sure that the three probes of the meter are all in good contact with the tape. As the tension meter is very sensitive, we recommend taking 3 separate readings.




Figure M34-B

6-6-12. HEIGHT ADJUSTMENT OF THE REEL TABLES

<< TOOL >>

Post Adjustment PlateVFK1012
Reel Table Height GaugeVFK0190

<< SPEC >>

0 ~ 0.15mm

1. Remove the cassette compartment.
2. Place the post Adjustment Plate on the reel tables.
3. Place the Reel Table Height Gauge on the plate so that the scraper of the gauge touches the cut-out portion of the plate, then set the gauge to zero 0 as shown in Figure M35-A.




Figure M35-A

4. Measure the height of the top surface of either Reel table and note the difference in height from the plate cut-out (Figure M35-A and M35-B). Repeat this procedures for the other Reel Table.




Figure M35-B

5. If the difference of Supply Reel table is more than 0.15mm higher or lower, replace the Supply Reel table. When the difference of Take Up Reel table is more than 0.15mm higher or lower, adjust nut (A) (Figure M35-C) so that measurement becomes the spec. If you can not adjust to the spec., replace Take Up Reel table.




Figure M35-C




Figure M35-D




Figure M35-E

Note: When replacing the tables, the DD Reel Unit needs to be removed from the chassis. Remove 6 screws and carefully lift it out as shown in Figure M35-D. When assembling the DD Reel Unit, slide a Main Rod to far left side by rotating the Center Gear, and then screw the 6 screws.

6-6-13. MEASUREMENT AND ADJUSTMENT OF THE BRAKE TORQUE

<< TOOL >>

Torque GaugeVFK0133
Adaptor for GaugeVFK0134

1. Remove the top cover and the cassette compartment.
2. Attach the adapter to the torque gauge and place the deck in STOP mode (Sub loading mode).
3. Place the torque gauge on the reel table as shown in Figure M36-A. The weight of the gauge should not rest on the reel table.
4. Turn the torque gauge in the direction indicated in Figure M36-B until the brake begins slipping and read the gauge.




Figure M36-A




Figure M36-B

5. If it is out of specification, replace the Brake Spring.

Note: If the proper brake torque cannot be obtained by replacing the Brake Spring, clean the braking surface of the reel table with a soft cloth and re-measure the brake torque. If it's still out of specification, replace the Main Brake (S) or (T) Unit.

6-6-14. PRESSING FORCE CONFIRMATION OF PRESSURE ROLLER UNIT

<< TOOL >>

Fan Type Tension GaugeVFK66
VHS 120min, Cassette Tape

<< SPEC >>

1050g \pm 230g

1. Remove the Cassette Compartment.
2. Play back the end portion of VHS (120min.) tape.
3. Set the Fan Type Tension Gauge to the part (A) of Pinch Roller Unit.
4. Press the Arm with the Gauge, in the direction indicated by the arrow as show in Figure M37.
5. Adjust the Solenoid Base so that the reading of the Tension Gauge is 1050g \pm 230g at the moment of the tape running stop.
6. If it is out of specification, replace the Tension spring.




Figure M37

6-6-15. ADJUSTMENT OF REV TENSION SENSOR POSITION

<< TOOL >>

Tension Sensor Adj. Fixture.....VFK0806
Tension Post Adj. PlateVFK0236
Fine Adj. ScrewdriverVFK0330
Digital Volt Meter Purchase locally

<< SPEC >>

2.3V \sim 2.7V

Note: Assemble a Tension Sensor Adjustment Fixture (VFK0806) and a Tension Post Adj. Plate (VFK0236) as shown in Figure M38-A.




Figure M38-A

1. Remove the Top Plate and Cassette Holder Unit. (refer to Disassemble Procedures)
2. Disconnect the 4pin and 2pin flat wire to the pin 3 and 4 of the connector P1508.
3. Connect two wires of 4pin flat wire to the pin 3 and 4 of the connector P1508 as shown in Figure M38-B.




Figure M38-B

4. Push the Sub Wiper Arm (R) to direction of Cassette loading. Then the Sub Wiper Arm (R) goes down it self and mode of machine change to STOP.
5. Turn the Power switch off.
6. Remove the Cassette Compartment (refer to Disassembly Procedures).
7. Connect the V.T.V.M. of D.V.M. to TP2502 on the SERVO/SYSCON C.B.A.
8. Place the Tension Post Position Adjustment Plate with the Fixture over the reel tables as shown in Figure M38-C.




Figure M38-C

9. Turn the Power switch on.
10. Slightly loosen 2 screws (C). Insert a Fine Adj. Screwdriver in the hole (D)(Figure M38-D).




Figure M38-D

11. Press the PLAY button.
12. Adjust the Rev Sensor Position so that measurement becomes D.C. 2.3V~2.7V.
13. Tighten the 2 Screws (C).
14. Remove the Tension Sensor Fixture.
15. Reinstall the Cassette Compartment.
16. Confirm Playback picture (Rev Playback mode, Playback mode etc.)

6-7. ASSEMBLY AND ADJUSTMENT PROCEDURES OF MECHANISM

The mechanism of this model is mostly engaged to the System Control Circuit, through the mode select switch. Therefore the relation between the mode select switch and the cam gear decides all further mechanical movement of the mechanical parts such as levers, gears, rollers and so on. If these parts are not fixed properly, the unit will be unloaded or compulsorily stopped. And it will result being damaged at any mechanical or electrical parts. The overall mechanical condition (alignment) of bottom and top view are shown in Figure M39-A and Figure M39-B. This mechanical adjustment is performed in the STOP mode.

4. Identification hole on the Mode Select Switch at 6 o'clock position and aligned with small hole on Pinch Cam as shown in Figure M39-B.
5. P5 Arm is completely loading position and the Inclined Base (S) and (T) are completely unloading position.
6. Small hole on Sub Cam Gear should align with small hole on the Connection Gear and rectangular mark on the Connection Gear should be at a 3 o'clock position.
7. Pressure Roller Unit is UP position.

6-7-1. CONFIRMATION OF ALIGNMENT CONDITION

1. Remove the Loading Belt.
2. Unscrew 4 screws (F) and remove the Gear Base Unit. (Figure M39-A)
3. Turn the Center Gear to counter-clockwise until 2 big holes of Center Gear align with 2 big holes of Retainer Gear and Ring Gear and Chassis as shown in Figure M39-C.




Figure M39-A




Figure M39-B Top View of Overall IQ-Mechanical Condition




Figure M39-C Bottom View of Overall Mechanical Condition

6-7-2. ASSEMBLY PROCEDURES OF SUB CAM GEAR RING GEAR AND DETENT ARM

1. Install the Ring Gear so that the two holes on the Ring Gear align with the two holes on the chassis as shown in Figure M40.
2. Install the Sub Cam Gear so that the large hole on Sub Cam Gear aligns with the hole on chassis. Also the small hole (located just outside of large hole) on Sub Cam Gear should align with the hole on Ring Gear as shown in Figure M40.
3. Confirm that the small hole on Sub Cam Gear is aligned with the small hole on Connection Gear as shown in Figure M39-B (In case of the Connection Gear is already installed).
4. Install the Detent Arm and make sure Detent Arm seats perfectly in detent of Sub Cam Gear as shown in Figure M40.




Figure M40

6-7-3. ASSEMBLY PROCEDURES OF MAIN CAM GEAR AND PINCH SPEED DOWN GEAR

1. Install the Main Cam Gear on to the Sub Cam Gear so that the small hole on the Main Cam Gear aligns with small hole on the Ring Gear as shown in Figure M41.
2. Insert a retaining ring.
3. Install the Pinch Speed Down Gear from top side of chassis so that the small hole on the Main Cam Gear as shown in Figure M41.




Figure M41

6-7-4. ASSEMBLY PROCEDURES OF LOADING CAM GEAR AND RETAINER GEAR

1. Install the Retainer Gear onto the Ring Gear so that the two holes on the Retainer Gear align with the two holes on the Ring Gear, at this time, small hole on the Main Cam Gear should aligns with small hole on the Retainer Gear as shown in Figure M42.
2. Install the Loading Cam Gear so that the small hole which is directly outside of the large hole on the Loading Cam Gear is aligned with the outside hole of the Retainer Gear as shown in Figure M42.




Figure M42

6-7-5. ASSEMBLY PROCEDURES OF CENTER GEAR

1. Softly Install the Center Gear onto the Retainer Gear so that the two holes in the Center Gear align with the holes on the Retainer Gear, then install the cut washer as shown in Figure M43.




Figure M43

6-7-6. ASSEMBLY PROCEDURES OF MAIN LEVER AND CAM FOLLOWER ARM UNIT

1. Install the Main Rod and then insert the cut washers as shown in Figure M44.
2. Install the Cam Follower Arm so that the pin of the Cam Follower Arm inserts into the groove of the Main Cam Gear and also inserts into the slot on the Main Rod, insert the retaining ring.




Figure M44

6-7-7. ASSEMBLY PROCEDURES OF LOADINGGEAR (T), LOADING GEAR (S) SECTOR GEAR

1. Set the P2 and P3 posts to fully unloaded position, then install the Loading Gear (T) and (S) so that the outer hole on the Loading Gear (T) aligns with the outer hole on the Loading Gear (S) as shown in Figure M45-A.
2. Install the Sector Gear so that the outer hole in the Sector Gear aligns with the projection mark on Loading Gear (T).
3. Insert 3 retaining rings as shown in Figure M45-B.




Figure M45-A




Figure M45-B

6-7-8. ASSEMBLY PROCEDURES OF CONNECTION GEAR

Note: Before assembling, Sub Cam Gear position (and positions of bottom side gears) must be correct as described before (Figure M39-B).

1. Install the Connection Gear so that the small hole on the Connection Gear aligns with the small hole on the Sub Cam Gear as shown in Figure M46.




Figure M46

6-7-9. ASSEMBLY PROCEDURES OF MODE SWITCH AND P5 PULL OUT SECTOR GEAR

1. Turn the Center Gear to unloading position.
2. Install the mode Select Switch and tighten the mounting screw, then solder the 5 soldering portions.
3. Install the P5 Pull Out Sector Gear so that the hole of P5 Pull Out Sector Gear aligns with the tip of gear at P5 Arm as shown in Figure M47.




Figure M47

6-7-10. ASSEMBLY PROCEDURES OF PINCH CAM AND PRESSURE ROLLER UNIT

1. Install the Pinch Cam while pushing the P5 post forward. The gear of the Pinch Cam should drop to a seated position. In this position make sure hole in the Mode Select Switch aligns with small hole on the Pinch Cam, also the small rift on the Pinch Cam should align with the hole on the Pinch Speed Down Gear as shown in Figure M48.
2. Install the Pressure Roller Unit. Make sure the seats perfectly onto the Pinch Cam, then install the Pinch Cam Cap.




Figure M48

6-7-11. ASSEMBLY PROCEDURES OF GEAR BASE UNIT

1. Install the Gear Base Unit and screw 4 screws (F) as shown in Figure M49.




Figure M49

Note: The Gear Base Unit has 2 gears and worm shaft. There is no adjustment for these gears.

6-6-12. REINSTALLATION OF CASSETTE COMPARTMENT

When you reinstall the cassette compartment, the position adjustment of mechanism is necessary for correct operation, as follows.

A. Confirmation of STOP Alignment Condition

1. Turn the Worm shaft counter-clockwise or clockwise until mechanism is placed into the Alignment Condition as following conditions.
 - a) Identification hole on the Mode Select Switch at 6 o'clock position and aligned with small hole on Pinch Cam. (Figure M48)
 - b) P5 Arm is completely loading position and the Inclined Base (S) and (T) are completely unloading position.
 - c) Small hole on Sub Cam Gear should align with small hole on the Connection Gear (Figure M46) and rectangular mark on the Connection Gear should be at a 3 o'clock position.
 - d) Pressure Roller Unit is UP position.

B. Confirmation of Cassette Compartment

1. Confirm that the Cassette Compartment is aligned properly. In the EJECT position (Cassette Holder up and advanced to the front) the two V-shaped marks on the slide switch should align. The slide switch is located on the right side of the Cassette Assembly towards the rear as shown in Figure M50A.




Figure M50-A

2. Remove 3 screws (A) as shown in Figure M50-B.
3. Take the top plate out.
4. Take the cassette Holder unit out as shown in Figure M50-C.




Figure M50-B




Figure M50-C Removal of Cassette Holder Unit

5. Press the sub wiper arm (R) to direction indicated by arrow so that the sub wiper arm (R) comes to cassette down position (STOP) completely as shown in Figure M50-D and keep it. In this position, the arrow on the Sub Wiper Arm (R) should align with the arrow on the Rack (A)(1) Unit as shown in Figure M50-E.




Figure M50-D




Figure M50-E

6. If the Cassette Compartment is not aligned, realignment may be accomplished by pushing the Main Shaft Unit to the right (gently) and pushing the front of the Rack Unit to the left. This procedure will disengage the teeth of the Rack Gear from the teeth on Sub Wiper Arm assembly. This will allow you to change the positional relationship between the Sub Wiper Arm Assembly and Rack Unit. This procedure is best attempted in the EJECT position. Once this is done, check for smooth operation of the compartment by inserting a cassette, and pushing in, and down.

C. Installation Procedure

1. Bring loading mechanism to the STOP (Sub-load) position.
2. Confirm that the chassis is aligned properly for Alignment Condition as shown in Figure M39-B and M39-C.
3. Put the Sub Wiper Arm (R) in its full down position (Sub Wiper Arm should rest on plastic protrusion on the bottom of the right side plate).
4. Install the cassette compartment (without cassette holder) to chassis so that the rectangular marking (or slot) on the connection gear should be line up with first tooth of the Rack Gear as shown in Figure M50-F and M50-G.




Figure M50-F




Figure M50-G




Figure M50-H

5. Tighten the 4 screws (D) as shown in Figure M50-H.
6. Manually move the loading mechanism toward the EJECT position.
7. Stop the manual eject procedure just before completion, so that the Sub Wiper Arms straight up. This position is also characterized by the channel guides (in the Wiper Arms) being directly under the cut outs on the top of the Cassette Compartment base (Figure M50-I).
8. Install the Cassette Holder Unit in the Cassette Compartment Base. The Cassette holder should drop into place if the Sub Wiper Arms are positioned as called for in step 7.




Figure M50-I

Note: For proper front loading, the guide pin on the opener lever should follow the upper track of the right side panel as shown in Figure M50-J.




Figure M50-J Right Side Plate

9. Install the top plate on the Cassette Compartment Base and tighten the 3 screws (A) as shown in Figure M50-B.
10. Manually confirm that front loading and main loading run smoothly. Also confirm EJECT before power is applied.

MEMO

SECTION 7

ELECTRICAL ADJUSTMENTS

CONTENTS


7-1. TEST & SERVICE EQUIPMENT	7-4
7-2. HOW TO READ THE ADJUSTMENT PROCEDURE TABLE	7-4
7-3. SERVO SECTION	7-5
7-3-1. PG Shifter Adj.	7-5
7-3-2. Tracking Fix Adj.	7-5
7-4. VIDEO REC SECTION	7-5
7-4-1. Drop Out Level Adj.	7-5
7-4-2. RF Peak Frequency Adj.	7-6
7-4-3. CPS Input Level Adj.	7-6
7-4-4. S-VHS Deviation Adj.	7-6
7-4-5. Chroma Rec Current Adj.	7-7
7-4-6. S-VHS Y Rec Current Adj.	7-7
7-4-7. VHS Y Rec Current Adj.	7-7
7-4-8. Video Level Meter Adj.	7-8
7-5. VIDEO PB SECTION	7-8
7-5-1. PB RF Chroma Level Adj.	7-8
7-5-2. PB Y Level Adj.	7-8
7-5-3. S-VHS Normal Equalizer Adj.	7-8
7-5-4. S-VHS SS Equalizer Adj.	7-9
7-5-5. VHS Equalizer Adj.	7-10
7-5-6. Video Tracking Meter Adj.	7-10
7-6. TBC SECTION	7-10
7-6-1. Y A/D Input (1) Adj.	7-10
7-6-2. Y A/D Input (2) Adj.	7-10
7-6-3. Y Output Level Adj.	7-11
7-6-4. Sync Level Adj.	7-11
7-6-5. C A/D Input (1) Adj.	7-12
7-6-6. C A/D Output Level Adj.	7-12
7-6-7. C A/D Input Adj.	7-12
7-6-8. E-E Chroma Adj.	7-12
7-6-9. CAC PR Level Adj.	7-13
7-6-10. CAC PB Level Adj.	7-13
7-6-11. Edit Chroma Adj.	7-14
7-6-12. Normal Chroma Adj.	7-14
7-6-13. Carrier Balance Adj.	7-14
7-6-14. Burst Level Adj.	7-15
7-6-15. Chroma Vector Balance Adj.	7-15
7-6-16. Burst Phase Adj.	7-16
7-6-17. Burst Position Adj.	7-16
7-6-18. Y/C Timing Adj.	7-16
7-6-19. PB S-VHS Y/C Delay Adj.	7-17
7-6-20. PB VHS Y/C Delay Adj.	7-17
7-6-21. Normal Y/C Timing Adj.	7-17
7-6-22. CAC Y/C Timing Adj.	7-18
7-6-23. Y Clock Phase Adj.	7-18
7-6-24. PLL Lock Adj.	7-18
7-6-25. C Clock Phase Adj.	7-18
7-6-26. Head Switch Adj.	7-19
7-6-27. S/H Adj.	7-19
7-6-28. 14.3MHz VCO Adj.	7-19
7-6-29. Ref. SCH Adj.	7-20
7-6-30. SCH Phase Adj.	7-20
7-6-31. System H Phase Adj.	7-20
7-6-32. Video Phase Adj.	7-21
7-6-33. System SC Phase Adj.	7-21

7-7. AUDIO SECTION	7-22
7-7-1. Normal Audio Input Level Adj.	7-22
7-7-2. Hi-Fi Audio Input Level Adj.	7-22
7-7-3. Audio Jack Output Balance Adj.	7-22
7-7-4. Audio Level Meter Adj.	7-23
7-7-5. Normal Audio Playback Frequency Response Adj.	7-23
7-7-6. Normal Audio PB Gain Adj.	7-24
7-7-7. Normal Audio Erase Current Adj.	7-24
7-7-8. Normal Audio Bias Current Adj.	7-24
7-7-9. Normal Audio General Frequency Responce Adj.	7-25
7-7-10. Normal Audio Time Code Meter Adj.	7-25
7-7-11. Hi-Fi Audio Head Switching Shifter Adj.	7-25
7-7-12. Hi-Fi Audio Carrier Frequency Adj.	7-26
7-7-13. Hi-Fi Audio Deviation Adj.	7-26
7-7-14. Normal Audio Rec Current Adj.	7-27
7-7-15. Hi-Fi Audio Rec Current Adj.	7-27
 7-8. OTHER SECTION	 7-28
7-8-1. VITC Mute Pulse Adj.	7-28
7-8-2. OSD Character Width Adj.	7-28
7-8-3. Flying Erase Current Adj.	7-28

7-1. TEST & SERVICE EQUIPMENT

No.	EQUIPMENT	CAPACITY
1	D.V.M. (Digital Volt Meter)	0.001 to 50V
2	Dual-Trace Oscilloscope (with Probes)	0.005 to 50V/div, DC to 100MHz (50MHz)
3	Frequency Counter	0 to 10MHz
4	Sinewave Signal Generator (RC Oscillator)	0 to 10MHz
5	Video Sweep Generator	0 to 10MHz
6	Waveform Monitor	
7	Video Signal Generator (Composite, Y/C)	video signal with 7.5% set-up
8	Spectrum Analyzer	
9	Vector Scope	
10	SCH Meter	
11	Color Monitor TV	
12	VHS Alignment Tape (VFM8080HQFP)	
13	Extender Board (VFK0941)	

7-2. HOW TO READ THE ADJUSTMENT PROCEDURES TABLE



7-3. SERVO SECTION

7-3-1. PG SHIFTER ADJ.

« NOTE »

Tape Interchangeability Adjustment should be always completed before this adjustment.

BOARD	SERVO & SYSTEM CTL C.B.A. (E3)
TP	TP41003 (G-1):AUDIO (2) C.B.A.(CH2.TRIG) TP3307 (B-1):VIDEO I/O C.B.A.(CH1)
ADJ.	VR2001 (H-5)
TAPE	VFM8080HQFP PORTION:2
INPUT	
MODE	PLAYBACK
M. EQ	OSCILLOSCOPE
SPEC.	T=7.5H±0.25H

« SET UP »

SYNC : NORM (MENU NO.1001)
FRAME SERVO : OFF (MENU NO.6005)
TRACKING VR : CENTER (FIX)

1. Playback the adjustment tape the portion 2.
2. Connect the oscilloscope to TP3307 for CH-1 and TP41003 for CH-2.(Trigger)
3. Adjust VR2001 so that "T" becomes 7.5H ± 0.25H as shown in Figure E1.




Figure E1

7-3-2. TRACKING FIX ADJ.

BOARD	SERVO & SYSTEM CTL C.B.A. (E3)
TP	TP41003 (G-1):AUDIO (2) C.B.A. TP61004 (D-1):INTERFACE C.B.A.
ADJ.	VR2003 (H-6):SERVO&SYSTEM CTL C.B.A.
TAPE	VFM8080HQFP PORTION:2
INPUT	
MODE	PLAYBACK
M. EQ	OSCILLOSCOPE
SPEC.	T=0.4msec.±0.1msec.

« SET UP »

SYNC : NORM (MENU NO.1001)
FRAME SERVO : OFF (MENU NO.6005)
TRACKING VR : CENTER (FIX)

1. Playback the adjustment tape the portion 2.
2. Connect the oscilloscope to TP61004 for CH-1 and TP41003 for CH-2.
3. Adjust VR2003 so that the "T" becomes 0.4msec ± 0.1msec as shown in Figure E2.




Figure E2

7-4. VIDEO REC SECTION

7-4-1. DROP OUT LEVEL ADJ.

BOARD	VIDEO DIGITAL C.B.A. (E6)
TP	TP3772 (F-1)
ADJ.	VR3771 (F-1)
TAPE	S-VHS BLANK TAPE
INPUT	COLOR BAR SIGNAL (LINE)
MODE	REC
M. EQ	OSCILLOSCOPE (more than 100MHz)
SPEC.	700mVp-p±70mVp-p

« NOTE »

Use a oscilloscope that is more than 100MHz range and increase the intensity.

« SET UP »

IMAGE MODE SELECT : NORMAL (MENU NO.2001)
VIDEO MODE : COLOR (MENU NO.2002)
S-VHS REC : ON (MENU NO.2006)
CH2 METER SW : VIDEO TRACKING
VIDEO LEVEL control : PUSH (AGC : ON)
INPUT SW : LINE

1. Place the deck in the REC mode with S-VHS mode.
2. Connect the oscilloscope to TP3772.
3. Adjust VR3771 so that the level becomes 700mVp-p ± 70mV as shown in Figure E3.




Figure E3

7-4-2. RF PEAK FREQUENCY ADJ.

BOARD	VIDEO I/O C.B.A. (E5)
TP	TP3003 (F-1)
ADJ.	VR3015 (E-1)
TAPE	
INPUT	TP3002: VIDEO SWEEP SIGNAL (150mVp-p)
MODE	STOP
M. EQ	OSCILLOSCOPE
SPEC.	7MHz \pm 0.1MHz (FIG. E4-B)

≪ SET UP ≫

IMAGE MODE SELECT : EDIT (MENU NO.2001)

1. Connect a jumper wire between TP3001 and GND (TPG3001).
2. Supply a 150mVp-p (in connected) sweep signal to TP3002 as shown in Figure E4-A.
3. Connect the oscilloscope to TP3003 and adjust VR3015 so that the peak frequency becomes 7.0MHz \pm 0.1MHz as shown in Figure E4-B.




Figure E4-A




Figure E4-B

7-4-3. CPS INPUT LEVEL ADJ.

BOARD	VIDEO I/O C.B.A. (E5)
TP	TP3008 (A-1)
ADJ.	VR3001 (A-1)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	OSCILLOSCOPE
SPEC.	1.5Vp-p \pm 0.05Vp-p

≪ SET UP ≫

VIDEO MODE : COLOR (MENU NO.2002)

PB/EE SELECT : EE (MENU NO.2004)

INPUT SW : LINE

1. Connect the oscilloscope to TP3008.
2. Adjust VR3001 so that the level becomes 1.5Vp-p \pm 0.05Vp-p as shown in Figure E5.




Figure E5

7-4-4. S-VHS DEVIATION ADJ.

BOARD	VIDEO I/O C.B.A. (E5)
TP	TP3201 (D-3)
ADJ.	VR3003 (f0)(B-1), VR3006 (DEV)(A-1)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	OSCILLOSCOPE
SPEC.	1.5Vp-p \pm 0.1Vp-p (FIG. E6)

≪ SET UP ≫

IMAGE MODE SELECT : EDIT (MENU NO.2001)

VIDEO MODE : COLOR (MENU NO.2002)

S-VHS REC : ON (MENU NO.2006)

VIDEO LEVEL control : PUSH (AGC : ON)

INPUT SW : LINE

USE EXTENDER BOARD for VIDEO I/O C.B.A.

1. Connect the oscilloscope to TP3201.
2. Adjust VR3003 so that the white peak (100%) level becomes maximum and the beat on the sync tip portion of the color bar signal becomes minimum as shown in Figure E6.
3. Adjust VR3006 so that the level of color bar signal becomes 1.5Vp-p \pm 0.1Vp-p as shown in Figure E6.




Figure E6

7-4-5. CHROMA REC CURRENT ADJ.

BOARD	HEAD AMP C.B.A. (E15)
TP	TP5003 (HOT)(B-4), TP5002 (GND)(B-4)
ADJ.	VR5002 (B-4)
TAPE	S-VHS BLANK TAPE
INPUT	COLOR BAR SIGNAL (LINE)
MODE	REC
M. EQ	OSCILLOSCOPE
SPEC.	50mVp-p ± 2mVp-p

≪ SET UP ≫

IMAGE MODE SELECT : EDIT (MENU NO.2001)

VIDEO MODE : COLOR (MENU NO.2002)

S-VHS REC : ON (MENU NO.2006)

VIDEO LEVEL control : PUSH (AGC : ON)

INPUT SW : LINE

1. Turn VR5001 fully clockwise to eliminate Y carrier.
2. Connect the oscilloscope to TP5003 with an 1:1 probe.
3. Adjust VR5002 so that the cyan level becomes 50mVp-p ± 2mV as shown in Figure E7.




Figure E7

≪ NOTE ≫

After this adjustment is finished, adjust 7-4-6. S-VHS Y REC Current Adj.

7-4-6. S-VHS Y REC CURRENT ADJ.**≪ NOTE ≫**

This adjustment should be performed only after completion of 7-4-5. Chroma REC Current Adj.

BOARD	HEAD AMP C.B.A. (E15)
TP	TP5003 (HOT)(B-4), TP5002 (GND)(B-4)
ADJ.	VR5001 (B-4)
TAPE	S-VHS BLANK TAPE
INPUT	COLOR BAR SIGNAL (LINE)
MODE	REC
M. EQ	OSCILLOSCOPE
SPEC.	175mVp-p ± 5mVp-p

≪ SET UP ≫

IMAGE MODE SELECT : EDIT (MENU NO.2001)

VIDEO MODE : COLOR (MENU NO.2002)

S-VHS REC : ON (MENU NO.2006)

VIDEO LEVEL control : PUSH (AGC : ON)

INPUT SW : LINE

1. Connect the oscilloscope to TP5003 with an 1:1 probe.
2. Adjust VR5001 so that the sync tip level becomes 175mVp-p ± 5mV as shown in Figure E8.




Figure E8

7-4-7. VHS Y REC CURRENT ADJ.**≪ NOTE ≫**

This adjustment should be performed only after completion of 7-4-5. Chroma REC Current Adj. and 7-4-6. S-VHS Y REC Current Adj.

BOARD	HEAD AMP C.B.A. (E15)
TP	TP5003 (HOT)(B-4), TP5002 (GND)(B-4)
ADJ.	VR3305 (F-1): VIDEO I/O C.B.A.
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	REC
M. EQ	OSCILLOSCOPE
SPEC.	180mVp-p ± 5mVp-p

≪ SET UP ≫

IMAGE MODE SELECT : EDIT (MENU NO.2001)

VIDEO MODE : COLOR (MENU NO.2002)

PB/EE SELECT : EE (MENU NO.2004)

S-VHS REC : OFF (MENU NO.2006)

VIDEO LEVEL control : PUSH (AGC : ON)

INPUT SW : LINE

1. Connect the oscilloscope to TP5003 with an 1:1 probe..
2. Adjust VR3305 so that the sync tip level becomes 180mVp-p ± 5mVp-p as shown in Figure E9.




Figure E9

7-4-8. VIDEO LEVEL METER ADJ.

≪ NOTE ≫

This adjustment should be performed only after completion of 7-4-4. S-VHS Deviation Adj.

BOARD	VIDEO I/O C.B.A. (E5)
TP	VIDEO LEVEL METER
ADJ.	VR3301 (B-1)
TAPE	
INPUT	COLOR BAR SIGNAL (S-VIDEO)
MODE	EJECT (E-E)
M. EQ	
SPEC.	REFER TO FIG E10

≪ SET UP ≫

IMAGE MODE SELECT : EDIT (MENU NO.2001)

PB/EE SELECT : EE (MENU NO.2004)

VIDEO LEVEL control : PUSH (AGC : ON)

INPUT SW : S-VIDEO

1. Adjust VR3301 so that the needle of VIDEO LEVEL METER becomes at point as shown in Figure E10.




Figure E10

7-5. VIDEO PB SECTION

7-5-1. PB RF CHROMA LEVEL ADJ.

BOARD	VIDEO I/O C.B.A. (E5)
TP	TP3005 (B-1)
ADJ.	VR3201 (D-1)
TAPE	C.B. SELF RECORDED TAPE (S-VHS)
INPUT	
MODE	PLAYBACK
M. EQ	OSCILLOSCOPE
SPEC.	0.7Vp-p \pm 0.05Vp-p

≪ SET UP ≫

IMAGE MODE SELECT : EDIT (MENU NO.2001)

VIDEO MODE : COLOR (MENU NO.2002)

PB/EE SELECT : EE (MENU NO.2004)

S-VHS REC : ON (MENU NO.2006)

VIDEO LEVEL control : PUSH (AGC : ON)

1. Connect the oscilloscope to TP3005.
2. Adjust VR3201 so that the cyan level becomes 0.7Vp-p \pm 0.05Vp-p as shown in Figure E11.




Figure E11

7-5-2. PB Y LEVEL ADJ.

≪ NOTE ≫

This adjustment should be performed only after completion of 7-4-4. S-VHS Deviation Adj.

BOARD	VIDEO I/O C.B.A. (E5)
TP	TP3307 (B-1)
ADJ.	VR3202 (D-3)
TAPE	C.B. SELF RECORDED TAPE (S-VHS)
INPUT	COLOR BAR SIGNAL
MODE	PLAYBACK, STOP (E-E)
M. EQ	OSCILLOSCOPE
SPEC.	PLAY LEVEL = E-E LEVEL \pm 0.05Vp-p

≪ SET UP ≫

IMAGE MODE SELECT : EDIT (MENU NO.2001)

VIDEO MODE : COLOR (MENU NO.2002)

S-VHS REC : ON (MENU NO.2006)

VIDEO LEVEL control : PUSH (AGC : ON)

1. Playback the color bar signal self recorded tape by S-VHS mode.
2. Connect the oscilloscope to TP3307.
2. Adjust VR3202 so that the playback Y level becomes the same (\pm 0.05Vp-p) as the stop (EE) Y level as shown in Figure E12.




Figure E12

7-5-3. S-VHS NORMAL EQUALIZER ADJ.

BOARD	VIDEO I/O C.B.A. (E5)
TP	TP3307 (B-1)
ADJ.	VR3010 (L CH), VR3011 (R CH)
TAPE	30% VIDEO SWEEP (B/W) SIGNAL SELF RECORDED TAPE (S-VHS)
INPUT	
MODE	PLAYBACK
M. EQ	OSCILLOSCOPE
SPEC.	100KHz:4MHz = 5:3.5 \pm 0.5

≪ SET UP ≫

IMAGE MODE SELECT : EDIT (MENU NO.2001)

S-VHS REC : ON (MENU NO.2006)

VIDEO LEVEL control : PUSH (AGC: ON)

1. Play back the 30% sweep signal (Figure E13-A) self recorded tape by S-VHS mode. (Vary the vertical scope setting until the 100KHz level reaches 5 divisions)
2. Connect the oscilloscope to TP3307.
3. Adjust VR3010 (L CH) and VR3011(R CH) so that the level becomes as shown in Figure E13-B.




Figure E13-A




Figure E13-B

7-5-4. S-VHS SS EQUALIZER ADJ.

≪ NOTE ≫

This adjustment should be performed only after completion of 7-5-3. S-VHS Normal Equalizer Adj.

BOARD	VIDEO I/O C.B.A. (E5)
TP	TP3307 (B-1), TP8502 (E-1): TBC (1) C.B.A.
ADJ.	VR3008 (L' CH)(E-1), VR3009 (R' CH)(E-1)
TAPE	30% VIDEO SWEEP (B/W) SIGNAL SELF RECORDED TAPE (S-VHS)
INPUT	
MODE	JOG
M. EQ	OSCILLOSCOPE
SPEC.	FIG. E14-A, B

≪ SET UP ≫

IMAGE MODE SELECT : EDIT (MENU NO.2001)

S-VHS REC : ON (MENU NO.2006)

DIGITAL SLOW SW : OFF

1. Play back the 30% sweep signal (Figure E13-A) self recorded tape by S-VHS mode.
2. Connect the oscilloscope to TP8502 for CH1 and TP3307 for CH2.
3. Place the deck in the JOG mode.
4. Rotate the JOG DIAL so that the high period of TP8502 becomes longest as shown in Figure E14-A.
5. Adjust VR3008 so that the L CH and L' CH frequency responses become same characteristics as shown in Figure E14-A.




Figure E14-A

6. Rotate the JOG DIAL so that the low period of TP8502 becomes longest as shown in Figure E14-B.
7. Adjust VR3009 so that the R CH and R' CH frequency responses become same characteristics as shown in Figure E14-B.




Figure E14-B

7-5-5. VHS EQUALIZER ADJ.

◀ NOTE ▶

This adjustment should be performed only after completion of 7-5-3. S-VHS Normal Equalizer Adj.

When you record the 30% video sweep signal, set the IMAGE MODE SELECT to EDIT.

BOARD	VIDEO I/O C.B.A. (E5)
TP	TP3307 (B-1)
ADJ.	VR3007 (E-1)
TAPE	30% VIDEO SWEEP (B/W) SIGNAL SELF RECORDED TAPE (VHS)
INPUT	
MODE	PLAYBACK
M. EQ	OSCILLOSCOPE
SPEC.	100KHz : 2MHz = 5 : 3.5 ± 0.5

◀ SET UP ▶

IMAGE MODE SELECT : EDIT (MENU NO.2001)

VIDEO MODE : B/W (MENU NO.2002)

S-VHS REC : OFF (MENU NO.2006)

VIDEO LEVEL control : PUSH (AGC : ON)

INPUT SW : S-VIDEO

1. Play back the 30% sweep signal (Figure E13-A) self recorded tape by VHS mode. (Vary the vertical scope setting until the 100KHz level reaches 5 divisions)
2. Connect the oscilloscope to TP3307.
3. Adjust VR3007 so that the level becomes as shown in Figure E15.




Figure E15

7-5-6. VIDEO TRACKING METER ADJ.

BOARD	VIDEO I/O C.B.A. (E5)
TP	VIDEO TRACKING METER
ADJ.	VR3014 (E-1)
TAPE	C.B. SELF RECORDED TAPE (S-VHS)
INPUT	
MODE	PLAYBACK
M. EQ	
SPEC.	REFER TO FIG. E16

◀ SET UP ▶

S-VHS REC : ON (MENU NO.2006)

VIDEO LEVEL control : PUSH (AGC : ON)

CH2 METER SW : VIDEO • TRACKING

1. Play back the color bar signal self recorded tape by S-VHS mode.
2. Adjust VR3014 so that the needle of VIDEO TRACKING METER becomes at point as shown in Figure E16.




Figure E16

7-6. TBC SECTION

7-6-1. Y A/D INPUT (1) ADJ.

BOARD	TBC (1) C.B.A. (E11)
TP	TP8201 (B-1)
ADJ.	VR8202 (B-1)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	OSCILLOSCOPE
SPEC.	1.5V ± 0.05V

◀ SET UP ▶

VIDEO MODE : COLOR (MENU NO.2002)

PB/EE SELECT : EE (MENU NO.2004)

INPUT SW : LINE

1. Connect the oscilloscope to TP8201.
2. Adjust VR8202 so that the level becomes 1.5V ± 0.05V as shown in Figure E17.




Figure E17

7-6-2. Y A/D INPUT (2) ADJ.

BOARD	TBC (1) C.B.A. (E11)
TP	VIDEO OUT
ADJ.	VR8201 (B-1)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	OSCILLOSCOPE
SPEC.	0mV ± 10mV

≪ SET UP ≫

TBC CONTROL : CENTER POSITION (OSD)
 VIDEO MODE : COLOR (MENU NO.2002)
 PB/EE SELECT : EE (MENU NO.2004)
 INPUT SW : LINE

1. Connect the oscilloscope to VIDEO OUT.
2. Adjust VR8201 so that the set-up level becomes $0\text{mV} \pm 10\text{mV}$ as shown in Figure E18.




Figure E18

7-6-3. Y OUTPUT LEVEL ADJ.

BOARD	TBC (2) C.B.A. (E12)
TP	VIDEO OUT (75Ω)
ADJ.	VR8804 (F-2)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	OSCILLOSCOPE
SPEC.	$0.734\text{Vp-p} \pm 0.05\text{Vp-p}$

≪ NOTE ≫

VIDEO OUT should be 75Ω terminated.

≪ SET UP ≫

TBC CONTROL : CENTER POSITION (OSD)
 VIDEO MODE : COLOR (MENU NO.2002)
 PB/EE SELECT : EE (MENU NO.2004)
 INPUT SW : LINE

1. Connect the oscilloscope to VIDEO OUT.
2. Adjust VR8804 so that the Y level becomes $0.734\text{Vp-p} \pm 0.05\text{Vp-p}$ as shown in Figure E19.




Figure E19

7-6-4. SYNC LEVEL ADJ.

≪ NOTE ≫

This adjustment should be performed only after completion of 7-6-3. Y Output Level Adj.
 VIDEO OUT should be 75Ω terminated.

BOARD	TBC (2) C.B.A. (E12)
TP	VIDEO OUT (75Ω)
ADJ.	VR8803 (F-2)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	OSCILLOSCOPE
SPEC.	$0.286\text{Vp-p} \pm 0.03\text{Vp-p}$

≪ SET UP ≫

TBC CONTROL : CENTER POSITION (OSD)
 VIDEO MODE : COLOR (MENU NO.2002)
 PB/EE SELECT : EE (MENU NO.2004)
 VIDEO LEVEL control : PUSH (AGC : ON)
 INPUT SW : LINE

1. Connect the oscilloscope to VIDEO OUT.
2. Adjust VR8804 so that the SYNC level becomes $0.286\text{Vp-p} \pm 0.03\text{V}$ as shown in Figure E20.




Figure E20

7-6-5. C A/D INPUT (1) ADJ.

BOARD	TBC (1) C.B.A. (E11)
TP	TP8202 (R)(A-1), TP8203 (B)(A-1)
ADJ.	VR8204 (R-Y)(B-1), VR8205 (B-Y)(B-1)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	OSCILLOSCOPE
SPEC.	1.5Vp-p \pm 0.05Vp-p

◀ SET UP ▶

VIDEO MODE : COLOR (MENU NO.2002)
PB/EE SELECT : EE (MENU NO.2004)
INPUT SW : LINE

1. Connect the oscilloscope to TP8202.
2. Adjust VR8204 so that the level becomes 1.5Vp-p \pm 0.05Vp-p as shown in Figure E21-A.




Figure E21-A

3. Connect the oscilloscope to TP8203.
4. Adjust VR8205 so that the level becomes 1.5Vp-p \pm 0.05Vp-p as shown in Figure E21-B.




Figure E21-B

7-6-6. C A/D OUTPUT LEVEL ADJ.

BOARD	TBC (1) C.B.A. (E11)
TP	TP8051 (E-3)
ADJ.	VR8002 (F-1)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	V.T.V.M. or D.V.M.
SPEC.	3.5V \pm 0.05V

◀ SET UP ▶

TBC CONTROL : CENTER POSITION (OSD)
VIDEO MODE : COLOR (MENU NO.2002)
INPUT SW : LINE

1. Connect the V.T.V.M. or D.V.M. to TP8051.
2. Adjust VR8002 so that the DC voltage becomes 3.5V \pm 0.05V.

7-6-7. C A/D INPUT (2) ADJ.

BOARD	TBC (1) C.B.A. (E11)
TP	COMPONENT OUT (PB, PR)
ADJ.	VR8203 (B-1), VR8302 (F-1)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	W.F.M. or OSCILLOSCOPE
SPEC.	0mV \pm 10mV

◀ SET UP ▶

VIDEO MODE : COLOR (MENU NO.2002)
PB/EE SELECT : EE (MENU NO.2004)
INPUT SW : LINE

1. Connect the W.F.M. to Component PR OUT.
2. Adjust VR8203 so that the level becomes minimum (0mV \pm 10mV) as shown in Figure E22-A.




Figure E22-A

3. Connect the W.F.M. to Component PB OUT.
4. Adjust VR8302 so that the level becomes minimum (0mV \pm 10mV) as shown in Figure E22-B.




Figure E22-B

7-6-8. E-E CHROMA ADJ.

BOARD	VIDEO C C.B.A. (E13)
TP	COMPONENT OUT (PB, PR)(75Ω)
ADJ.	VR9401 (A-1), VR8810 (F-1), VR8811 (F-1) : TBC (2) C.B.A.
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	W.F.M. or OSCILLOSCOPE
SPEC.	FIG. E23-A, B, C

◀ NOTE ▶

VIDEO OUT should be 75Ω terminated.

◀ SET UP ▶

TBC CONTROL : CENTER POSITION.(OSD)
 IMAGE MODE SELECT : EDIT (MENU NO.2001)
 VIDEO MODE : COLOR (MENU NO.2002)
 DNR : OFF
 INPUT SW : LINE
 VIDEO LEVEL control : PUSH (AGC : ON)

1. Connect the W.F.M. to Component PB OUT.
2. Adjust VR9401 so that the waveform becomes as shown in Figure E23-A.




Figure E23-A

3. Adjust VR8810 so that the level becomes 0.486Vp-p ± 0.05Vp-p as shown in Figure E23-B.




Figure E23-B

4. Connect the W.F.M. to Component PR out.
5. Adjust VR8811 so that the level becomes 0.486Vp-p ± 0.05Vp-p as shown in Figure E23-C.




Figure E23-C

7-6-9. CAC PR LEVEL ADJ.

BOARD	VIDEO C C.B.A. (E13)
TP	COMPONENT PR OUT
ADJ.	VR9407 (B-1)
TAPE	C.B. SELF RECORDED TAPE (S-VHS)
INPUT	
MODE	PLAYBACK
M. EQ	W.F.M. or OSCILLOSCOPE
SPEC.	B = A ± 2%

◀ SET UP ▶

VIDEO MODE : COLOR (MENU NO.2002)
 DNR : OFF
 INPUT SW : S-VIDEO
 VIDEO LEVEL control : PUSH (AGC : ON)

1. Play back the color bar signal (S-VIDEO) self recorded tape by S-VHS mode.
2. Connect the W.F.M. to Component PR OUT.
3. Adjust VR9407 so that the levels "A" and "B" become the same at the EDIT mode and NORMAL mode (change the IMAGE MODE SELECT (MENU NO.2001)) as shown in Figure E24.




Figure E24

7-6-10. CAC PB LEVEL ADJ.

BOARD	VIDEO C C.B.A. (E13)
TP	COMPONENT PB OUT
ADJ.	VR9406 (C-1)
TAPE	C.B. SELF RECORDED TAPE (S-VHS)
INPUT	
MODE	PLAYBACK
M. EQ	W.F.M. or OSCILLOSCOPE
SPEC.	B = A ± 2%

◀ SET UP ▶

VIDEO MODE : COLOR (MENU NO.2002)
 DNR : OFF
 INPUT SW : S-VIDEO
 VIDEO LEVEL control : PUSH (AGC : ON)

1. Play back the color bar signal (S-VIDEO) self recorded tape by S-VHS mode.
2. Connect the W.F.M. to Component PB OUT.
3. Adjust VR9406 so that the levels "A" and "B" become the same at the EDIT mode and NORMAL mode (change the IMAGE MODE SELECT (MENU NO.2001)) as shown in Figure E25.




Figure E25

7-6-11. EDIT CHROMA ADJ.

⌵ NOTE ⌵

This adjustment should be performed only after completion of 7-6-8. E-E Chroma Adj.

BOARD	VIDEO C C.B.A. (E13)
TP	COMPONENT PB OUT (75Ω)
ADJ.	VR9405 (B-1), VR9410 (A-1)
TAPE	C.B. SELF RECORDED TAPE (S-VHS)
INPUT	
MODE	PLAYBACK
M. EQ	W.F.M. or OSCILLOSCOPE
SPEC.	FIG. E26-A, B

⌵ SET UP ⌵

IMAGE MODE SELECT : EDIT (MENU NO.2001)

VIDEO MODE : COLOR (MENU NO.2002)

DNR : OFF

INPUT SW : LINE

VIDEO LEVEL control : PUSH (AGC : ON)

1. Play back the color bar signal self recorded tape by S-VHS mode.
2. Connect the W.F.M. to Component PB OUT.
3. Adjust VR9410 so that the waveform become as shown in Figure E26-A.




Figure E26-A

4. Adjust VR9405 so that the level becomes $0.486\text{Vp-p} \pm 0.05\text{Vp-p}$ as shown in Figure E26-B.



Figure E26-B

7-6-12. NORMAL CHROMA ADJ.

BOARD	VIDEO C C.B.A. (E13)
TP	COMPONENT OUT (PB, PR)(75Ω)
ADJ.	VR9406 (C-1), VR9407 (B-1)
TAPE	C.B. SELF RECORDED TAPE (S-VHS)
INPUT	
MODE	PLAYBACK
M. EQ	W.F.M. or OSCILLOSCOPE
SPEC.	FIG. E27-A, B

⌵ NOTE ⌵

This adjustment should be performed only after completion of 7-6-8. E-E Chroma Adj and 7-6-11. Edit Chroma Adj.

⌵ SET UP ⌵

IMAGE MODE SELECT : NORMAL (MENU NO.2001)

VIDEO MODE : COLOR (MENU NO.2002)

DNR : OFF

INPUT SW : LINE

VIDEO LEVEL control : PUSH (AGC : ON)

1. Play back the color bar signal self recorded tape by S-VHS mode.
2. Connect the W.F.M. to Component PB OUT.
3. Adjust VR9406 so that the level becomes $0.486\text{Vp-p} \pm 0.05\text{Vp-p}$ as shown in Figure E27-A.



Figure E27-A

4. Connect the W.F.M. to Component PR OUT.
5. Adjust VR9407 so that the level becomes $0.486\text{Vp-p} \pm 0.05\text{Vp-p}$ as shown in Figure E27-B.




Figure E27-B

7-6-13. CARRIER BALANCE ADJ.

BOARD	TBC (2) C.B.A. (E12)
TP	VIDEO OUT (75Ω)
ADJ.	VR8807 (E-1), VR8808 (E-1)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	VECTORSCOPE
SPEC.	FIG. E28

⌵ NOTE ⌵

VIDEO OUT should be 75Ω terminated.

⌵ SET UP ⌵

TBC CONTROL : CENTER POSITION

VIDEO MODE : COLOR (MENU NO.2002)

INPUT SW : LINE

VIDEO LEVEL control : PUSH (AGC : ON)

1. Connect the vectorscope to VIDEO OUT and adjust VR8807 and VR8808 so that the point "C" becomes center of the vector scope as shown in Figure E28.




Figure E28

7-6-14. BURST LEVEL ADJ.

« NOTE »

This adjustment should be performed only after completion of 7-6-13. Carrier Balance Adj.

VIDEO OUT should be 75Ω terminated.

BOARD	TBC (2) C.B.A. (E12)
TP	VIDEO OUT (75Ω)
ADJ.	VR8806 (E-1)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	VECTORSCOPE
SPEC.	FIG. E29

« SET UP »

TBC CONTROL : CENTER POSITION

VIDEO MODE : COLOR (MENU NO.2002)

INPUT SW : LINE

VIDEO LEVEL control : PUSH (AGC : ON)

1. Connect the vectorscope to VIDEO OUT.
2. Adjust VR8806 that the burst signal becomes 75% (180°) as shown in Figure E29.




Figure E29

7-6-15. CHROMA VECTOR BALANCE ADJ.

BOARD	TBC (2) C.B.A. (E12)
TP	VIDEO OUT (75Ω)
ADJ.	VR8801 (E-1), VR8802 (E-1), VR8815 (D-1)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	VECTORSCOPE
SPEC.	FIG. E30

« NOTE »

VIDEO OUT should be 75Ω terminated.

« SET UP »

TBC CONTROL : CENTER POSITION

VIDEO MODE : COLOR (MENU NO.2002)

INPUT SW : LINE

VIDEO LEVEL control : PUSH (AGC : ON)

1. Connect the vectorscope to VIDEO OUT.
2. Adjust VR8801, VR8802 and VR8815 so that the all vectors except burst phase become correct position as shown in Figure E30.




Figure E30

7-6-16. BURST PHASE ADJ.

BOARD	TBC (2) C.B.A. (E12)
TP	VIDEO OUT (75Ω)
ADJ.	VR8814 (D-1)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	VECTORSCOPE
SPEC.	FIG. E31

◀ NOTE ▶

VIDEO OUT should be 75Ω terminated.

◀ SET UP ▶

TBC CONTROL : CENTER POSITION

VIDEO MODE : COLOR (MENU NO.2002)

INPUT SW : LINE

VIDEO LEVEL control : PUSH (AGC : ON)

1. Connect the vectorscope to VIDEO OUT.
2. Adjust the vectorscope so that the burst signal becomes 75% (180°).
3. Adjust VR8814 so that the all vectors become correct position as shown in Figure E31.




Figure E31

7-6-17. BURST POSITION ADJ.

BOARD	TBC (2) C.B.A. (E12)
TP	VIDEO OUT (75Ω)
ADJ.	VR8805 (D-1)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	W.F.M. or OSCILLOSCOPE
SPEC.	5.3 μsec ± 0.1 μsec

◀ NOTE ▶

VIDEO OUT should be 75Ω terminated.

◀ SET UP ▶

TBC CONTROL : CENTER POSITION

VIDEO MODE : COLOR (MENU NO.2002)

INPUT SW : LINE

VIDEO LEVEL control : PUSH (AGC : ON)

1. Connect the W.F.M. to VIDEO OUT.
2. Adjust VR8805 so that the period of H. Sync (down edge) to Burst signal (Burst start point) becomes 5.3 μsec. ± 0.1 μsec. as shown in Figure E32.




Figure E32

7-6-18. Y/C TIMING ADJ.

BOARD	TBC (1) C.B.A. (E11)
TP	VIDEO OUT (75Ω)
ADJ.	VR8103 (C-1)
TAPE	
INPUT	SIN² PULSE & BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	W.F.M. or OSCILLOSCOPE
SPEC.	0nsec ± 50nsec

◀ NOTE ▶

VIDEO OUT should be 75Ω terminated.

◀ SET UP ▶

TBC CONTROL : CENTER POSITION

VIDEO MODE : COLOR (MENU NO.2002)

INPUT SW : LINE

1. Connect the oscilloscope (W.F.M.) to VIDEO OUT and expanded the "A" portion as shown in Figure E33-A.




Figure E33-A

2. Adjust VR8103 so that the waveform becomes as shown in Figure E33-B.




Figure E33-B

7-6-19. PB S-VHS Y/C DELAY ADJ.

BOARD	VIDEO I/O C.B.A. (E10)
TP	VIDEO OUT
ADJ.	VR3205 (E-3)
TAPE	SIN ² PULSE & BAR SIGNAL OTHE RECORDED TAPE (S-VHS)
INPUT	
MODE	PLAYBACK
M. EQ	W.F.M. or OSCILOSCOPE
SPEC.	100nsec \pm 50nsec (FIG. E34)

◀ SET UP ▶

IMAGE MODE SELECT : EDIT (MENU NO.2001)
VIDEO MODE : COLOR (MENU NO.2002)

1. Connect the oscilloscope (W.F.M.) to VIDEO OUT and expanded the "A" portion as shown in Figure E33-A.
2. Play back the SIN² PULSE & BAR signal other recorded tape by S-VHS mode.
3. Adjust VR3205 so that the waveform becomes as shown in Figure E34.




Figure E34

7-6-20. PB VHS Y/C DELAY ADJ.

BOARD	VIDEO I/O C.B.A. (E10)
TP	VIDEO OUT
ADJ.	VR3204 (E-3)
TAPE	SIN ² PULSE & BAR SIGNAL OTHE RECORDED TAPE (VHS)
INPUT	
MODE	PLAYBACK
M. EQ	W.F.M. or OSCILOSCOPE
SPEC.	100nsec \pm 50nsec (FIG. E34)

◀ SET UP ▶

IMAGE MODE SELECT : EDIT (MENU NO.2001)
VIDEO MODE : COLOR (MENU NO.2002)

1. Connect the oscilloscope (W.F.M.) to VIDEO OUT and expanded the "A" portion as shown in Figure E33-A.
2. Play back the SIN² PULSE & BAR signal other recorded tape by VHS mode.
3. Adjust VR3204 so that the waveform becomes as shown in Figure E34.

7-6-21. NORMAL Y/C TIMING ADJ.

◀ NOTE ▶

This adjustment should be performed only after completion of 7-6-18. Y/C Timing Adj., 7-6-19. PB S-VHS Y/C Delay Adj. and 7-6-20. PB VHS Y/C Delay Adj.

BOARD	VIDEO C C.B.A. (E13)
TP	VIDEO OUT
ADJ.	VR9403 (C-1), SW3921 (A-1)(DIGITAL C.B.A)
TAPE	SIN ² PULSE & BAR SIGNAL OTHE RECORDED TAPE (S-VHS)
INPUT	
MODE	PLAYBACK
M. EQ	W.F.M. or OSCILLOSCOPE
SPEC.	100nsec \pm 50nsec (FIG. E34)

◀ SET UP ▶

TBC CONTROL : CENTER POSITION
IMAGE MODE SELECT : NORMAL (MENU NO.2001)
VIDEO MODE : COLOR (MENU NO.2002)
DNR : OFF
VIDEO LEVEL control : PUSH (AGC : ON)

1. Connect a jumper wire between TP9405 and TPG9406.
2. Connect the oscilloscope (W.F.M.) to VIDEO OUT and expanded the "A" portion as shown in Figure E33-A.
3. Play back the SIN² PULSE & BAR signal other recorded tape by S-VHS mode.
4. Adjust VR9403 and SW3921 so that the waveform becomes as shown in Figure E34.

7-6-22. CAC Y/C TIMING ADJ.**≪ NOTE ≫**

This adjustment should be performed only after completion of 7-6-18. Y/C Timing Adj., 7-6-19. PB S-VHS Y/C Delay Adj. and 7-6-20. PB VHS Y/C Delay Adj.

BOARD	VIDEO C.C.B.A. (E13)
TP	TP9407 (C-2), TP9404 (B-1)
ADJ.	VR9402 (C-1)
TAPE	SIN ² PULSE & BAR SIGNAL OTHER RECORDED TAPE (S-VHS)
INPUT	
MODE	PLAYBACK
M. EQ	OSCILLOSCOPE
SPEC.	70nsec ± 35nsec (FIG. E35)

≪ SET UP ≫

TBC CONTROL : CENTER POSITION
 IMAGE MODE SELECT : NORMAL (MENU NO.2001)
 VIDEO MODE : COLOR (MENU NO.2002)
 DNR : OFF
 VIDEO LEVEL control : PUSH (AGC : ON)

1. Connect the oscilloscope to TP9407 for CH1 and TP9404 for CH2.
2. Set the vertical scope setting of both the channels (CH1 and CH2) to the same range.
3. Set the scope to ADD (CH1+CH2) mode.
4. Play back the SIN² PULSE & BAR signal other recorded tape by S-VHS mode.
5. Adjust VR9402 so that the waveform becomes as shown in Figure E35.




Figure E35

7-6-23. Y CLOCK PHASE ADJ.

BOARD	TBC (1) C.B.A. (E11)
TP	TP8101 (C-3)
ADJ.	VR8101 (C-3)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	OSCILLOSCOPE
SPEC.	A=45±5

≪ SET UP ≫

INPUT SELECT : LINE

1. Connect the oscilloscope to TP8101.
2. Adjust VR8101 so that the waveform becomes as shown in Figure E36.




Figure E36

7-6-24. PLL LOCK ADJ.

BOARD	TBC (1) C.B.A. (E11)
TP	TP8105 (B-2), TP8103 (C-2)
ADJ.	VC8101 (B-3)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	OSCILLOSCOPE
SPEC.	840nsec ± 20nsec (FIG. E37)

≪ SET UP ≫

INPUT SELECT : LINE

1. Connect the oscilloscope to TP8105 for CH1 and TP8103 for CH2.
2. Adjust VC8101 so that the "T" becomes 840nsec. ± 20 nsec. as shown in Figure E37.




Figure E37

7-6-25. C CLOCK PHASE ADJ.

BOARD	TBC (1) C.B.A. (E11)
TP	TP8301 (C-3)
ADJ.	VR8301 (B-3)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	OSCILLOSCOPE
SPEC.	A=45±5

◀ SET UP ▶

INPUT SELECT : LINE

1. Connect a scope to TP8301.
2. Adjust VR8301 so that the waveform becomes as shown in Figure E36.

7-6-26. HEAD SWITCH ADJ.

BOARD	TBC (1) C.B.A. (E11)
TP	TP41003 (G-1: AUDIO(2)), TP8501 (F-1)
ADJ.	VR8501 (E-1)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	REC
M. EQ	OSCILLOSCOPE
SPEC.	$T = 32.5 \mu\text{sec} \pm 2.5 \mu\text{sec}$ (FIG. E38)

◀ SET UP ▶

INPUT SELECT : LINE

1. Connect a scope to TP41003 for CH-1 and TP8501 for CH-2.
2. Adjust VR8501 so that the "T" becomes $32.5 \mu\text{sec} \pm 2.5 \mu\text{sec}$ as shown in Figure E38.




Figure E38-A

◀ NOTE ▶

You can adjust more easy by using the ADD (CH1 & CH2) feature on a scope as shown in Figure E-38-B




Figure E38-B

7-6-27. S/H ADJ.

BOARD	TBC (2) C.B.A. (E12)
TP	TP8603 (A-4), TP8604 (B-1)
ADJ.	VR8601 (B-1)
TAPE	
INPUT	COLOR BAR SIGNAL (REF. IN)
MODE	EJECT (E-E)
M. EQ	OSCILLOSCOPE
SPEC.	$A = B \pm 10\%$

◀ SET UP ▶

INPUT SELECT : LINE

1. Supply a color bar signal to the REF. IN.
2. Connect a scope to TP8603 for CH-1 and TP8604 for CH-2.
3. Adjust VR8601 so that the position of S/H pulse (TP8604) becomes as shown in Figure E39.




Figure E39

7-6-28. 14.3MHz VCO ADJ.

BOARD	TBC (2) C.B.A. (E12)
TP	TP8609 (C-2)
ADJ.	VC8671 (A-2)
TAPE	
INPUT	NO SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	FREQUENCY COUNTER
SPEC.	$f = 3,579,545\text{Hz} \pm 5\text{Hz}$

◀ SET UP ▶

INPUT SELECT : LINE

1. Connect a counter to TP8609.
2. Adjust VC8671 so that the frequency becomes $3,579,545\text{Hz} \pm 5\text{Hz}$.

7-6-29. REF. SCH ADJ.

BOARD	TBC (2) C.B.A. (E12)
TP	TP8609 (C-2), TP8610 (C-2)
ADJ.	VR8603 (B-1)
TAPE	
INPUT	COLOR BAR SIGNAL (REF. & LINE)
MODE	EJECT (E-E)
M. EQ	OSCILLOSCOPE
SPEC.	A = B ± 10%

≪ NOTE ≫

SCH of a color bar signal (REF. & LINE) should be 0°.

≪ SET UP ≫

INPUT SELECT : LINE

1. Connect a scope to TP8609 for CH1 and TP8610 for CH2.
2. Adjust VR8603 so that the up edge of H pulse becomes as shown in Figure E40.




Figure E40

7-6-30. SCH PHASE ADJ.

BOARD	TBC (2) C.B.A. (E12)
TP	VIDEO OUT (75Ω)
ADJ.	SW8701 (C-1), VR8602 (B-1)
TAPE	
INPUT	COLOR BAR SIGNAL (REF. & LINE)
MODE	EJECT (E-E)
M. EQ	SCH METER
SPEC.	0 ± 2°

≪ NOTE ≫

VIDEO OUT should be 75Ω terminated.

SCH of a color bar signal (REF. & LINE) should be 0°.

Trigger of SCH METER should be EXT.

≪ SET UP ≫

VIDEO MODE : COLOR (MENU NO.2002)

PB/EE SELECT : EE (MENU NO.2004)

INPUT SW : LINE

1. Connect a SCH Meter as shown in Figure E41-A.
2. Adjust SW8701 and VR8602 so that the SCH phase becomes 0° ± 2° as shown in Figure E41-B.




Figure E41-A




Figure E41-B

7-6-31. SYSTEM H PHASE ADJ.

BOARD	TBC (2) C.B.A. (E12)
TP	REF VIDEO, VIDEO OUT (75Ω)
ADJ.	VR8701 (B-1)
TAPE	
INPUT	COLOR BAR SIGNAL (REF.)
MODE	EJECT (E-E)
M. EQ	OSCILLOSCOPE
SPEC.	FIG. E42-B

≪ NOTE ≫

VIDEO OUT should be 75Ω terminated.

SCH of color bar signal (REF.) should be 0°.

≪ SET UP ≫

VIDEO MODE : COLOR (MENU NO.2002)

TBC CONTROL (SYSTEM H PHASE) : CENTER (OSD)

INPUT SW : LINE

1. Connect a scope as shown in Figure E42-A.
2. Adjust VR8701 so that the H phase of these signals are the same as shown in Figure E42-B.




Figure E42-A




Figure E42-B

7-6-32. VIDEO PHASE ADJ.

BOARD	TBC (1) C.B.A. (E-11)
TP	VIDEO OUT (75Ω)
ADJ.	VR8102 (C-1)
TAPE	
INPUT	COLOR BAR SIGNAL (LINE)
MODE	EJECT (E-E)
M. EQ	W.F.M. or OSCILLOSCOPE
SPEC.	FIG. E43

◀ NOTE ▶

VIDEO OUT should be 75Ω terminated.

◀ SET UP ▶

VIDEO MODE : COLOR (MENU NO.2002)
PB/EE SELECT : EE (MENU NO.2004)
INPUT SW : LINE

1. Connect the W.F.M. to VIDEO OUT.
2. Adjust VR8102 so that the waveform becomes as shown in Figure E43.




Figure E43

7-6-33. SYSTEM SC PHASE ADJ.

BOARD	TBC (2) C.B.A. (E12)
TP	VIDEO OUT (75Ω)
ADJ.	VR8671 (A-1)
TAPE	
INPUT	COLOR BAR SIGNAL (REF. & LINE)
MODE	EJECT (E-E)
M. EQ	SCH METER
SPEC.	0° ± 2°

⌞ NOTE ⌟

VIDEO OUT should be 75Ω terminated.

◀ SET UP ▶

TBC CONTROL : CENTER POSITION
PB/EE SELECT : EE (MENU NO.2004)
INPUT SW : LINE

1. Connect the SCH Meter as shown in Figure E41-A.
2. Adjust VR8671 so that the SYSTEM SC PHASE becomes $0^\circ \pm 2^\circ$ as shown in Figure E41-B.
3. If not, adjust the TBC CONTROL (SYSTEM SC COARSE), and repeat step 2.

7-7.AUDIO SECTION

Unless otherwise specified, the following connections are used to check the output and input levels from/to the AUDIO OUT and IN jacks (XLR) as shown in Figure E44.




Figure E44

And connect the AG-DS850 and Audio Meter (V.T.V.M. or D.V.M.) in parallel as shown in Figure E45 when you check the level of input signal.

(0dBm = 0.775Vrms = 2.19Vp-p)




Figure E45

Please note that the Audio Output Level Switch is located on the AUDIO (2) C.B.A. (C-1)

7-7-1. NORMAL AUDIO INPUT LEVEL ADJ.

BOARD	AUDIO (1) C.B.A. (E7)
TP	NORM/Hi-Fi AUDIO OUT (CH1/CH2)
ADJ.	VR40011 (CH1)(E-1), VR40012 (CH2)(E-1)
TAPE	
INPUT	1KHz, 0dBm SINE WAVE SIGNAL
MODE	EJECT (E-E)
M. EQ	V.T.V.M. (D.V.M.)
SPEC.	0dBm \pm 0.2dBm

◀ SET UP ▶

S-VHS REC : OFF (MENU NO.2006)
 DOLBY NR : OFF (MENU NO.3001)
 AUDIO LIMITER : OFF (MENU NO.3002)
 AUDIO OUT SELECT SW : NORM
 INPUT AUDIO LEVEL SW (NORM/Hi-Fi) : 0dBs
 OUTPUT AUDIO LEVEL SW : 0dBs
 CH1 REC : CH1 (MENU NO.3005)
 AUDIO CH2 : AUDIO (MENU NO.3006)
 NORM. AUDIO (CH1/2) LEVEL CONTROL : CENTER

1. Supply a 1KHz, 0dBm sine wave signal to the NORM/Hi-Fi AUDIO (CH1 & CH2) INPUTs.
2. Adjust VR40011 (CH1) and VR40012 (CH2) so that the level becomes 0dBm \pm 0.2dBm.

7-7-2. Hi-Fi AUDIO INPUT LEVEL ADJ.

BOARD	AUDIO (2) C.B.A. (E8)
TP	Hi-Fi AUDIO OUT (CH1/CH2)
ADJ.	VR41008 (CH1)(D-1), VR41009 (CH2)(E-1)
TAPE	
INPUT	1KHz, 0dBm SINE WAVE SIGNAL
MODE	EJECT (E-E)
M. EQ	V.T.V.M. (D.V.M.)
SPEC.	0dBm \pm 0.2dBm

◀ SET UP ▶

S-VHS REC : OFF (MENU NO.2006)
 Hi-Fi INPUT SELECT : Hi-Fi INPUT (MENU NO.3004)
 INPUT AUDIO LEVEL SW (Hi-Fi) : 0dBs
 OUTPUT AUDIO LEVEL SW : 0dBs
 Hi-Fi AUDIO (CH1/2) LEVEL CONTROL : CENTER

1. Supply a 1KHz, 0dBm sine wave signal to the Hi-Fi AUDIO (CH1 & CH2) INPUTs.
2. Adjust VR41008 (CH1) and VR41009 (CH2) so that the level becomes 0dBm \pm 0.2dBm.

7-7-3. AUDIO JACK OUTPUT BALANCE ADJ.

◀ NOTE ▶

This adjustment should be performed only after completion of 7-7-1. Normal Audio Input Level Adj. and 7-7-2. Hi-Fi Audio Input level Adj.

BOARD	REAR AMP C.B.A. (E28)
TP	NORM/Hi-Fi AUDIO OUT (CH1, CH2) Hi-Fi AUDIO OUT (CH1, CH2)
ADJ.	NOR: VR4007(CH1)(C-1), VR4008(CH2)(C-1) Hi-Fi: VR4005(CH1)(C-2), VR4006(CH2)(C-1)
TAPE	
INPUT	1KHz, 0dBm SINE WAVE SIGNAL
MODE	EJECT (E-E)
M. EQ	V.T.V.M. (D.V.M.)
SPEC.	LESS THAN 68mVrms

1. Supply a 1KHz, 0dB sine wave signal to the NORM /Hi-Fi (CH1 & CH2) Audio Inputs.
2. Connect the V.T.V.M.(D.V.M.) to NORM/Hi-Fi AUDIO OUT (CH1/CH2) as shown in Figure E46.
3. Adjust VR4007 (CH1) and VR4008 (CH2) so that the level becomes minimum (less than 68mVrms).
4. Connect the V.T.V.M.(D.V.M.) to the Hi-Fi AUDIO OUT (CH1/CH2) as shown in Figure E46.
5. Adjust VR4005 (CH1) and VR4006 (CH2) so that the level becomes minimum (less than 68mVrms).
6. Perform 7-7-1. Normal Audio Input Level Adj. and/or 7-7-2. Hi-Fi Audio Input Level Adj. again if VR4007 (CH1) VR4008 and/or VR4005 (CH1), VR4006 (CH2) are adjusted.




Figure E46

7-7-4. AUDIO LEVEL METER ADJ.

« NOTE »

This adjustment should be performed only after completion of 7-7-1. Normal Audio Input Adj.

BOARD	AUDIO (2) C.B.A. (E8)
TP	AUDIO METER (CH1, CH2)
ADJ.	VR41012 (CH1)(B-1), VR41013 (CH2)(B-1)
TAPE	
INPUT	1KHz, 0dBm SINE WAVE SIGNAL
MODE	EJECT (E-E)
M. EQ	
SPEC.	0 ± 0.5

« SET UP »

S-VHS REC : ON (MENU NO.2006)
 DOLBY NR : OFF (MENU NO.3001)
 AUDIO LIMITER : OFF (MENU NO.3002)
 Hi-Fi REC : ON (MENU NO.3003)
 CH1 REC : CH1 (MENU NO.3005)
 AUDIO CH2 : AUDIO (MENU NO.3006)
 CH2 METER : AUDIO CH2
 AUDIO METER SW : NORM
 INPUT AUDIO LEVEL SW (NORM/Hi-Fi) : 0dBs
 NORM. AUDIO (CH1/2) LEVEL CONTROL : CENTER

1. Supply a 1KHz, 0dBm sine wave signal to the NORM/Hi-Fi AUDIO (CH1 & CH2) INPUTs.
2. Adjust VR41012 (CH1) and VR41013 (CH2) so that the needle of Audio Level Meter (CH1 & CH2) reaches "0 ± 0.5" as shown in Figure E47.




Figure E47

7-7-5. NORMAL AUDIO PLAYBACK FREQUENCY RESPONSE ADJ.

BOARD	AUDIO (1) C.B.A. (E7)
TP	TP40005 (CH1)(G-1), TP40007 (CH2)(E-1)
ADJ.	VR40002 (CH1)(F-1), VR40007 (CH2)(D-1)
TAPE	VFM8080HQFP, PORTION : 5
INPUT	
MODE	PLAYBACK
M. EQ	OSCILLOSCOPE
SPEC.	400Hz=5KHz (0dB ± 0.5dB)

« NOTE »

After this adjustment is finished, adjust 7-7-6. Normal Audio PB Gain Adj.

« SET UP »

DOLBY NR : OFF (MENU NO.3001)
 AUDIO CH2 : AUDIO (MENU NO.3006)

1. Set the VR40003 and VR40008 to the center position.
2. Play back the alignment tape at portion 5.
3. Connect a oscilloscope to TP40005 and TP40007.
4. Adjust VR40002(CH1) and VR40007(CH2) so that the 400Hz and 5KHz levels become the same (0dBm ± 0.5dBm) as shown in Figure E48.




Figure E48

7-7-6. NORMAL AUDIO PB GAIN ADJ.

◀ NOTE ▶

This Adjustment should be performed only after completion of 7-7-5. Normal Audio PB Frequency Response Adj.

BOARD	AUDIO (1) C.B.A. (E7)
TP	TP40005 (CH1)(G-1), TP40007 (CH2)(E-1)
ADJ.	VR40003 (CH1)(F-1), VR40008 (CH2)(D-1)
TAPE	VFM8080HQFP, PORTION : 5
INPUT	
MODE	PLAYBACK
M. EQ	OSCILLOSCOPE
SPEC.	CH1: 300mVp-p ± 15mVp-p CH2: 310mVp-p ± 15mVp-p

◀ SET UP ▶

DOLBY NR : OFF (MENU NO.3001)
AUDIO CH2 : AUDIO (MENU NO.3006)

1. Connect a scope to TP40005 (CH1) and TP40007 (CH2), and adjust VR40003 (CH1) and VR40008 (CH2) so that the levels become 300mVp-p ± 15mVp-p (CH1) and 310mVp-p ± 15mVp-p (CH2) as shown in Figure E49.




Figure E49

7-7-7. NORMAL AUDIO ERASE CURRENT ADJ.

BOARD	AUDIO (1) C.B.A. (E7)
TP	TP40002 (CH1)(A-3), TP40004 (CH2)(E-3)
ADJ.	TL40002 (A-3), TL40003 (CH1)(A-3), TL40004 (CH2)(B-3)
TAPE	BLANK TAPE
INPUT	
MODE	REC
M. EQ	FREQUENCY COUNTER, OSCILLOSCOPE
SPEC.	70KHz ± 1KHz

◀ SET UP ▶

S-VHS REC : ON (MENU NO.2006)
CH1 REC : CH1 (MENU NO.3005)
AUDIO CH2 : AUDIO (MENU NO.3006)

1. Connect a frequency counter to TP40002 and adjust TL40002 so that the frequency becomes 70KHz ± 1KHz.
2. Connect the oscilloscope to TP40002 (CH1) and TP40004 (CH2), and adjust TL40003 (CH1) and TL40004 (CH2) so that the level becomes maximum.

7-7-8. NORMAL AUDIO BIAS CURRENT ADJ.

BOARD	AUDIO (1) C.B.A. (E7)
TP	A/C HEAD
ADJ.	S-VHS : TL40001 (CH1)(A-2), TL40005 (CH2)(B-2) VHS : VR40004 (CH1)(A-1), VR40009 (CH2)(B-2)
TAPE	VHS, S-VHS BLANK TAPE
INPUT	NO SIGNAL
MODE	REC
M. EQ	V.T.V.M. (D.V.M.)
SPEC.	S-VHS : 6.5mVrms ± 0.1mVrms VHS : 5.0mVrms ± 0.1mVrms

◀ SET UP ▶

S-VHS REC : ON (MENU NO.2006)
CH1 REC : CH1 (MENU NO.3005)
AUDIO CH2 : AUDIO (MENU NO.3006)

1. Insert the S-VHS blank tape and place the deck in the REC mode.
2. Connect the V.T.V.M.(D.V.M.) to the A/C Head as shown in Figure E50.
3. Adjust TL40001 (CH1) and TL40005 (CH2) so that the level becomes 6.5mVrms ± 0.1mVrms.
4. Insert the VHS blank tape and place the deck in the REC mode.
5. Adjust VR40004 (CH1) and VR40009 (CH2) so that the level becomes 5.0mVrms ± 0.1mVrms.




Figure E50

7-7-9. NORMAL AUDIO FREQUENCY RESPONSE ADJ.

BOARD	AUDIO (1) C.B.A. (E7)
TP	TP40005 (G-1), TP40007 (E-1)
ADJ.	VHS: J40004 (CH1)(B-1), J40003 (CH2)(C-1) S-VHS: C40053 (CH1)(F-1), C40118 (CH2)(C-2)
TAPE	VHS, S-VHS BLANK TAPE
INPUT	1K, 5K, 8K, 10K -20dBm SINE WAVE SIGNAL
MODE	PLAYBACK
M. EQ	V.T.V.M. (D.V.M.)
SPEC.	WITHIN $\pm 2\text{dBm}$

◀ SET UP ▶

S-VHS REC : OFF (MENU NO.2006)
 AUDIO CH2 : AUDIO (MENU NO.3006)
 DOLBY NR : OFF (MENU NO.3001)
 AUDIO LIMITER : OFF (MENU NO.3002)
 CH1 REC : CH1 (MENU NO.3005)
 AUDIO CH2 : AUDIO (MENU NO.3006)
 INPUT AUDIO LEVEL SW (NORM/Hi-Fi) : 0dBs
 NORM. AUDIO (CH1/2) LEVEL CONTROL : CENTER

- Record -20dBm sine wave signal (1KHz, 5KHz, 8KHz, 10KHz) on both S-VHS and VHS tapes, with the machine in the respective mode.
- Read the level at TP40005 (CH1) and TP40007 (CH2) while playing back the 1KHz section of VHS tape. These are the reference level.
- Play back the 5KHz, 8KHz and 10KHz sections.
- Confirm that these higher frequency playback level match that of the 1KHz level to within $\pm 2\text{dB}$.
- If the 8KHz playback level is more than +2dB higher than the 1KHz level, remove jumpers J40004 (CH1) and/or J40003 (CH2).
- Repeat step 2 to 4, playing back the S-VHS tape.
- If the 8KHz playback level is more than +2dB higher than the 1KHz level, remove C40053 (CH1) and/or C40118 (CH2).

7-7-10. NORMAL AUDIO TIME CODE METER ADJ.

BOARD	AUDIO (2) C.B.A. (E8)
TP	AUDIO LEVEL CH2 METER
ADJ.	VR41014 (A-1)
TAPE	BLANK TAPE
INPUT	TIME CODE SIGNAL (or 300Hz, 1Vp-p sine wave signal)
MODE	REC
M. EQ	
SPEC.	0 ± 0.5

◀ SET UP ▶

S-VHS REC : OFF (MENU NO.2006)
 AUDIO CH2 : LTC (MENU NO.3006)
 CH2 METER : AUDIO CH2

- Supply a Time Code Signal (or 300Hz, 1Vp-p sine wave signal) to the TIME CODE IN connector.
- Adjust VR41014 so that needle of Audio level CH2 Meter reaches "0 ± 0.5 " as shown in Figure E51.




Figure E51

7-7-11. Hi-Fi AUDIO HEAD SWITCHING SHIFTER ADJ.

◀ NOTE ▶

This adjustment should be performed only after completion of 7-3-1. PG Shifter Adj.

BOARD	AUDIO (2) C.B.A. (E8)
TP	TP41004 (F-1), TP41006 (F-1)
ADJ.	VR41004 (G-1)
TAPE	VFM8080HQFP, PORTION : 1
INPUT	
MODE	PLAYBACK
M. EQ	OSCILLOSCOPE
SPEC.	FIG. E52

◀ SET UP ▶

S-VHS REC : ON (MENU NO.2006)

- Adjust VR41004 so that disappear the drop-out at the (a) and (b) positions as shown in Figure E52.
- Turn the Tracking VR and then confirm that disappear the drop-out at the (a) and (b) positions.
- If not, repeat the steps 1 and 2 until that disappear the drop-out.




Figure E52

7-7-12. Hi-Fi AUDIO CARRIER FREQUENCY ADJ.

BOARD	AUDIO (2) C.B.A. (E8)
TP	TP41005 (CH1)(E-2), TP41008 (CH2)(F-3)
ADJ.	VR41002 (CH1)(C-1), VR41006 (CH2)(F-3)
TAPE	
INPUT	NO SIGNAL
MODE	EJECT (E-E)
M. EQ	FREQUENCY COUNTER
SPEC.	CH1 : 1.3MHz \pm 10KHz CH2 : 1.7MHz \pm 10KHz

« NOTE »

If the signal level is too low to trigger frequency counter, adjust VR41003 (L CH) and VR41007 (R CH) clockwise. And then refer to 7-7-14. Hi-Fi Audio Rec Current Adj. for the correct setting of these VRs, after this adjustment.

« SET UP »

S-VHS REC : ON (MENU NO.2006)

Hi-Fi INPUT SELECT : Hi-Fi INPUT (MENU NO.3004)

1. Ground the Hi-Fi Audio Inputs (CH1 & CH2).
2. Connect the frequency counter to TP41005 (CH1) and adjust VR41002 (CH1) so that the frequency becomes 1.3MHz \pm 10KHz.
3. Connect the frequency counter to TP41008 (CH1) and adjust VR41006 (CH2) so that the frequency becomes 1.7MHz \pm 10KHz.

2. Connect the spectrum analyzer to TP41005 (CH1) and set the center frequency to 1.3MHz.
3. Adjust VR41001 (CH1) so that the width of the "fw" portion becomes 100KHz \pm 5KHz as shown in Figure E53.
4. Change the probe of spectrum analyzer from TP41005 (CH1) to TP41008 (CH2) and set the center frequency to 1.7MHz.
5. Adjust VR41005 (CH2) so that the width of the "fw" portion becomes 100KHz \pm 5KHz as shown in Figure E53.




Figure E53

7-7-13. Hi-Fi AUDIO DEVIATION ADJ.

« NOTE »

This adjustment should be performed only after completion of 7-7-2. Hi-Fi Audio Input Level Adj.

A. FACTORY & LEAGAL ADJ.

BOARD	AUDIO (2) C.B.A. (E8)
TP	TP41005 (CH1)(F-1), TP41008 (CH1)(F-1)
ADJ.	VR41001 (CH1)(F-1), VR41005 (CH2)(E-1)
TAPE	
INPUT	1KHz, 0dBm SINE WAVE SIGNAL
MODE	EJECT (E-E)
M. EQ	SPECTRUM ANALYZER
SPEC.	fw = 100KHz \pm 5KHz

« SET UP »

INPUT AUDIO LEVEL SW (Hi-Fi) : 0dBs

Hi-Fi INPUT SELECT : Hi-Fi INPUT (MENU NO.3004)

Hi-Fi REC : ON (MENU NO.3003)

Hi-Fi AUDIO (CH1/2) LEVEL CONTROL : CENTER

1. Supply a 1KHz, 0dBm sine wave signal to the Hi-Fi AUDIO (CH1 & CH2) INPUTs.

B. FIELD ADJ.

BOARD	AUDIO (2) C.B.A. (E8)
TP	Hi-Fi AUDIO OUTPUT (CH1)(CH2)
ADJ.	VR41001 (CH1)(F-1), VR41005 (CH2)(E-1)
TAPE	VFM8080HQFP, PORTION: 5
INPUT	
MODE	PLAYBACK
M. EQ	V.T.V.M. (D.V.M.) or OSCILLOSCOPE
SPEC.	-4dBm \pm 0.5dBm

« SET UP »

OUTPUT AUDIO LEVEL SW (Hi-Fi) : 0dBs

1. Playback the alignment tape VFM8080HQFP portion 5.
2. Connect a V.T.V.M to the Hi-Fi Audio Outputs (CH1, CH2).
3. Adjust VR41001 so that the level becomes -4dBm \pm 0.5 dBm.
4. Adjust VR41005 (CH2) so that the level becomes -4dBm \pm 0.5dBm.

7-7-14. NORMAL AUDIO REC CURRENT ADJ.

BOARD	AUDIO (1) C.B.A. (E7)
TP	NORM./Hi-Fi AUDIO OUT, Hi-Fi AUDIO OUT TP40003 (CH1)(B-1), TP40006 (CH2)(C-1)
ADJ.	VR40005 (CH1)(E-1), VR40010 (CH2)(D-1)
TAPE	S-VHS BLANK
INPUT	1KHz, 0dBm SINE WAVE SIGNAL
MODE	REC & PLAY
M. EQ	V.T.V.M. (D.V.M.)
SPEC.	0dBm \pm 1dBm

« SET UP »

S-VHS REC : ON (MENU NO.2006)
 DOLBY NR : OFF (MENU NO.3001)
 AUDIO LIMITER : OFF (MENU NO.3002)
 CH1 REC : CH1 (MENU NO.3005)
 AUDIO CH2 : AUDIO (MENU NO.3006)
 INPUT AUDIO LEVEL SW (NORM./Hi-Fi) : 0dBs
 NORM. AUDIO (CH1/2) LEVEL CONTROL : CENTER

1. Connect the V.T.V.M.s to the deck as shown in Figure E54. Note that only one channel will be adjusted at a time.
2. Supply a 1KHz, 0dBm sine wave signal to NORM./Hi-Fi AUDIO INPUT (CH1).
3. Place the deck in the REC mode with S-VHS mode.
4. Adjust VR40005 (CH1) so that V.T.V.M. (2) reads approximately 0.8Vrms (2.26Vp-p).
 Suppose that the indicated value on V.T.V.M. (1) is 0dBm.
5. Play back the recorded portion, and note the amount of difference between V.T.V.M. (1) and (2).
6. Place the deck in the REC mode again, and re-adjust VR40005 (CH1) slightly, and repeat step 5, noting the new difference.
7. Repeat this step 3 to 6 until record and playback difference is minimized (0dBm \pm 1dBm).
8. Repeat the above procedure again for channel 2, using the other set of test point (TP40006) and VR (VR40010).




Figure E54

7-7-15. Hi-Fi AUDIO REC CURRENT ADJ.

BOARD	AUDIO (2) C.B.A. (E8)
TP	TP5001 (HEAD AMP C.B.A.)
ADJ.	VR41007 (B-1), VR41003 (B-1)
TAPE	S-VHS RECORDED TAPE
INPUT	NO SIGNAL
MODE	REC
M. EQ	OSCILSCOPE
SPEC.	CH1: 290mVp-p \pm 5mVp-p CH2: 210mVp-p \pm 5mVp-p

« SET UP »

S-VHS REC : ON (MENU NO.2006)
 Hi-Fi REC : ON (MENU NO.3003)
 Hi-Fi INPUT SELECT : Hi-Fi INPUT (MENU NO.3004)

1. Ground the Hi-Fi AudioInput.
2. Turn VR41003 fully counter-clockwise.
3. Adjust VR41007 so that the level becomes 210mVp-p \pm 5mVp-p as shown in Figure E55.
4. Adjust VR41003 so that the level becomes 290mVp-p \pm 5mVp-p as shown in Figure E56.




Figure E55




Figure E56

7-8.OTHER SECTION

7-8-1. VITC MUTE PULSE ADJ.

BOARD	TIME CODE C.B.A.
TP	TP68003 (B-14) TP3004 (C-3): VIDEO I/O C.B.A.
ADJ.	VR68001 (B-14)
TAPE	S-VHS BLANK
INPUT	COLOR BAR SIGNAL (LINE)
MODE	REC
M. EQ	OSCILLOSCOPE
SPEC.	$T = 1 \mu\text{sec} \pm 0.3 \mu\text{sec}$.

◀ SET UP ▶

VITC REC : ON (MENU NO.7003)

INPUT SW : LINE

ALL DEL SW (SW68001: TC C.B.A.) : ON

1. Connect a scope to TP3004 for CH-1 and TP68003 for CH-2 and expand V-Sync portion as shown in Figure E57.
2. Adjust VR68001 so that the "T" becomes $1 \mu\text{sec} \pm 0.3 \mu\text{sec}$ as shown in Figure E57.




Figure E57

7-8-2. OSD CHARACTER WIDTH ADJ.

BOARD	REAR AMP C.B.A. (E28)
TP	VIDEO MONITOR OUT
ADJ.	CT6601 (B-5)
TAPE	
INPUT	NO SIGNAL
MODE	EJECT (E-E)
M. EQ	OSCILLOSCOPE
SPEC.	$T = 52 \mu\text{sec} \pm 0.5 \mu\text{sec}$.

◀ SET UP ▶

DIAL MODE : MENU

1. Connect the oscilloscope to VIDEO MONITOR OUT.
2. Turn the JOG dial so that the SETUP-MENU NO. becomes 1001 (flash).
3. Adjust CT6601 so that the "T" becomes $52 \mu\text{sec} \pm 0.5 \mu\text{sec}$ as shown in Figure E58.




Figure E58

7-8-3. FLYING ERASE CURRENT ADJ.

BOARD	AUDIO (2) C.B.A. (E8)
TP	TP41009 (HOT)(A-1), TP41010 (GNE)(A-1)
ADJ.	VR41015 (B-1), VR41016 (B-1)
TAPE	S-VHS RECORDED TAPE
INPUT	COLOR BAR SIGNAL (LINE)
MODE	VIDEO INSERT EDIT
M. EQ	OSCILLOSCOPE
SPEC.	$150\text{mVp-p} \pm 10\text{mVp-p}$

◀ SET UP ▶

IMAGE MODE SELECT : NORMAL (MENU NO.2001)

VIDEO MODE : COLOR (MENU NO.2002)

S-VHS REC : ON (MENU NO.2006)

INPUT SW : LINE

VIDEO LEVEL control : PUSH (AGC : ON)

1. Place the deck in the video insert edit node.
2. Connect the GND of oscilloscope to TP41010.
3. Connect a scope to TP41009 (HOT), TP41010 (GND) and adjust VR41015 and VR41016 so that the "A" and "B" levels become $150\text{mVp-p} \pm 10\text{mVp-p}$ as shown in Figure E59.




Figure E59


SECTION 8

BLOCK DIAGRAMS


CONTENTS

OVERALL BLOCK DIAGRAM	BLK-3
FRONT BLOCK DIAGRAM	BLK-4
SYSTEM CONTROL BLOCK DIAGRAM	BLK-5
SERVO BLOCK DIAGAM	BLK-6
VIDEO OVERALL BLOCK DIAGRAM	BLK-6
VIDEO C BLOCK DIAGRAM	BLK-7
VIDEO DIGITAL BLOCK DIAGRAM.....	BLK-8
VIDEO I/O BLOCK DIAGRAM.....	BLK-9
NORMAL AUDIO BLOCK DIAGRAM	BLK-10
Hi-Fi AUDIO BLOCK DIAGAM	BLK-11
TBC (1) BLOCK DIAGRAM	BLK-12
TBC (2) BLOCK DIAGRAM	BLK-13
INTERFACE BLOCK DIAGRAM	BLK-14

OVERALL BLOCK DIAGRAM



FRONT BLOCK DIAGRAM




REF. No. 62000 SERIES


The schematic diagram illustrates the internal circuitry of a VCR, centered around the IC2 (CPU). The pinout for IC2 is as follows:

PIN	PORT	FUNCTION	ACTIVE	FUNCTION	PORT	PIN	
3	P63	T REEL RSF	L/H	T REEL FG	P26	26	
4	P64	S REEL RSF	L/H	S REEL FG	P26	25	
5	P61	S REEL RSF	L/H	FWD PB/REC (CNT1)	P30	47	
6	P60	FE HEAD	H	REV PB (CNT2)	P31	46	
7	P57	RELAY	L/H	HIGH SPEED PB (CNT3)	P32	45	
8	P56	RELAY	L/H	FWD (CNT4)	P33	44	
9	P55	VIDEO REC	H	READY-OFF (CNT6)	P84	2	
10	P54	FLYING ERASE	L	S DAC	A#4	66	
11	P53	VIDEO ERASE R	L	T DAC	A#5	65	
12	P52	VIDEO ERASE L	L	SF AD	A#2	68	
14	P50	POWER OFF	H	SR AD	A#3	67	
31	OSC2	REF OSC	-	AD2	A#6	64	
32	OSC1	REF OSC	-	AD3	A#7	63	
20	P44	COUNTER INH	H	+5V	AVDD	72	
21	P43	READ	L	V REF	VREF	71	
22	P42	WRITE	H	V REF	VREF	82	
24	P40	POWER FAILURE	H	GND	AVSS	80	
16	RST	RESET	L	H	PINCH ON	P94	55
73	VDD	+5V	+5V	L	PINCH ON	P93	56
27	P24	HEAD SW	-	H	UNLOADING	P92	57
38	P17	SUPPLY PHOTO	-	H	LOADING MOTOR ON	P91	58
37	P16	TAKE-UP PHOTO	-	H	SPEED DOWN	P90	59
89	A#1	CASSETTE SWITCH	L	H	REEL SOLENOID ON	P67	83
84	P66	SENSOR LED	-	L	SOLENOID ABNOR	P21	29
70	A#6	DEW	H	H	FAN MOTOR LOCK	P41	23
38	P15	CASSETTE DOWN	L	H	B/W	P74	77
40	P13	MODE PLAY	L	H	COLOR	P73	76
41	P12	MODE LOAD	L	L	VIDEO EE	P72	70
42	P11	MODE STOP	L	H	AUDIO DUB	P70	81
43	P10	MODE EJECT	L	-	SC#	S#T#	48
30	P14	W/SAFETY TAB	L	-	SDA	S#I#	49
18	P46	AUDIO MASK	-	-	S#O#	S#B#	50
17	P47	AUDIO ENABLE	-	-	SYS CLK	P97	52
76	P75	A LATCH	-	-	SYS IF	P96	53
74	P77	A CLOCK	-	-	SYS SYS	P95	54
75	P76	A DATA	-	L	EXT	P41	13
19	P45	+5V	+5V	-	CAPSTAN FG	P22	28



The diagram also shows various other components and their connections, including IC101 (V. REF), IC2501-2507 (video and audio processing), IC2701 (oscillator), and IC2702 (servo motor driver). It includes a detailed pinout for the IC2 (CPU) and a list of components and their functions, such as the motor base, sensor LED, and various switches and relays.





SERVO BLOCK DIAGRAM






VIDEO OVERALL BLOCK DIAGRAM





VIDEO C BLOCK DIAGRAM



 LUMINANCE MAIN SIGNAL PATH IN REC MODE
 COMPOSITE MAIN SIGNAL PATH IN REC MODE

 CHROMINANCE MAIN SIGNAL PATH IN REC MODE
 CHROMINANCE MAIN SIGNAL PATH IN PLAYBACK




REF. NO. 9000 SERIES.


 LUMINANCE MAIN SIGNAL PATH IN REC MODE
 COMPOSITE MAIN SIGNAL PATH IN REC MODE

 CHROMINANCE MAIN SIGNAL PATH IN REC MODE
 CHROMINANCE MAIN SIGNAL PATH IN PLAYBACK MODE

 COMPONENT MAIN SIGNAL PATH




VIDEO DIGITAL BLOCK DIAGRAM

 LUMINANCE MAIN SIGNAL PATH IN REC MODE
 LUMINANCE MAIN SIGNAL PATH IN PLAYBACK MODE


CHROMINANCE MAIN

CHROMINANCE MAIN





← LUMINANCE MAIN SIGNAL PATH IN REC MODE
← LUMINANCE MAIN SIGNAL PATH IN PLAYBACK MODE

← CHROMINANCE MAIN SIGNAL PATH IN REC MODE
← CHROMINANCE MAIN SIGNAL PATH IN PLAYBACK MODE





VIDEO I/O BLOCK DIAGRAM






NORNAL AUDIO BLOCK DIAGRAM







AUDIO (1) C. B. A.

[illegible]





TBC (1) BLOCK DIAGRAM





TBC (2) BLOCK DIAGRAM






CHROMINANCE MAIN SIGNAL PATH


CHROMINANCE MAIN SIGNAL PATH


COMPONENT MAIN SIGNAL PATH


COMPOSITE MAIN SIGNAL PATH



INTERFACE BLOCK DIAGRAM







SECTION 9

SUPPLEMENT

CONTENTS

VOLTAGE TABLE

POWER 1,2	9-2
REEL DRIVE C.B.A.	9-2
MIC JACK C.B.A.	9-2
HEAD AMP C.B.A.	9-2
VIDEO C C.B.A.	9-3
VIDEO DIGITAL C.B.A.	9-6
SERVO & SYSTEM CONTROL C.B.A.	9-11
VIDEO I/O C.B.A.	9-18
TBC (1) C.B.A.	9-22
TBC (2) C.B.A.	9-29
AUDIO (1) C.B.A.	9-32
AUDIO (2) C.B.A.	9-31
INTERFACE C.B.A.	9-37
FRONT C.B.A.	9-40
REAR AMP C.B.A.	9-41

POWER 1, 2

Ref. No.	IC1001 (SCM-5)							IC1002 (SCM-5)			Q1001 (SCM-5)				Q1002 (SCM-5)					
Mode	1	2	3	4	5	6	7	K	R	A	1	2	3	4	E	C	B			
STOP	-86.7	-0.1	-0.2	-0.2	14.9	0.2	0.1	4.3	2.3	-0.2	5.4	4.4	0.2	14.9	11.6	13.4	12.2			
REC	-100.8	-0.1	-0.2	-0.2	15.2	0.2	0.1	4.3	2.3	-0.2	5.4	4.4	0.2	15.1	11.3	13.2	12.2			

REEL DRIVE C.B.A.

Ref. No.	IC2701 (SCM-78)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	1.4	0.1	1.3	1.4	2.5	2.4	2.5	2.4	2.4	2.5	0	0	4.7	3.4	2.4	2.1	4.1	0.6	1.7	0.1
REC	2.3	0.1	2.5	1.4	2.5	2.5	2.5	2.5	2.5	2.5	0	0	4.7	3.4	2.4	2.2	4.1	0.6	0.7	0.1
Ref. No.	IC2701 (SCM-78)																			
Mode	21	22	23	24																
STOP	0	0.7	0.5	5.1																
REC	0	0.7	1.4	5.2																
Ref. No.	IC2702 (SCM-78)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0.5	0.1	2.3	1.4	2.4	2.5	2.5	2.5	2.5	2.4	0	0	4.7	3.4	2.6	2.3	4.1	0.6	0.5	0.1
REC	1.5	0.1	1.5	1.4	2.5	2.5	2.5	2.5	2.5	2.5	0	0	4.7	3.4	2.5	2.3	4.1	0.6	0.5	0.1
Ref. No.	IC2702 (SCM-78)								IC2703 (SCM-78)											
Mode	21	22	23	24	1	2	3	4	5	6	7	8								
STOP	0	0.7	2.3	5.2	0	0.2	0.1	0	0.1	0.1	3.0	4.7								
REC	0	0.7	1.7	5.2	3.5	0.1	0.1	0	0.1	0.1	2.9	4.7								
Ref. No.	IC2704 (SCM-78)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	2.6	2.4	0	0	0	0	0	0	0	4.7	0.1	2.4	2.4	2.4	2.6	4.7				
REC	2.5	2.4	0	0	0	0	0	0	0	4.7	0.1	2.4	3.1	2.4	2.6	4.7				
Ref. No.	IC2705 (SCM-78)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	0.1	0.1	4.7	2.2	2.1	2.2	2.1	2.9	2.4	1.8	2.4	0	4.7	0.1						
REC	2.4	2.8	4.7	2.1	2.1	2.1	2.1	2.9	2.4	1.8	2.4	0	4.7	0.1						
Ref. No.	IC2706 (SCM-78)								Q2701 (SCM-78)				QR2701 (SCM-78)							
Mode	1	2	3	4	5	6	7	8	E	C	B	E	C	B						
STOP	4.6	4.6	4.6	0	2.4	2.4	2.4	11.7	2.8	3.8	3.4	0	4.7	0.1						
REC	4.6	4.6	4.6	0	2.4	2.4	2.4	11.7	2.8	3.8	3.4	0	4.7	0.1						

MIC JACK C.B.A.

Ref. No.	IC4301 (SCM-54)								Q4301 (SCM-54)											
Mode	1	2	3	4	5	6	7	8	E	C	B									
STOP	5.5	5.5	5.5	0	5.6	5.7	5.7	10.9	10.9	11.6	11.6									
REC	5.5	5.5	5.5	0	5.6	5.7	5.7	10.9	10.9	11.6	11.6									

HEAD AMP C.B.A.

Ref. No.	IC5001 (SCM-77)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	2.3	0.8	0.6	0	0.6	0.8	4.9	0.8	0.6	0	0.6	0.8	0	0	0	0	0	0	0.6	1.7
REC	2.3	0	0	0	0	0	0.3	0	0	0	0	0	0	5.9	5.8	5.9	11.2	0	2.7	0
Ref. No.	IC5001 (SCM-77)																			
Mode	21	22	23	24	25	26	27	28	29	30										
STOP	0	0	0	4.6	4.9	1.8	3.1	0	1.9	1.9										
REC	4.6	0	4.6	0	0.3	0.3	0.1	0	11.1	3.9										
Ref. No.	IC5002 (SCM-77)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0.3	0	2.8	1.2	3.7	4.9	2.9	2.3	4.9	0	0	2.5	0	0	0	0.8	0.7	0	0.7	0.8
REC	4.0	1.3	2.7	1.3	0.1	4.9	3.7	2.3	4.9	0	0	2.5	0	0	0	0	0	0	0	0
Ref. No.	IC5002 (SCM-77)				Q5001 (SCM-77)			Q5002 (SCM-77)			Q5003 (SCM-77)						Q5004 (SCM-77)			
Mode	21	22	23	24	E	C	B	E	C	B	1	2	3	4	5	6	E	C	B	
STOP	0	0	0	0	2.4	0	1.8	0	0	0	0	0	0	0	0	0	0	0	0	
REC	0	7.3	0	0.6	0.3	0	0	0	0	0.8	0	0.7	0	0	0.7	0	0	0	0.8	
Ref. No.	Q5005 (SCM-77)						QR5001 (SCM-77)													
Mode	E	C	B	E	C	B														
STOP	0	0	0.8	0	0	5.0														
REC	0	0	0	0	2.5	0.3														

VIDEO C C.B.A.

Ref. No.	IC9101 (SCM-17)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	1.8	3.4	1.4	3.1	0	0	0	5.0	2.4	5.0	2.2	2.4	2.8	2.3	2.0	2.3	2.0	2.1	5.0	2.4
REC	1.8	3.4	1.4	2.9	0	0	0	5.0	2.4	5.0	2.2	2.4	2.8	2.3	2.0	2.3	2.0	2.1	5.0	2.4
Ref. No.	IC9101 (SCM-17)																			
Mode	21	22	23	24	25	26	27	28												
STOP	5.0	0	0	0	2.3	1.3	3.2	1.6												
REC	5.0	0	0	0	2.3	1.3	3.2	1.6												
Ref. No.	IC9102 (SCM-17)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	1.6	3.2	1.3	2.3	0	0	0	5.0	2.4	5.0	2.1	2.0	2.3	2.0	2.1	2.3	2.0	2.2	5.0	2.4
REC	1.6	3.2	1.3	2.3	0	0	0	5.0	2.4	5.0	2.1	2.0	2.3	2.0	2.1	2.3	2.0	2.2	5.0	2.4
Ref. No.	IC9102 (SCM-17)																			
Mode	21	22	23	24	25	26	27	28												
STOP	5.0	0	0	0	2.3	1.2	3.2	1.6												
REC	5.0	0	0	0	2.3	1.3	3.2	1.6												
Ref. No.	IC9103 (SCM-17)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	5.0	1.7	1.4	2.8	1.5	2.4	1.8	2.0	1.6	1.4	1.8	3.5	1.4	3.3	2.4	3.2	2.6	2.4	1.6	3.3
REC	5.0	1.6	1.5	3.1	1.6	2.1	1.7	1.7	1.9	1.7	1.9	3.5	1.3	3.2	2.3	3.0	3.2	2.4	1.6	3.2
Ref. No.	IC9103 (SCM-17)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	1.2	3.0	2.3	2.9	2.4	2.1	0.1	5.0	2.4	5.0	0.1	2.4	2.4	0.3	5.0	0.1	5.0	0.1	0.4	4.9
REC	1.2	2.4	2.2	2.5	2.6	2.1	0.1	5.0	2.7	5.2	0	2.5	2.5	0.3	5.1	0.1	5.1	0.1	0	5.0
Ref. No.	IC9103 (SCM-17)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	4.7	0.5	0.1	0.1	5.0	0.3	0.3	0.3	0.3	0	5.0	0.1	1.9	3.4	2.7	2.6	2.6	2.4	2.4	2.4
REC	4.8	0.4	0.1	0.1	5.1	0.3	0.3	0.3	0.3	0	5.1	0.1	1.9	3.4	2.5	2.4	2.4	2.5	2.4	2.4
Ref. No.	IC9103 (SCM-17)																			
Mode	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80
STOP	2.4	2.4	3.7	3.2	3.1	3.2	3.1	2.6	3.1	1.2	3.6	2.0	0.1	0.1	0.1	0.1	2.8	5.1	5.1	5.1
REC	2.4	2.4	2.4	2.6	2.4	3.2	2.9	2.6	3.2	1.2	3.5	1.9	0.1	0.1	0.1	0.1	2.8	5.1	5.1	5.1
Ref. No.	IC9103 (SCM-17)																			
Mode	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
STOP	0.1	2.4	0.1	0	0	0	0	0.3	0.3	0.3	0.3	0	0	0	0	0	0	0	0	0
REC	0	2.4	0.1	0	0	0	0	0.3	0.3	0.3	0.3	0	0	0	0	0	0	0	0	0
Ref. No.	IC9104 (SCM-17)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	1.9	3.4	1.3	3.0	2.4	2.5	3.1	2.4	2.5	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	0	5.0
REC	1.9	3.4	1.3	3.0	2.4	2.5	3.1	2.4	2.5	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	0	5.0
Ref. No.	IC9104 (SCM-17)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36				
STOP	3.3	4.8	3.8	3.8	3.5	0	4.3	0	4.2	0	4.8	5.0	0	0	0	0				
REC	3.3	4.8	3.8	3.8	3.5	0	4.3	0	4.2	0	4.8	5.0	0	0	0	0				
Ref. No.	IC9105 (SCM-17)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	2.6	2.4	5.0	0	2.3	0	2.8	2.4	2.2	3.0	1.4	3.4	0	1.9	2.1	2.3	2.0	2.0	2.2
REC	0	2.6	2.4	5.0	0	2.3	0	2.8	2.4	2.2	3.0	1.4	3.4	0	1.9	2.1	2.3	2.0	2.0	2.2
Ref. No.	IC9105 (SCM-17)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	1.3	3.2	1.6	0	3.8	2.6	0	5.0	0	5.0	0	0	0	5.0	5.0	5.0	5.0	2.5	2.3	1.4
REC	1.3	3.2	1.6	0	3.8	2.6	0	5.0	0	5.0	0	0	0	5.0	5.0	5.0	5.0	2.5	2.3	1.4
Ref. No.	IC9105 (SCM-17)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52								
STOP	5.0	5.0	0.3	0.1	4.9	4.8	0.5	0	0	0.2	4.0	5.0								
REC	5.0	5.0	0.3	0.1	4.9	4.8	0.4	0	0	0.2	4.0	5.0								
Ref. No.	IC9201 (SCM-18)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	3.2	0	5.0	2.7	0	0.1	2.3	5.0	0	2.3	5.0	0	1.5	1.8	1.6	1.6	2.0	5.0	0	1.0
REC	3.2	0	5.0	2.7	0	0.1	2.3	5.0	0	2.3	5.0	0	1.5	1.8	1.6	1.6	2.0	5.0	0	1.0

Ref. No.	IC9201 (SCM-18)																			
Mode	21	22	23	24																
STOP	2.8	1.5	0.2	2.4																
REC	2.8	1.5	0.2	2.4																
Ref. No.	IC9202 (SCM-18)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	2.9	4.7	2.4	3.0	1.0	4.2	2.1	2.3	2.6	0	2.8	2.8	3.2	4.8	4.7	3.1	0	3.5	0	4.0
REC	2.9	4.7	2.4	3.0	1.0	4.2	2.1	2.3	2.6	0	2.8	2.8	3.2	4.8	4.7	3.1	0	3.5	0	4.0
Ref. No.	IC9202 (SCM-18)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36				
STOP	4.0	0.2	3.8	0.2	4.7	3.1	2.6	3.6	3.6	0	0	0	4.0	2.8	3.8	2.8				
REC	4.0	0.2	3.8	0.2	4.7	3.1	2.6	3.6	3.6	0	0	0	4.0	2.8	3.8	2.8				
Ref. No.	IC9204 (SCM-18)					IC9222 (SCM-18)			IC9401 (SCM-19)											
Mode	1	2	3	4	5	I	G	O	1	2	3	4	5	6	7	8				
STOP	0.2	3.8	0	0.1	4.7	11.5	0	5.0	2.8	0.1	2.8	0	0	4.7	2.1	0				
REC	0.2	3.8	0	0.1	4.7	11.5	0	5.0	2.8	0.1	2.8	0	0	4.7	2.1	0				
Ref. No.	IC9402 (SCM-19)																			
Mode	1	2	3	4	5	6	7	8												
STOP	4.7	2.8	2.5	4.0	0	2.8	0	4.0												
REC	4.7	2.8	2.5	4.0	0	2.8	0	4.0												
Ref. No.	IC9403 (SCM-19)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	2.7	2.5	2.9	2.3	2.7	3.0	1.6	1.8	2.4	2.4	1.8	2.2	2.2	2.8	0	0	1.9	2.8	2.0
REC	0	2.7	2.5	2.9	2.3	2.7	3.0	1.6	1.8	2.4	2.4	1.8	2.1	2.1	2.8	0	0	1.9	2.8	2.0
Ref. No.	IC9403 (SCM-19)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	2.3	0	5.0	2.8	2.5	2.5	0	0	0	0	0	0	0	0	0	0	2.9	0	2.9	2.7
REC	2.3	0	5.0	2.8	2.5	2.5	0	0	0	0	0	0	0	0	0	0	2.9	0	2.9	2.7
Ref. No.	IC9403 (SCM-19)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56				
STOP	2.7	0	2.4	0	0	3.5	2.1	2.1	2.4	3.5	0	3.1	3.1	3.1	3.1	0				
REC	2.7	2.7	2.4	0	0	3.5	2.1	2.1	2.4	3.5	0	3.1	3.1	3.1	3.1	0				
Ref. No.	IC9404 (SCM-19)																IC9405 (SCM-19)			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	I	G	O	
STOP	2.3	0.1	1.6	0	1.6	1.6	4.9	2.3	2.3	0	2.3	5.0	4.7	2.3	0	2.3	11.4	0	5.0	
REC	2.3	0.1	1.6	0	1.6	1.6	4.9	2.3	2.3	0	2.3	4.9	4.7	2.3	0	2.3	11.4	0	5.0	
Ref. No.	IC9410 (SCM-19)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	5.0	3.2	3.2	2.9	2.9	4.0	3.5	5.0	4.0	1.7	4.3	0.1	2.1	2.5	2.4	4.9	0	3.0	2.6	3.0
REC	5.0	3.2	3.2	2.9	2.9	4.0	3.5	5.0	4.0	1.7	4.3	0.1	2.1	2.5	2.4	4.9	0	3.0	2.6	3.0
Ref. No.	IC9421 (SCM-19)																			
Mode	21	22	1	2	3	4	5	6	7	8										
STOP	3.5	3.0	3.9	1.8	2.3	0	0	0	0.3	5.0										
REC	3.5	3.0	3.9	1.8	2.3	0	0	0	0.3	5.0										
Ref. No.	Q9101 (SCM-17)			Q9102 (SCM-17)			Q9103 (SCM-18)			Q9201 (SCM-18)			Q9202 (SCM-18)			Q9203 (SCM-18)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	3.6	11.4	4.2	3.7	11.4	4.3	2.2	4.7	3.0	0.9	4.8	1.6	-0.2	4.8	0.5	1.8	4.8	2.4		
REC	3.6	11.4	4.2	3.7	11.4	4.3	2.2	4.7	3.0	0.9	4.8	1.6	-0.2	4.8	0.5	1.8	4.8	2.4		
Ref. No.	Q9204 (SCM-18)			Q9205 (SCM-18)			Q9206 (SCM-18)			Q9401 (SCM-19)			Q9402 (SCM-19)			Q9403 (SCM-19)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	0.6	0	0	0	1.8	0	1.2	-1.8	1.6	-1.0	-0.5	-4.9	-1.2	2.6	4.7	3.2		
REC	0	0	0.6	0	0	0	1.8	0	1.2	-1.8	1.6	-1.0	-0.5	-4.9	-1.2	2.6	4.7	3.2		
Ref. No.	Q9404 (SCM-19)			Q9407 (SCM-19)			Q9408 (SCM-19)			Q9410 (SCM-19)			Q9411 (SCM-19)			IC9413 (SCM-19)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0.9	-4.9	0.2	2.1	4.7	2.8	2.2	4.7	2.8	2.6	4.8	3.2	-1.0	4.7	-0.3	-0.8	4.7	-0.1		
REC	0.9	-4.9	0.2	2.1	4.7	2.8	2.2	4.7	2.8	2.6	4.8	3.2	-1.0	4.7	-0.3	-0.8	4.7	-0.1		
Ref. No.	IC9415 (SCM-19)			Q9416 (SCM-19)			Q9418 (SCM-19)			Q9419 (SCM-19)			Q9420 (SCM-19)			Q9421 (SCM-19)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	-0.4	-4.9	-1.0	0.7	3.2	1.4	-1.2	-4.9	-1.8	-1.0	0.9	-0.3	-1.8	-1.8	-2.5	-1.8	-1.8	-4.8		
REC	-0.4	-4.9	-1.0	0.7	3.2	1.4	-1.2	-4.9	-1.8	-1.0	0.9	-0.3	-1.8	-1.8	-2.5	-1.8	-1.8	-4.8		

Ref. No.	QR9402 (SCM-19)			QR9403 (SCM-19)			QR9404 (SCM-19)			QR9405 (SCM-19)			QR9406 (SCM-19)			QR9407 (SCM-19)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	4.7	0	5.4	0	2.9	0.1	0	2.8	0.1	0	0	0.1	4.8	4.8	0.1	4.8	-2.5	4.8		
REC	4.7	0	5.4	0	2.9	0.1	0	2.8	0.1	0	0	0.1	4.8	4.8	0.1	4.8	-2.5	4.8		
Ref. No.	QR9408 (SCM-19)																			
Mode	E	C	B																	
STOP	0	4.8	0.1																	
REC	0	4.8	0.1																	

VIDEO DIGITAL C.B.A.

Ref. No.	IC3602 (SCM-21)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	4.9	5.1	5.0	0.1	0.1	5.0	0.1	0	5.0	5.0	5.0	0.1	0.1	5.0	5.0				
REC	0	4.9	5.0	5.0	-0.1	0	5.0	0.1	0.1	5.0	5.0	5.0	0.1	0.1	5.0	5.0				
Ref. No.	IC3691 (SCM-21)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	5.1	5.1	0.1	5.1	0.1	5.1	0.1	5.0	0.1	5.0	0.5	5.0	5.0	5.0						
REC	5.0	5.1	0.1	5.0	0.1	5.0	0.1	0.1	5.0	5.0	0.2	0.1	5.0	5.0						
Ref. No.	IC3701 (SCM-27)																			
Mode	1	2	3	4	5	6	7	8	9											
STOP	0	0	0	0	0	0	0.1	0	0											
REC	0	0	0	0	0	0	0.1	0	0											
Ref. No.	IC3702 (SCM-27)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	5.0	5.0	0	2.5	2.5	0	0	0.1	5.0	5.0	0	4.9	5.0	5.0						
REC	5.0	5.0	0	2.5	2.5	0	0	0.1	5.0	5.0	0	5.0	5.0	5.1						
Ref. No.	IC3703 (SCM-27)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	5.0	0	0	5.0	0	5.0	0	0	5.0	5.0	0	5.0	5.0	5.0						
REC	5.0	0.1	0.1	5.1	0	5.1	0	0	5.1	5.1	0.1	5.1	5.1	5.1						
Ref. No.	IC3704 (SCM-27)(SCM-29)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	5.0	5.0	0	5.0	0	5.0	0	5.0	0	5.0	5.0	0	0	5.0						
REC	5.0	5.0	0	5.0	0.1	5.0	0	5.0	0	5.0	5.0	0	0	5.0						
Ref. No.	IC3771 (SCM-29)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	1.1	0	0	-0.8	-0.8	0	-4.9	0	0.1	0.1	0.1	-0.8	0	-0.8	0	4.8				
REC	1.1	0	0	-0.8	-0.8	0	-4.9	0	0.1	0.1	0.1	-0.8	0	-0.8	0	4.8				
Ref. No.	IC3781 (SCM-29)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18		
STOP	4.8	0	1.9	3.6	0	3.7	1.9	3.1	3.6	4.1	4.6	1.7	3.1	0	0.3	2.2	2.4	2.8		
REC	4.7	0	1.9	3.6	0	3.6	1.9	3.1	3.6	4.1	4.6	1.7	3.1	0	0.3	2.3	2.5	2.8		
Ref. No.	IC3782 (SCM-29)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	5.0	2.5	2.4	5.0	2.5	2.5	0	2.5	2.5	5.0	2.5	2.5	5.0	5.0						
REC	5.0	2.5	2.4	5.0	2.5	2.5	0	2.5	2.5	5.0	2.5	2.5	5.0	5.0						
Ref. No.	IC3783 (SCM-29)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0	5.0	2.5	0.3	5.0	0.3	0.1	0.4	0.3	0.3	2.5	0.1	0.2	0.2	5.0				
REC	0	0	5.0	2.5	0.3	5.0	0.3	0.1	0.4	0.3	0.3	2.5	0.1	0.2	0.3	5.0				
Ref. No.	IC3801 (SCM-23)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	2.3	2.7	2.1	0.9	2.8	3.4	2.9	4.6	2.3	2.3	2.7	2.2	0.9	2.8	3.4	2.9	0.1	4.9	4.9	2.3
REC	2.3	2.7	2.3	1.2	2.9	3.3	3.0	4.6	2.4	2.3	2.8	2.4	1.2	2.9	3.3	3.0	0.1	4.6	0.2	2.4
Ref. No.	IC3801 (SCM-23)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	2.3	0.1	2.7	2.2	0.9	2.8	3.4	2.1	0.1	2.0	2.8	1.1	1.1	3.8	3.8	3.9	4.1	4.9	0.1	2.3
REC	2.3	0.1	2.8	2.4	1.2	2.9	3.3	2.1	0.1	1.8	3.5	1.1	1.1	3.9	3.8	4.0	4.2	5.0	0.1	2.4
Ref. No.	IC3801 (SCM-23)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	2.3	2.7	2.2	0.9	2.9	3.4	2.9	2.3	2.3	0.1	2.7	2.3	0.9	2.8	3.4	0.1	2.9	4.6	4.7	3.0
REC	2.2	2.9	2.4	1.2	2.9	3.3	3.0	2.4	2.2	0.1	2.8	2.4	1.2	2.9	3.3	0.1	3.0	4.6	4.7	3.0
Ref. No.	IC3801 (SCM-23)																			
Mode	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80
STOP	3.4	2.8	0.9	2.2	2.7	2.3	2.3	1.6	2.5	2.1	0.7	1.4	2.0	1.5	1.5	0.6	2.7	2.6	2.6	0.9
REC	3.3	2.9	1.2	2.4	2.8	2.3	2.4	1.6	2.4	2.2	0.8	1.5	2.1	1.7	1.6	0.6	2.8	2.7	2.7	0.9
Ref. No.	IC3801 (SCM-23)																			
Mode	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
STOP	0.9	1.9	1.4	0.8	0.9	0.8	0.9	5.0	0.1	0.9	0.9	1.0	1.2	1.7	0.1	0.1	2.3	2.3	2.4	2.3
REC	0.9	2.3	1.3	0.8	0.8	0.8	0.8	5.0	0.1	0.8	0.8	0.9	1.1	1.7	0.1	0.1	2.3	2.4	2.4	2.4

Ref. No.	IC3802 (SCM-23)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	1.8	0.7	1.9	0.1	1.8	1.2	1.0	0.9	0.8	0.8	0.8	0.8	0.8	4.2	4.6	0.1	0.1	0.1	2.4	2.4
REC	1.9	0.8	1.9	0.1	1.7	1.0	0.9	0.9	0.9	0.8	0.9	0.8	4.9	4.9	4.9	0.1	0.1	0.1	2.3	2.4
Ref. No.	IC3802 (SCM-23)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	2.3	2.3	2.4	0.1	0.1	2.8	2.3	2.3	4.9	2.3	2.7	4.1	3.9	3.7	3.8	1.1	1.1	4.9	0.1	1.5
REC	2.3	2.3	2.3	0.1	0.1	2.8	2.3	2.3	4.9	2.3	2.7	4.1	3.9	3.8	3.8	1.1	1.1	4.9	0.1	3.4
Ref. No.	IC3802 (SCM-23)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	3.1	4.6	3.0	3.4	3.0	0.7	1.9	2.3	2.2	2.3	0.1	0.1	0.1	0.1	0.1	4.5	0.1	0.1	4.9	4.5
REC	1.8	4.5	2.9	3.2	2.8	1.2	2.4	2.7	2.2	2.3	0.1	0.1	0.1	0.1	0.1	4.5	0.1	0.1	4.9	4.5
Ref. No.	IC3802 (SCM-23)																			
Mode	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80
STOP	4.5	4.5	0.1	4.5	4.5	4.5	4.5	0.4	0.4	0.1	0.1	0.1	0.1	1.0	0.1	2.5	1.6	1.3	1.7	1.5
REC	4.5	4.5	0.1	4.5	4.5	4.5	4.5	0.4	0.5	0.1	0.1	0.1	0.1	1.0	0.1	2.5	1.5	1.7	2.1	1.5
Ref. No.	IC3802 (SCM-23)																			
Mode	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
STOP	0.6	2.1	2.5	1.6	1.8	1.6	4.9	0.1	1.3	1.3	1.3	1.3	1.3	1.3	0.1	0.3	0.1	0.1	0.2	4.8
REC	0.8	2.1	2.4	1.6	1.7	1.4	4.9	0.1	1.2	1.2	1.2	1.2	1.1	1.2	0.1	0.4	0.1	0.1	0.2	4.7
Ref. No.	IC3803 (SCM-24)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	2.1	1.9	1.7	3.7	4.9	0.1	5.0	0.1	0.1	2.3	2.3	0.1	0.1	0.1	4.9	4.9	1.0	2.3	2.3	2.7
REC	2.1	2.1	1.8	3.7	4.9	0.1	4.9	0.1	0.1	2.3	2.3	0.1	0.1	0.1	4.5	0.2	1.0	2.3	2.3	2.7
Ref. No.	IC3803 (SCM-24)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	0.1	2.3	0.1	0.9	2.8	0.1	3.4	0.1	2.9	0.1	0.1	2.3	2.3	2.8	2.2	0.9	2.8	3.4	0.1	3.0
REC	0.1	2.3	0.1	1.1	2.9	0.1	3.2	0.1	2.9	0.1	0.1	2.3	2.2	2.8	2.2	1.1	2.9	3.3	0.1	2.9
Ref. No.	IC3803 (SCM-24)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	4.9	0.1	0.1	0.3	5.0	0.1	0.1	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	0.1	2.0	2.5	2.3
REC	4.9	0.1	0.1	0.4	5.0	0.1	0.1	2.3	2.2	2.2	2.2	2.2	2.3	2.3	2.2	2.3	0.1	2.1	2.5	2.4
Ref. No.	IC3803 (SCM-24)																			
Mode	61	62	63	64																
STOP	2.3	2.5	2.4	2.3																
REC	2.4	2.6	2.4	2.3																
Ref. No.	IC3804 (SCM-24)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	2.0	2.3	2.3	2.3	2.3	2.3	5.0	0.1	0.1	2.3	2.3	2.3	2.3	4.9	0.1	4.9	3.7	1.7	2.0	2.1
REC	2.0	2.3	2.2	2.2	2.2	2.2	4.9	0.1	0.1	2.2	2.2	2.2	2.2	4.9	0.1	4.9	3.7	1.7	2.1	2.1
Ref. No.	IC3804 (SCM-24)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	2.3	2.4	2.6	2.3	2.3	4.8	4.9	0.1	4.5	4.2	1.9	0.1	3.4	2.8	0.9	2.3	2.7	2.7	4.9	0.1
REC	2.2	2.4	2.6	2.3	2.3	4.8	4.9	0.1	4.5	0.2	2.0	0.1	3.3	2.9	1.1	2.3	2.8	2.2	4.9	0.1
Ref. No.	IC3804 (SCM-24)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	2.3	2.3	2.3	2.3	0.1	2.3	2.3	2.2	2.1	2.1	0.1	2.3	0.1	2.3	0.1	1.6	2.5	2.1	0.7	1.4
REC	2.3	2.2	2.3	2.3	0.1	2.3	2.2	2.2	2.1	2.1	0.1	2.3	0.1	2.4	0.1	1.6	2.4	2.2	0.8	1.4
Ref. No.	IC3804 (SCM-24)																			
Mode	61	62	63	64																
STOP	2.0	1.5	1.5	0.1																
REC	2.1	1.5	1.5	0.1																
Ref. No.	IC3805 (SCM-24)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0.1	2.0	1.9	1.9	1.9	0.1	1.9	0.1	5.0	0.1	1.8	0.1	2.3	2.3	0.1	0.1	0.1	3.0	1.9	1.8
REC	0.1	1.6	1.6	1.5	1.5	0.1	1.5	0.1	4.9	0.1	1.4	0.1	2.3	2.3	0.1	0.1	0.1	3.4	1.5	1.5
Ref. No.	IC3805 (SCM-24)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	0.1	1.8	1.8	1.8	0.1	1.8	0.1	1.8	1.9	1.6	1.3	1.3	0.1	1.3	1.3	1.3	1.3	2.7	2.4	5.0
REC	0.1	1.5	1.5	1.5	0.1	1.5	0.1	1.5	1.6	1.3	1.3	1.3	0.1	1.3	1.3	1.3	1.2	2.7	2.4	4.9

Ref. No.	IC3805 (SCM-24)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	0.1	2.3	2.2	2.2	2.3	2.3	2.4	0.1	4.9	4.9	5.0	0.1	0.1	0.1	0.1	4.7	2.5	0.1	0.2	5.0
REC	0.1	2.3	2.3	2.3	2.3	2.3	2.3	0.1	2.8	4.9	4.9	0.1	0.1	0.1	0.1	4.7	2.5	0.1	0.2	4.9
Ref. No.	IC3805 (SCM-24)																			
Mode	61	62	63	64																
STOP	0.3	2.6	0.1	2.0																
REC	0.4	2.7	0.1	2.0																
Ref. No.	IC3806 (SCM-22)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	1.5	1.3	1.8	1.4	0.6	2.1	2.5	1.6	2.3	0	0	4.8	4.8	3.8	3.8	2.9	4.8	4.8	0
REC	0	1.5	1.7	2.1	1.4	0.8	2.1	2.4	1.6	2.3	0	0	4.8	4.8	3.8	3.8	2.9	4.8	4.8	0
Ref. No.	IC3807 (SCM-22)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	1.6	1.6	0.9	0.9	2.6	2.6	2.7	0.6	2.3	0	0	4.8	4.8	3.8	3.7	2.9	4.8	4.8	0
REC	0	1.4	2.2	0.9	0.9	2.7	2.6	2.7	0.7	2.3	0	0	4.8	4.8	3.7	3.7	2.9	4.8	4.8	0
Ref. No.	IC3808 (SCM-22)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	2.0	2.0	2.0	2.7	2.3	0	4.8	2.3	2.3	2.3	2.3	2.3	2.3	2.2	2.1	2.3	4.8	4.8	2.2	2.2
REC	2.0	2.0	1.9	2.6	2.3	0	4.8	2.3	2.3	2.3	2.3	2.3	2.3	2.2	2.1	2.3	4.8	4.8	2.2	2.2
Ref. No.	IC3808 (SCM-22)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	2.2	1.9	4.2	0	4.3	0	3.4	0	0	2.3	2.3	2.7	2.2	0.9	2.8	3.4	2.1	2.3	0	4.8
REC	2.2	1.9	4.2	0	4.3	0	3.4	0	0	2.3	2.3	2.7	2.2	1.1	2.9	3.3	2.1	2.3	0	4.8
Ref. No.	IC3808 (SCM-22)																			
Mode	41	42	43	44																
STOP	1.8	1.9	2.0	2.0																
REC	1.7	1.8	1.9	1.9																
Ref. No.	IC3810 (SCM-22)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	2.4	3.4	2.4	3.5	1.9	1.6	0	2.3	1.3	1.9	3.5	3.5	3.5	4.8						
REC	2.4	3.4	2.4	0.3	1.9	1.6	0	2.3	1.3	1.9	3.5	3.5	3.5	4.8						
Ref. No.	IC3811 (SCM-22)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	2.4	2.4	2.4	2.4	0.2	4.6	0	0.2	4.6	2.4	2.4	2.4	2.4	4.8						
REC	2.4	2.4	2.4	2.4	0.3	4.6	0	0.2	4.6	2.4	2.4	2.4	2.4	4.8						
Ref. No.	IC3812 (SCM-22)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18		
STOP	4.7	3.5	4.2	1.8	3.0	0	0	2.1	4.7	3.2	0	3.0	0	1.6	2.2	2.3	3.9	3.9		
REC	4.8	3.5	4.3	1.9	3.1	0	0	2.1	4.8	3.2	0	3.1	0	1.6	2.2	2.4	4.0	4.0		
Ref. No.	IC3813 (SCM-23)										IC3814 (SCM-23)									
Mode	1	2	3	4	5	6	7	8			G	V	O							
STOP	4.9	0.1	4.9	0.1	0.1	4.9	0.1	5.0	0.1	5.0	4.9									
REC	4.9	0.1	4.9	0.1	0.1	4.9	0.1	5.0	0.1	5.0	4.9									
Ref. No.	IC3815 (SCM-24)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	1.3	1.2	1.3	1.3	1.3	1.3	1.7	1.9	2.5	5.0	5.0	4.7	2.4	2.5	2.4	2.6	0.1	2.2	0.8	2.9
REC	1.2	1.1	1.2	1.2	1.2	1.2	1.5	1.7	2.5	4.9	5.0	4.6	2.3	2.3	2.2	2.8	0.1	2.3	1.2	2.9
Ref. No.	IC3815 (SCM-24)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	3.4	2.9	3.0	3.4	2.9	0.8	2.1	2.6	2.3	2.3	0.1	0.1	4.9	0.1	4.9	1.9	1.7	1.3	5.0	1.3
REC	3.2	2.9	2.9	3.3	2.9	1.2	2.3	2.8	2.2	2.3	0.1	0.1	4.9	0.1	4.9	2.0	1.6	1.3	5.0	1.2
Ref. No.	IC3815 (SCM-24)																			
Mode	41	42	43	44																
STOP	1.3	1.3	1.3	1.3																
REC	1.3	1.2	1.1	1.2																
Ref. No.	IC3816 (SCM-23)																			
Mode	1	2	3	4	5	6	7	8												
STOP	4.5	4.7	2.9	0	2.0	0.1	0.4	4.8												
REC	4.5	4.7	2.9	0	2.0	0.1	0.4	4.8												

Ref. No.	IC3817 (SCM-23)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	4.5	4.9	4.9	4.2	0.4	4.6	0.6	0.1	0.2	4.9	4.9	4.5	0.2	4.9	0.9	5.0				
REC	4.5	5.0	5.0	4.2	0.4	4.6	0.6	0.1	0.2	4.9	4.9	4.5	0.2	4.9	0.9	5.0				
Ref. No.	IC3818 (SCM-23)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	4.5	5.0	0.5	0.1	4.9	4.9	0.1	4.9	0.2	4.5	4.6	5.0	0.5	5.0						
REC	4.5	5.0	0.5	0.1	5.0	5.0	0.1	4.9	0.1	4.5	4.5	5.0	0.5	5.0						
Ref. No.	IC3901 (SCM-26)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	5.0	4.6	4.5	0	5.0	0	0	5.1	0	0	0	0	5.0	5.0	0	0	5.0	0	0	0
REC	4.9	4.6	4.5	0	4.9	0	0	5.1	0	0	0	0	5.0	5.0	0	0	4.9	0	0	0
Ref. No.	IC3901 (SCM-26)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	0	0	0	0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	0	0	0	0	0	0	0	0
REC	0	0	0	0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	0	0	0	0	0	0	0	0
Ref. No.	IC3901 (SCM-26)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	0	0	0	0	0	0	0	0	0	0	5.0	0	4.9	0	1.8	2.3	5.0	0	4.6	0.9
REC	0	0	0	0	0	0	0	0	0	0	4.9	0	4.9	0	1.8	2.3	5.0	0	4.6	0.9
Ref. No.	IC3901 (SCM-24)				IC3902 (SCM-26)				IC3903 (SCM-26)											
Mode	61	62	63	64	G	V	O		1	2	3	4	5	6	7	8				
STOP	0	4.9	4.9	0.1	0.1	5.0	5.0		5.0	5.0	5.0	0.1	0.1	0.1	0.1	5.0				
REC	0	4.9	4.9	0.1	0.1	5.0	5.0		5.0	5.0	5.0	0.1	0.1	0.1	0.1	5.0				
Ref. No.	IC3921 (SCM-25)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	5.0	0.1	5.0	5.0	5.0	5.0	5.0	0.1	5.0	5.0	5.0	5.0	5.0	0.1	0.1	5.0				
REC	5.0	0.1	5.1	5.1	5.1	5.1	5.1	0.1	5.1	5.1	5.0	5.1	5.1	0.1	0.1	5.1				
Ref. No.	IC3922 (SCM-25)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	5.0	2.1	5.0	5.0	5.0	5.0	5.0	0.1	2.3	5.0	2.4	2.4	2.4	2.4	2.4	5.0				
REC	5.0	2.1	5.0	5.0	5.0	5.0	5.0	0.1	2.5	5.0	2.4	2.4	2.4	2.4	2.4	0.8				
Ref. No.	IC3923 (SCM-25)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	2.2	2.3	2.3	2.2	2.2	2.3	0.1	0.1	0.1	0.1	2.4	2.4	2.4	5.0						
REC	2.3	2.3	2.4	2.3	2.3	2.4	0.1	0.1	0.1	0.1	2.4	2.4	2.4	5.0						
Ref. No.	IC3924 (SCM-25)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0.1	2.5	2.4	2.3	2.3	2.7	2.1	0.9	2.8	3.4	2.0	0.1	4.1	0.1	4.1	4.1	2.0	2.5	2.7	0.6
REC	0.1	2.5	2.4	2.3	2.2	2.7	2.2	1.0	3.0	3.3	2.1	0.1	4.1	0.1	4.1	4.1	2.0	2.4	2.8	0.8
Ref. No.	IC3924 (SCM-25)								IC3925 (SCM-25)											
Mode	21	22	23	24	25	26	27	28	1	2	3	4	5							
STOP	1.9	2.4	1.9	1.9	0	4.1	0.1	5.0	0	2.3	0.1	2.5	5.0							
REC	1.9	2.4	1.9	1.9	0	4.1	0.1	5.0	0	2.3	0.1	2.5	5.0							
Ref. No.	IC3951 (SCM-25)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	1.9	1.9	2.0	3.0	2.4	0	4.8	0	0	0	0	0	0	0	0	0	4.8	4.8	2.2	2.1
REC	1.7	1.7	1.9	3.1	2.4	0	4.8	0	0	0	0	0	0	0	0	0	4.8	4.8	2.2	2.1
Ref. No.	IC3951 (SCM-25)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	2.2	1.9	2.2	0	4.3	0	3.8	0	0	1.9	1.9	2.4	1.9	0.7	2.6	2.5	2.0	2.4	0	4.8
REC	2.2	1.9	2.2	0	4.3	0	3.8	0	0	1.9	1.9	2.5	2.1	0.9	2.6	2.4	2.0	2.4	0	4.8
Ref. No.	IC3951 (SCM-25)																			
Mode	41	42	43	44																
STOP	1.9	1.9	1.9	1.9																
REC	1.7	1.7	1.7	1.7																
Ref. No.	Q3691 (SCM-21)			Q3693 (SCM-21)			Q3701 (SCM-27)			Q3702 (SCM-27)			Q3703 (SCM-27)			Q3771 (SCM-29)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0.7	0	0	2.2	0	1.6	2.5	4.9	2.2	0	11.5	0	-5.0	4.8	-4.2	-0.8	4.8	-0.2		
REC	0.7	0	0	2.2	0	1.6	3.0	4.9	2.2	0	11.5	0.5	-5.0	4.8	-4.2	-0.8	4.8	-0.2		

Ref. No.	Q3772 (SCM-29)			Q3773 (SCM-29)			Q3774 (SCM-29)			Q3783 (SCM-29)			Q3784 (SCM-29)			Q3801 (SCM-22)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	-0.8	4.8	-0.2	-1.1	4.8	-0.5	-0.2	-4.9	-0.8	0	0	0.6	-0.6	4.8	0	1.3	4.8	1.9		
REC	-0.8	4.8	-0.2	-1.1	4.8	-0.5	-0.2	-4.9	-0.8	0	0	0.6	-0.6	4.8	0	1.3	4.9	1.9		
Ref. No.	Q3802 (SCM-22)			Q3803 (SCM-22)			Q3804 (SCM-22)			Q3805 (SCM-22)			Q3806 (SCM-22)			Q3807 (SCM-22)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0.9	3.3	1.6	3.1	4.8	3.2	0.7	3.1	1.4	3.4	4.8	3.1	3.2	4.8	3.8	2.8	4.8	3.4		
REC	0.9	3.3	1.6	3.2	4.8	3.3	0.7	3.1	1.4	3.4	4.8	3.1	3.2	4.8	3.8	2.8	4.8	3.4		
Ref. No.	Q3808 (SCM-22)			Q3809 (SCM-22)			Q3951 (SCM-25)			Q3952 (SCM-25)										
Mode	E	C	B	E	C	B	E	C	B	E	C	B								
STOP	3.7	4.8	4.3	3.5	4.8	4.2	3.2	4.8	3.8	3.7	4.8	4.3								
REC	3.7	4.8	4.3	3.5	4.8	4.2	3.2	4.8	3.8	3.7	4.8	4.3								
Ref. No.	QR3704 (SCM-27)			QR3705 (SCM-27)			QR3772 (SCM-29)			QR3810 (SCM-23)										
Mode	E	C	B	E	C	B	E	C	B	E	C	B								
STOP	0	0	4.5	0.1	0.1	4.1	0.1	5.0	0.1	0.1	0.1	4.9								
REC	0	0	4.5	0.1	0.1	4.1	0.1	5.0	0.1	0.1	0.1	4.9								

SERVO & SYSTEM CONTROL C.B.A.

Ref. No.	IC1501 (SCM-16)								IC1502 (SCM-16)			IC1503 (SCM-16)			IC1505 (SCM-16)			IC1506 (SCM-16)		
Mode	1	2	3	4	5	6	7	8	G	I	O	G	I	O	K	A	R	K	A	R
STOP	4.7	0.1	2.7	0	2.7	5.3	0.1	5.3	0	-14.7	-12.2	0	-7.0	-5.0	7.7	0	2.5	5.9	0	2.5
REC	4.7	0.1	2.7	0	2.7	5.3	0.1	5.3	0	-14.8	-12.2	0	-7.0	-5.0	7.7	0	2.5	5.9	0	2.5
FF	4.7	0.1	2.7	0	2.7	5.3	0.1	5.3	0	-14.7	-12.2	0	-6.9	-5.0	7.7	0	2.5	5.9	0	2.5
Ref. No.	IC2001 (SCM-9)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	5.0	4.6	2.5	2.5	5.1	0	0	0	0	2.5	2.6	0	5.1	0	4.1	5.1	0	5.1	2.6
REC	3.1	5.0	4.6	2.5	2.5	5.1	0	0	0	0	2.6	0	0	5.1	0	4.1	5.1	0	5.1	2.6
FF	0	5.0	4.6	2.5	2.5	5.2	0	5.2	0	0	2.6	2.6	0	5.2	0	4.1	5.2	0	5.2	2.6
Ref. No.	IC2001 (SCM-9)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	0	0	0	0	5.1	0	2.6	0	0	0	0	5.1	0.1	2.4	0	0	0	0	5.1	0
REC	0	0	0	0	5.1	0	2.6	0	0	0	0	5.1	0.5	2.4	0	0	0	0	5.1	0
FF	0	0	0	0	5.2	0	2.6	0	0	0	0	5.2	0.5	2.4	0	0	0	0	5.2	0
Ref. No.	IC2001 (SCM-9)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	0	0	5.1	0	0	0	0	2.5	2.5	0	0.2	0	0	0	0	0	0	1.9	5.1	0
REC	0	0	5.1	0	0	5.1	0	2.5	2.5	0	3.1	0	0	0	0	0	0	1.9	5.1	0
FF	0	0	5.2	0	0	5.2	0	2.5	2.5	0	0	0	0	0	0	0	0	1.9	5.2	0
Ref. No.	IC2001 (SCM-9)				IC2002 (SCM-9)			IC2003 (SCM-9)												
Mode	61	62	63	64	V	G	O	1	2	3	4	5	6	7	8					
STOP	1.1	3.1	5.1	0	5.1	0	5.1	2.3	0.5	2.5	0	0	0	0	5.0					
REC	1.1	3.1	5.1	0	5.1	0	5.1	2.3	0.5	2.5	0	0	0	0	0					
FF	1.1	3.1	5.2	0	5.2	0	5.2	2.3	0.5	2.6	0	0	0	0	5.0					
Ref. No.	IC2004 (SCM-9)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0	0	0	0	0	0	0	0	0	2.6	2.6	2.5	2.6	2.6	5.1				
REC	0	0	0	0	0	0	0	0	0	0	2.6	2.6	2.6	2.6	2.6	5.1				
FF	0	0	0	0	0	0	0	0	5.2	0	2.6	2.6	2.6	2.6	2.6	5.2				
Ref. No.	IC2005 (SCM-9)										IC2006 (SCM-9)									
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	1	2	3	4	5	
STOP	2.6	2.6	2.1	0	2.6	0	0	0	0	0	0	0	5.1	5.1	2.6	2.6	0	0	5.1	
REC	2.6	2.6	2.1	0	2.6	0	0	0	0	0	0	0	5.1	5.1	2.6	2.6	0	0	5.1	
FF	2.6	2.6	2.1	0	2.6	0	0	0	0	0	0	0	5.2	5.2	2.6	2.6	0	0	5.2	
Ref. No.	IC2007 (SCM-9)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	0	0	0	5.1	5.1	0	5.1	5.1	0	0	0	0	5.1	5.1	0	5.1	0	0	5.1
REC	0	0	0	0	4.5	5.1	0	5.1	5.1	0	0	0	0	5.1	5.1	0	5.1	0	0	5.1
FF	0	0	0	0	4.5	5.2	0	5.2	5.2	0	0	0	0	5.2	5.2	0	5.2	0	0	5.2
Ref. No.	IC2007 (SCM-9)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	0	0	0	2.6	0	0	5.1	0	5.1	0	0	0	0	5.1	0	0	0	0	0	5.1
REC	0	0	0	2.6	0	0	5.1	0	5.1	0	0	0	0	5.1	0	0	0	0	0	5.1
FF	0	0	0	2.6	0	0	5.2	0	5.2	0	0	0	0	5.2	0	0	0	0	0	5.2
Ref. No.	IC2007 (SCM-9)																			
Mode	41	42	43	44																
STOP	5.1	5.1	0	2.5																
REC	5.1	5.1	0	2.5																
FF	5.2	5.2	0	2.5																
Ref. No.	IC2008 (SCM-9)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	0	0	0	0.2	3.5	0	4.7	5.1	0	0	0	0	5.1	5.1	0	5.1	0	0	5.1
REC	0	0	0	0	0	3.5	0	0	5.1	0	0	0	0	5.1	5.1	0	5.1	0	0	5.1
FF	0	0	0	0	0.3	3.5	0	4.7	5.1	0	0	0	0	5.2	5.2	0	5.2	0	0	5.2
Ref. No.	IC2008 (SCM-9)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	0	0	2.6	0	0	0	0	0	5.1	0	0	0	0	5.1	0	0	0	0	0	5.1
REC	0	0	2.6	2.6	0	0	0	0	5.1	0	0	0	0	5.1	0	0	0	0	0	5.1
FF	0	0	2.6	2.6	0	0	0	0	5.2	0	0	0	0	5.2	0	0	0	0	0	5.2

Ref. No.	IC2008 (SCM-9)				IC2009 (SCM-9)															
Mode	41	42	43	44	1	2	3	4	5	6	7	8								
STOP	5.1	5.1	0	2.5	2.6	0	0	0	5.1	2.6	2.6	5.1								
REC	5.1	5.1	0	2.5	2.6	0	0	0	5.1	2.6	2.6	5.1								
FF	5.2	5.2	0	2.5	2.6	0	0	0	5.2	2.6	2.6	5.2								
Ref. No.	IC2010 (SCM-9)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	0.5	0.1	5.0	0.5	2.5	0.2	2.5	0	0	0.1	0.3	0	5.1	0						
REC	0.5	0.2	5.0	0.5	2.5	0.2	2.5	0	0	0.1	0.4	0	5.1	0						
FF	0.5	0.2	5.0	0.5	2.5	0.2	2.5	0	0	0.1	0.5	0	5.2	0						
Ref. No.	IC2012 (SCM-9)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	2.5	2.6	2.6	2.6	2.6	2.6	0	2.4	2.3	2.5	2.4	0.8	3.7	5.1						
REC	2.5	2.6	2.6	2.6	2.6	2.6	0	2.4	2.3	2.5	2.4	0.8	3.6	5.1						
FF	2.6	2.6	2.6	2.6	2.6	2.6	0	2.4	2.3	2.5	2.4	0.8	3.6	5.2						
Ref. No.	IC2013 (SCM-9)								IC2014 (SCM-9)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5							
STOP	0	0	0	0	2.4	2.4	2.4	11.7	2.6	2.6	0	2.5	5.0							
REC	0	0	0	0	2.4	2.4	2.4	11.7	2.6	2.6	0	2.5	5.0							
FF	0	0	0	0	2.4	2.4	2.4	11.7	2.6	2.6	0	2.5	5.0							
Ref. No.	IC2201 (SCM-13)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	0	5.1	5.1	0	0	0	0	3.1	2.4	2.6	2.1	2.4	5.1	5.1	5.1	5.1	4.9	3.1	4.2
REC	0	0	5.1	5.1	0	0	0	0	3.1	2.4	2.6	2.1	2.4	5.1	5.1	5.1	5.1	4.9	2.8	3.9
FF	0	0	5.2	5.2	0	0	0	0	3.1	2.5	2.7	2.1	2.4	5.2	5.2	5.2	5.2	5.0	3.2	4.3
Ref. No.	IC2201 (SCM-13)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	0	0	0	5.1	5.1	5.1	0	0	5.1	0	0	0	0	0	0	0	0	0	0	0
REC	0	0	0	5.1	5.1	5.1	0	0	0	0	0	0	0	0	0	0	0	0	0	0
FF	0	0	0	5.2	5.2	5.2	0	5.2	5.2	0	0	0	0	0	0	0	0	0	0	0
Ref. No.	IC2201 (SCM-13)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	0	0	5.1	3.9	4.7	4.3	3.5	4.3	3.5	3.6	3.6	3.1	3.6	3.1	4.9	4.7	4.1	3.4	3.9	5.1
REC	0	0	5.1	2.7	2.7	3.6	3.6	3.6	3.7	3.7	3.5	4.5	3.5	2.6	3.7	3.5	3.7	3.8	4.2	5.1
FF	0	0	5.2	2.6	3.3	3.9	3.3	3.3	4.0	3.3	3.5	3.4	3.4	3.3	4.1	2.6	2.8	3.9	2.8	5.2
Ref. No.	IC2201 (SCM-13)																			
Mode	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80
STOP	5.1	5.1	0	0	0	0	0	5.1	5.1	5.1	0	0.9	0.9	0.8	0.9	4.1	4.6	3.8	4.7	4.7
REC	5.1	5.1	0	0	0	0	0	5.1	5.1	5.1	0	2.4	2.8	3.2	2.1	1.9	1.5	3.9	4.6	4.6
FF	5.2	5.2	0	0	0	0	0	5.2	5.2	5.2	0	0.3	0	1.0	0.8	4.5	4.7	3.9	4.7	4.7
Ref. No.	IC2201 (SCM-13)																			
Mode	81	82	83	84																
STOP	0	0	0.5	5.1																
REC	0	0	0.5	5.1																
FF	0	0	0.5	5.2																
Ref. No.	IC2202 (SCM-12)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	4.0	3.9	0	5.0	0	0	4.0	0	2.6	5.1	5.1	5.1	0	0	5.1	4.5	5.0	0	0	4.6
REC	0	2.7	0	2.6	2.6	2.5	2.5	0	2.5	5.1	0	5.1	0	0	0	4.5	5.0	0	0	4.6
FF	3.3	2.6	0	5.0	0	0	4.1	0.4	2.6	0	0	5.2	0	0	0	4.6	5.0	0	0	4.6
Ref. No.	IC2202 (SCM-12)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	4.5	4.5	0	5.1	5.1	0.2	0	0	0	0	0	0	5.1	0	0	5.1	5.1	5.1	5.1	5.1
REC	2.3	2.3	0	5.1	0	0.2	0	0	0	0	0	0	5.1	0	5.1	5.1	0	0	5.1	2.2
FF	0.1	4.5	0	5.2	5.2	0.1	0	0	0	0	0	0	5.2	5.2	0	0	0	0	0	0
Ref. No.	IC2202 (SCM-12)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	5.1	2.3	5.1	5.1	5.1	5.1	0	5.1	0	0	0	0	5.1	1.9	1.9	2.2	5.0	3.2	0.5	4.1
REC	2.9	2.3	5.1	2.7	2.7	2.6	2.7	2.6	2.7	2.6	2.7	0	5.1	1.9	1.9	2.2	5.0	2.8	0.6	1.9
FF	0	0	5.2	0	0	0	0	0	0	0	0	0	5.2	1.9	1.9	2.2	5.0	3.2	0.5	4.5

Ref. No.	IC2202 (SCM-12)																			
Mode	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80
STOP	0.9	0.8	0.9	0.9	3.9	4.2	4.1	3.8	4.9	3.1	3.6	3.1	5.1	0	3.5	3.5	4.3	4.3	3.5	4.3
REC	2.1	3.2	2.8	2.4	4.2	3.8	3.7	3.5	3.6	2.6	0	4.4	5.1	0	3.6	3.7	3.6	3.6	3.7	3.7
FF	0.8	1.0	0.5	0.3	2.7	3.9	4.1	2.8	4.1	3.3	3.4	3.4	5.2	0	3.3	3.3	4.0	3.3	3.3	3.3
Ref. No.	IC2203 (SCM-12)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	0	5.1	5.1	5.1	5.1	0	5.1	5.1	0	5.1	5.1	0	0	5.1	0	1.6	1.6	0	0
REC	0	5.1	5.1	0	0	5.1	3.8	2.2	2.6	2.7	2.7	2.7	2.7	2.7	2.7	2.7	0.6	0.6	0	0
FF	5.2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Ref. No.	IC2203 (SCM-12)				IC2206 (SCM-12)															
Mode	21	22	23	24	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
STOP	0	0	5.1	-5.0	5.1	5.1	4.6	0	0	5.0	5.0	0	0	0	0	0	0	4.6	5.1	0
REC	0	0	5.1	-5.0	5.1	2.5	2.3	0	0	5.0	5.0	0	0	0	0	0	0	2.3	2.6	0
FF	0	0	0	-5.0	5.2	0	0.1	2.8	2.4	5.1	5.1	0	0	0	0	0	0	0.1	0	0
Ref. No.	IC2207 (SCM-12)								IC2302 (SCM-10)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	1.6	1.6	1.6	-5.0	0.3	0.3	4.0	5.1	0.1	0	0	-5.0	0	0	-0.1	5.0				
REC	2.1	1.6	1.6	-5.0	0.3	0.3	4.0	5.1	0	0	0	-5.0	0	0	-0.1	5.0				
FF	2.4	1.6	1.6	-5.0	0.3	0.3	4.0	5.2	0.6	0	0	-5.0	0	0	-0.1	5.0				
Ref. No.	IC2303 (SCM-10)								IC2304 (SCM-10)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	-0.2	0	0	-5.0	0.3	0.2	3.9	5.0	4.9	0.1	0.9	-5.0	0.9	-0.2	4.9	5.0				
REC	0	0	0	-5.0	0.3	0.3	3.9	5.0	4.9	0	0.9	-5.0	0.9	0	4.9	5.0				
FF	-1.5	-0.1	0	-5.0	0.3	0.3	3.9	5.0	3.6	0	0.7	-5.0	0.7	-1.4	1.4	5.0				
Ref. No.	IC2305 (SCM-10)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0	0.1	0.1	0.1	0	0	0	0	0	0	0	0	0	0	5.0				
REC	0	0	0.1	0.1	0.1	0	0	0	0	0	4.6	0	3.1	3.0	0	5.0				
FF	1.9	2.7	0.1	0.1	0.1	0	0	0	0	0	0	0.4	0	2.0	0.4	5.0				
Ref. No.	IC2310 (SCM-10)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	1.3	0.2	0	0.9	4.4	0	0	0	0	0	5.0	3.4	2.6	1.7	5.1				
REC	0	1.3	0.2	0	0.9	4.4	0	0	0	0	2.5	0.3	0.4	2.6	3.8	5.1				
FF	0	1.3	0.2	0	0.9	4.4	0	0	0	0	0	5.0	3.4	2.6	1.7	5.0				
Ref. No.	IC2311 (SCM-10)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0	0	0	0	0	-5.0	0	0	0	0	0	5.9	0	0	11.7				
REC	0	0	0	0	0	0	-5.0	0	11.7	0	11.7	0	0	0	0	11.7				
FF	0	0	0	0	0	0	-5.0	0	0	0	0	0	5.9	0	0	11.7				
Ref. No.	IC2312 (SCM-10)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	0	11.6	11.6	11.6	11.7	0	0	0	0	0	0	0	11.7	11.7						
REC	11.7	0	4.6	0	11.7	0	0	0	0	0	0	0	11.7	11.7						
FF	0	11.6	11.6	11.6	11.7	0	0	0	0	0	0	0	11.7	11.7						
Ref. No.	IC2401 (SCM-11)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	0	5.1	0	5.1	5.1	0	0	0	0	0	0	0	5.1	5.1						
REC	5.1	0	3.1	0.1	5.1	0	0	0	0	0	0	5.1	0	5.1						
FF	0	5.1	0	5.2	5.2	0	0	2.7	0	1.9	0	2.0	3.1	5.1						
Ref. No.	IC2402 (SCM-11)								IC2403 (SCM-11)					IC2404 (SCM-11)						
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	1	2	3	4	5		
STOP	0	0	0	0	5.1	0	0	5.1	5.1	0	0	0	5.1	5.1	0	0	0	5.1		
REC	3.1	0	0	0	0	0	3.1	5.1	0.1	2.1	0	3.1	5.1	0.4	3.1	0	2.1	5.1		
FF	3.1	0	0	0	5.2	3.2	0	5.2	5.2	0	0	0	5.2	0	5.2	0	0	5.2		
Ref. No.	IC2405 (SCM-11)																			
Mode	1	2	3	4	5															
STOP	5.1	5.1	0	5.1	5.1															
REC	3.1	1.8	0	0.4	5.1															
FF	3.2	0	0	0	5.2															

Ref. No.	IC2406 (SCM-11)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	5.1	5.1	0	0	5.1	0	5.1	5.1	5.1	3.6	0	5.1	0	0	0	5.1	5.1	5.1	0	5.1
REC	5.1	3.1	0	0	5.1	0	5.1	5.1	5.1	3.3	0	1.8	3.1	0	0	0	5.1	3.1	0	5.1
FF	5.2	3.1	0	0	5.1	0	5.2	5.1	5.1	5.1	0	5.2	5.2	0	0	5.2	5.2	3.2	0	5.2
Ref. No.	IC2406 (SCM-11)																			
Mode	21	22	23	24	25	26	27	28	29	30										
STOP	4.8	0	0	0	0	0	2.5	2.5	0	5.1										
REC	4.8	0	0	0	0	0	2.5	2.5	0	5.1										
FF	4.8	0	0	0	0	0	2.5	2.5	0	5.2										
Ref. No.	IC2501 (SCM-8)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	3.2	3.2	3.1	11.7	2.4	2.4	2.0	4.6	4.6	4.6	0	2.4	2.4	2.4						
REC	2.5	2.5	2.5	11.7	2.4	2.4	2.2	4.6	4.6	4.6	0	2.4	2.4	2.4						
FF	2.4	2.4	2.3	11.7	2.4	2.4	2.3	0.6	0.6	0.6	0	0.2	0.2	0.2						
Ref. No.	IC2502 (SCM-8)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	2.4	2.4	2.4	11.7	2.4	2.4	2.4	2.4	2.4	2.4	0	1.6	1.7	1.7						
REC	2.4	2.4	2.3	11.7	2.4	2.4	2.4	2.4	2.4	2.4	0	1.0	1.0	1.0						
FF	3.8	3.8	3.8	11.7	2.4	2.4	1.5	2.8	2.7	2.7	0	1.6	1.6	1.5						
Ref. No.	IC2503 (SCM-8)																			
Mode	1	2	3	4	5	6	7	8												
STOP	11.6	2.2	2.4	0	0.5	0.5	0	11.7												
REC	11.6	2.2	2.4	0	0.5	0.5	0	11.7												
FF	11.6	2.3	2.4	0	0.5	0.5	0	11.7												
Ref. No.	IC2505 (SCM-8)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	2.4	2.4	2.0	2.0	2.4	0	0	0	11.6	0	11.6	2.4	2.4	2.4	2.4	11.7				
REC	2.4	2.4	2.2	2.2	2.4	0	0	0	11.6	0	11.6	2.4	2.4	2.4	2.4	11.7				
FF	2.4	2.4	2.3	2.3	2.4	0	0	0	11.6	0	0	2.4	2.4	2.4	2.4	11.7				
Ref. No.	IC2506 (SCM-8)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	2.3	2.1	2.1	2.3	2.3	0	0	0	11.6	0	2.6	2.6	2.4	2.5	2.4	11.7				
REC	2.3	2.2	2.2	2.3	2.3	0	0	0	11.6	0	2.5	2.5	2.4	2.5	2.4	11.7				
FF	2.3	2.3	2.3	2.3	2.3	0	0	0	0	0	2.3	2.4	2.4	2.3	2.3	11.7				
Ref. No.	IC2507 (SCM-8)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	1.4	0.1	0.3	0.3	0.3	0	0	0	0	0	0	0.2	0.2	0.2	0.1	11.7				
REC	0.8	0.1	0.3	0.3	0.3	0	0	0	0	0	0	0.3	0.3	0.3	0.1	0				
FF	0.1	1.8	0.3	0.3	0.3	0	0	0	0	11.6	0	0.3	0.3	0.3	0	11.7				
Ref. No.	IC2701 (SCM-15)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	14.9	2.9	3.3	3.0	18.9	2.9	3.2	3.2	14.1	0	0.2	0	1.8	2.7	0.5	0.2	0.5	0.4	0	0
REC	14.9	2.9	3.3	3.0	18.1	2.9	3.2	3.2	14.5	0.4	0.4	0	2.1	2.8	0.5	0.4	0.5	0.4	0	0
FF	14.9	2.8	2.9	2.9	17.8	2.7	2.7	2.7	10.1	0.3	0.4	0	1.8	2.7	0.5	0.3	0.5	0.3	0	0
Ref. No.	IC2701 (SCM-15)																			
Mode	21	22	23	24																
STOP	2.6	2.5	2.9	2.7																
REC	2.6	2.5	2.9	2.7																
FF	2.6	2.5	2.9	2.8																
Ref. No.	IC2703 (SCM-14)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18		
STOP	14.7	14.7	0.4	1.1	0	2.5	2.4	0.6	0.5	2.6	5.0	3.6	3.6	3.6	1.1	14.9	14.7	0.1		
REC	14.7	14.7	0.4	1.1	0	2.5	2.4	0.6	0.5	2.6	5.0	3.6	3.6	3.6	1.1	15.0	14.7	0.1		
FF	14.7	14.8	0.4	1.1	0	2.5	2.4	0.6	0.5	2.6	5.0	3.6	3.6	3.6	1.1	14.9	14.7	0.1		
Ref. No.	IC2704 (SCM-14)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	9.4	0	9.4	1.4	1.9	1.9	1.9	1.9	1.9	1.9	2.6	0	4.7	3.4	2.4	2.4	0.2	0	0	0
REC	0.9	0	0.9	1.4	1.9	1.9	1.9	1.9	1.9	1.9	0	0	4.7	3.4	2.4	2.1	2.8	0.6	0.4	0.1
FF	9.4	0	9.4	1.4	1.9	1.9	1.9	1.9	1.9	1.9	2.6	0	4.7	3.4	2.4	2.4	0.2	0	0	0

Ref. No.	IC2704 (SCM-4)				IC2705 (SCM-14)								IC2706 (SCM-14)							
Mode	21	22	23	24	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8
STOP	0	0	9.4	4.0	0	3.2	1.7	0	2.2	0.5	5.0	5.0	3.2	1.9	1.9	0	1.9	1.9	0.5	5.0
REC	0	0.7	1.0	4.0	2.6	2.0	2.0	0	2.0	2.0	2.6	5.0	2.0	1.9	1.9	0	1.9	1.9	2.0	5.0
FF	0	0	9.4	16.5	5.0	0.6	2.2	0	2.2	1.0	5.0	5.0	0.6	1.9	1.9	0	1.9	1.9	1.0	5.0
Ref. No.	IC2707 (SCM-14)								IC2708 (SCM-14)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	4.2	2.5	2.5	0	2.4	2.5	0	5.0	2.5	2.5	2.5	0	2.5	2.5	2.5	5.0				
REC	2.5	2.5	2.5	0	2.5	2.5	2.5	5.0	2.5	2.5	2.5	0	2.5	2.5	2.5	5.0				
FF	4.1	2.5	2.5	0	2.5	2.5	0	5.0	2.5	2.5	2.5	0	2.5	2.5	2.5	5.0				
Ref. No.	IC2709 (SCM-14)								IC2710 (SCM-14)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	0.1	2.5	2.4	0	2.4	2.5	4.5	5.0	2.5	2.5	2.5	0	2.5	2.5	2.5	5.0				
REC	2.3	2.5	2.5	0	2.5	2.5	2.3	5.0	2.5	2.5	2.5	0	2.5	2.5	2.5	5.0				
FF	0.1	2.5	2.4	0	2.4	2.5	4.5	5.0	2.5	2.5	2.5	0	2.5	2.5	2.5	5.0				
Ref. No.	IC2711 (SCM-14)								IC2715 (SCM-14)											
Mode	1	2	3	4	5	6	7	8	I	G	O									
STOP	2.5	2.5	2.5	0	2.5	2.5	2.5	5.0	18.4	0	12.0									
REC	2.5	2.5	2.5	0	2.5	2.5	2.5	5.0	18.4	0	12.0									
FF	2.5	2.5	2.5	0	2.5	2.5	2.5	5.0	18.3	0	12.0									
Ref. No.	IC60001 (SCM-6)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0	0.1	0	0	0	0	0	0	11.5	4.6	0.2	0.2	5.0	1.7	0				
REC	0	0	0.1	0	0	0	0	0	0	0	4.6	0.2	0.2	5.0	1.7	5.0				
FF	0	0	0.1	0	0	0	0	0	0	11.5	4.6	0.4	0.4	5.0	1.7	5.0				
Ref. No.	IC60002 (SCM-6)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0.8	4.8	0	0	0	0	0	0	0	0	0	0	4.9	0	0	4.9	0	4.7	4.9	0
REC	0.8	4.8	0	0	0	0	4.8	4.7	4.8	0	3.2	3.2	4.9	0	0	4.9	0	4.7	4.9	0
FF	0.9	0	0	0	0	0	0	0	0	0	0	0	4.9	0	0	4.9	0	4.8	4.9	0
Ref. No.	IC60002 (SCM-6)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	4.5	0	0	0.1	4.7	0.1	2.5	0	4.9	4.9	1.5	---	0	0	4.8	4.9	4.9	0	0	0
REC	4.5	0	0	0	2.8	2.3	2.6	2.5	4.9	4.9	1.5	---	0	0	4.8	4.9	4.9	0	0	0
FF	4.6	0	0	0.1	2.5	2.2	2.6	5.2	0	0	0	---	0	0	4.9	4.9	4.9	0	0	4.9
Ref. No.	IC60002 (SCM-6)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	4.8	4.8	4.8	4.8	0	4.8	0	5.0	4.6	0.2	0.3	4.7	4.5	4.9	4.8	0	0	0	0	0
REC	4.8	4.8	4.8	4.8	0	4.8	0	5.0	4.6	0.2	0.2	4.8	4.5	4.9	4.8	0	0	0	0	0
FF	4.9	0	4.9	4.9	4.9	4.9	4.9	5.0	4.7	0.2	0.2	4.8	4.5	4.9	0	4.9	0	0	0	0
Ref. No.	IC60002 (SCM-6)																			
Mode	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80
STOP	1.1	0.9	1.6	2.3	2.3	2.5	4.6	2.4	2.6	0.6	3.8	4.8	4.8	4.7	0.5	4.2	0	0.1	0	0
REC	1.1	0.9	1.0	2.3	2.3	2.5	4.6	2.4	2.6	0.6	3.8	4.9	4.9	4.8	0.5	4.3	0	0.1	0	0
FF	0.7	0.9	1.0	3.7	3.1	0	0.6	0.2	2.6	0.6	3.8	4.9	4.9	4.9	0.5	4.3	0	0.1	0	0
Ref. No.	IC60002 (SCM-6)				IC60003 (SCM-6)				IC60007 (SCM-6)											
Mode	81	82	83	84	V	G	O	1	2	3	4	5	6	7	8					
STOP	0	0	0	4.5	4.9	0	4.9	1.6	0.3	0.3	0	1.6	1.1	4.0	5.1					
REC	0	0	0	4.5	4.8	0	4.8	1.5	0.3	0.3	0	1.6	1.1	4.0	5.1					
FF	0	0	0	4.6	4.9	0	4.9	1.5	0.3	0	0	1.6	1.1	4.0	5.2					
Ref. No.	IC60101 (SCM-6)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	3.8	3.8	3.8	11.5	1.0	1.0	1.0	2.4	2.4	2.4	0	0.3	0.3	11.4						
REC	3.8	3.8	3.8	11.5	1.0	1.0	1.0	2.4	2.4	2.4	0	0.4	0.4	10.3						
FF	3.8	3.8	3.8	11.5	1.0	1.0	1.0	2.4	2.4	2.4	0	0.3	0.3	10.3						
Ref. No.	IC60501 (SCM-7)								IC60502 (SCM-7)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8	9	10		
STOP	4.9	2.9	3.2	0	3.2	2.9	4.9	5.1	0	0.2	0.2	0	0	0	12.9	10.3	12.9	0.2		
REC	4.8	2.9	3.2	0	3.2	2.9	4.8	5.1	0	0.2	0.2	0	0	0	12.9	10.3	12.9	0.2		
FF	4.9	2.9	3.2	0	3.2	2.9	4.9	5.2	0	0.2	0.2	0	0	0	12.9	10.3	12.9	0.2		

Ref. No.	IC60503 (SCM-7)			CYLSERVO IC2016 (SCM-7)																
Mode	V	G	O	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
STOP	5.0	0	5.0	0	5.1	0	0	0	0	5.1	0	5.1	0	5.1	2.6	2.6	5.1	0	5.1	
REC	5.0	0	5.0	0	5.1	0	0	0	0	5.1	0	5.1	0	5.1	2.6	2.6	5.1	0	5.1	
FF	0	5.2	5.2	0	-5.2	0	0	0	0	5.2	0	5.2	0	5.2	2.6	2.6	5.2	0	5.2	
Ref. No.	Q1501 (SCM-16)			Q1502 (SCM-16)			Q1503 (SCM-16)			Q1504 (SCM-16)			Q1505 (SCM-16)			Q2001 (SCM-9)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	5.1	5.4	5.7	0	5.3	-3.0	14.8	18.3	15.4	13.0	13.6	13.5	12.0	13.0	12.3	3.5	5.1	3.8		
REC	5.1	5.4	5.7	0	5.6	-3.0	15.0	18.5	15.5	13.0	13.4	13.5	12.0	12.9	12.3	3.5	5.1	3.8		
FF	5.1	5.4	5.7	0	4.7	-3.0	15.0	18.1	15.4	13.0	13.5	13.5	12.0	12.9	12.3	3.5	5.1	3.8		
Ref. No.	Q2302 (SCM-10)			Q2303 (SCM-10)			Q2304 (SCM-10)			Q2305 (SCM-10)			Q2703 (SCM-15)			Q2704 (SCM-15)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	11.7	0	0	0	0.6	0	3.5	0.5	1.2	5.0	1.7	4.0	2.8	4.0	18.2	18.4	18.0		
REC	0	5.6	0.3	0	0	0.3	0.7	0.8	1.3	3.2	5.0	3.7	4.0	2.8	4.0	18.5	11.0	18.3		
FF	0	11.7	0	0	0	0.6	0	3.5	0.5	1.2	5.0	1.7	16.4	2.8	15.8	18.3	4.2	17.7		
Ref. No.	Q2705 (SCM-15)			Q2706 (SCM-15)			Q2707 (SCM-15)			Q2709 (SCM-15)			Q2710 (SCM-15)			Q2711 (SCM-15)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	15.5	0.2	0	0.2	0.4	0	17.5	0.1	18.2	12.0	18.0	18.2	12.1	18.0	17.5	3.7	17.5		
REC	0	17.8	0.1	0	0.1	0.5	0	17.5	0.1	18.5	15.7	18.3	18.5	12.5	18.3	17.5	4.0	17.5		
FF	0	17.1	0	0	0	0.7	0	17.4	0.1	18.4	17.0	18.0	18.3	8.0	17.9	17.4	4.0	17.4		
Ref. No.	Q2713 (SCM-15)			Q2714 (SCM-15)			Q2715 (SCM-15)			Q2716 (SCM-15)			Q60001 (SCM-6)			Q60002 (SCM-6)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	2.9	2.9	2.4	2.9	2.9	2.4	5.2	2.9	5.2	5.1	2.9	5.3	0.5	13.0	0.4	12.2	0	12.7		
REC	3.0	3.0	2.4	3.0	2.9	2.4	5.2	2.9	5.1	5.2	2.9	5.7	0.5	13.0	0.4	12.1	0	12.6		
FF	15.0	2.6	15.3	9.7	2.7	8.2	15.3	2.9	15.9	10.0	2.7	9.7	0.6	13.0	0.4	12.1	0	12.6		
Ref. No.	Q60003 (SCM-6)			Q60004 (SCM-6)			Q60005 (SCM-6)			Q60006 (SCM-6)			Q60007 (SCM-6)			Q60008 (SCM-6)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	12.8	0	12.3	0	0	0	0	0.1	0	0	4.9	0.1	0	4.6	0.1	0	0.1	0.1		
REC	12.8	0	12.3	0	0	0	0	0	0	0	4.9	0	0	4.6	0.1	0	12.3	-0.7		
FF	12.8	0	12.3	0	0	0	0	0	0	0	4.9	0	0	4.6	0.2	0	0.2	0.2		
Ref. No.	Q60501 (SCM-7)			Q60502 (SCM-7)			Q60503 (SCM-7)			Q60504 (SCM-7)			Q60505 (SCM-7)			Q60506 (SCM-7)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0.6	0.6	1.2	0.6	1.2	0.4	4.2	4.8	4.8	5.0	4.8	4.2	0	0	0.8	0	0	0.7		
REC	0.6	0.6	1.2	0.6	1.2	0.4	4.2	4.8	4.8	5.0	4.8	4.2	0	0	0.8	0	0	0.7		
FF	0.6	0.6	1.2	0.6	1.2	0.4	0	0.4	0	5.2	-0.4	5.2	0	14.9	0	0	0	0		
Ref. No.	Q60507 (SCM-7)			Q60508 (SCM-7)			Q60509 (SCM-7)													
Mode	E	C	B	E	C	B	E	C	B											
STOP	0	14.8	0	14.9	1.4	14.8	0	4.9	0.2											
REC	0	14.8	0	14.9	1.4	14.8	0	4.8	0.2											
FF	0	14.8	0	14.9	0	14.8	0	4.9	0											
Ref. No.	QR1502 (SCM-16)			QR1503 (SCM-16)			QR2003 (SCM-9)			QR2005 (SCM-9)			QR2304 (SCM-10)			QR2305 (SCM-10)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	5.5	0.1	4.7	0	0	0	0	2.0	0.8	0	4.9	0.6	5.0	0	4.9	5.0	0	4.9		
REC	5.5	0.1	4.7	0	0	0	0	2.0	0.8	0	4.9	0.6	5.0	0	4.9	5.0	0	4.9		
FF	5.5	0.2	4.7	0	0	0	0	2.0	0.8	0	4.9	0.6	5.0	2.7	-0.2	5.0	1.9	1.4		
Ref. No.	QR2306 (SCM-10)			QR2308 (SCM-10)			QR2309 (SCM-10)			QR2310 (SCM-10)			QR2311 (SCM-10)			QR2312 (SCM-10)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	0	0	5.0	0	5.0	1.0	5.0	0	0	0	0	0	11.6	0	11.6	0		
REC	0	0	0	0	2.0	3.0	5.0	1.1	4.9	0	0.3	3.1	0	0.3	0	0	0	4.8		
FF	0	2.6	0	0	1.8	2.4	5.0	3.3	3.4	0	0	0	0	0	11.6	0	11.6	0		
Ref. No.	QR2313 (SCM-10)			QR2314 (SCM-10)			QR2401 (SCM-11)			QR2402 (SCM-11)			QR2501 (SCM-8)			QR2502 (SCM-8)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	11.7	11.7	0	0	11.6	0	0	5.1	0	5.1	4.1	4.0	0	11.6	0	0	0	4.9		
REC	11.7	0	11.7	0	4.6	3.1	0	0.1	4.8	5.1	4.1	4.0	0	11.6	0	0	0	4.9		
FF	11.7	11.7	0	0	11.6	0	0	5.2	0	5.2	5.1	4.0	0	0	4.9	0	0	4.9		
Ref. No.	QR2503 (SCM-8)			QR2504 (SCM-8)			QR2505 (SCM-8)			QR2701 (SCM-14)			QR2702 (SCM-15)			QR2703 (SCM-15)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	11.6	0	0	0	4.9	0	0	4.9	0	0	5.1	5.0	1.4	4.0	0	0.3	0		
REC	0	11.6	0	0	0	4.9	0	0	4.9	0	0.4	0	5.0	1.4	4.0	0	1.6	1.4		
FF	0	0	4.9	0	0	4.9	0	11.6	0	0	0	5.2	5.0	0	16.4	0	1.8	1.2		

Ref. No.	QR2704 (SCM-15)			QR60001 (SCM-6)			QR60002 (SCM-6)			QR60003 (SCM-6)			QR60004 (SCM-6)			QR60006 (SCM-6)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0.1	2.4	5.2	0.4	4.5	0	12.6	0	12.8	0.2	12.8	0	0.1	2.9	0	0	4.0		
REC	0	0.1	2.5	5.1	0.4	4.5	0	12.6	0	12.8	12.7	0	0	0	0	0	0	4.0		
FF	0	0.1	2.4	5.2	0.4	4.6	0	12.6	0	12.8	0.3	12.8	0	0.1	2.9	0	0	4.0		
Ref. No.	QR60007 (SCM-6)			QR60008 (SCM-6)			QR60010 (SCM-6)			QR60013 (SCM-6)			QR60012 (SCM-6)			QR60501 (SCM-7)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	5.3	0	0	13.0	0	0	3.7	0	0	4.8	0	0	1.6	0	0	10.3	0		
REC	0	5.3	0	0	0.1	4.8	0	0.1	4.9	0	4.8	0	0	1.6	0	0	10.2	0		
FF	0	5.3	0	0	13.0	0	0	3.7	0	0	4.9	0	0	1.6	0	0	10.2	0		
Ref. No.	QR60502 (SCM-7)			QR60503 (SCM-7)																
Mode	E	C	B	E	C	B														
STOP	4.9	4.8	0	0	0	13.9														
REC	4.9	4.8	0	0	0	13.9														
FF	5.2	0.3	4.9	0	0	13.9														

VIDEO I/O C.B.A.

Ref. No.	IC3001 (SCM-32)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	4.5	3.0	5.1	1.8	1.6	2.2	2.9	0	2.9	3.6	2.7	3.0	2.9	1.6						
REC	4.5	3.0	5.1	1.8	-1.6	2.2	2.9	0	2.9	3.6	2.7	3.0	2.9	1.6						
Ref. No.	IC3002 (SCM-32)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	4.7	3.0	3.0	2.8	2.7	4.4	3.3	4.7	3.8	1.6	4.0	0	1.9	2.4	2.3	4.7	0	2.9	2.7	2.9
REC	4.7	3.0	3.0	2.8	2.7	4.4	3.3	4.7	3.8	1.6	4.0	0	1.9	2.4	2.3	4.7	0	2.9	2.7	2.9
Ref. No.	IC3003 (SCM-32)																			
Mode	21	22	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16		
STOP	3.3	2.9	2.3	2.9	2.7	2.6	2.6	0	-4.9	0	0.1	0	0.1	4.5	4.5	4.5	2.9	4.7		
REC	3.3	2.9	2.4	2.9	2.7	2.6	2.6	0	-4.9	0	0.1	0.2	0.1	4.5	4.5	4.5	2.9	4.7		
Ref. No.	IC3004 (SCM-32)																			
Mode	1	2	3	4	5	6	7	8												
STOP	7.1	0.1	7.1	0	0	11.4	6.3	0												
REC	7.1	0.1	7.1	0	0	11.4	6.3	0												
Ref. No.	IC3005 (SCM-32)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	4.8	5.1	0.3	4.5	0.1	4.9	0	4.4	0.5	0.1	0.3	5.1	4.2	0	5.1				
REC	0	4.8	5.1	0.3	4.5	0.1	4.9	0	4.4	0.5	0.1	0.3	5.1	4.2	0	5.1				
Ref. No.	IC3006 (SCM-31)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	0.1	3.6	4.6	4.6	0	4.5	0	2.3	2.5	0	0.1	0.4	0	4.6						
REC	0.1	0.1	0.3	0.2	0	0	0	2.3	2.5	0	0.1	0.4	0	4.6						
Ref. No.	IC3007 (SCM-31)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	3.5	1.9	4.6	2.9	2.6	2.6	0	2.0	0	0	0	0	2.5	3.5	1.1	0.2	2.8	2.8	2.3	4.6
REC	3.5	1.9	4.6	2.9	2.6	2.6	0	2.0	0	0	0	1.0	2.5	3.5	1.1	0.2	2.8	2.8	2.3	4.7
Ref. No.	IC3007 (SCM-31)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32								
STOP	0	4.5	0.2	2.1	3.7	0.1	4.9	2.4	2.7	3.4	0	4.6								
REC	0	4.6	0.2	2.1	3.7	0.1	4.9	2.4	2.7	3.5	0	4.7								
Ref. No.	IC3008 (SCM-31)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	-0.9	-0.5	-0.4	4.9	-0.1	-0.1	0	1.5	1.5	1.5	-5.0	-2.4	-2.4	-2.4						
REC	-0.9	-0.5	-0.4	4.9	-0.1	-0.1	-0.1	1.5	1.5	1.5	-5.0	-2.4	-2.4	-2.4						
Ref. No.	IC3009 (SCM-31)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	1.5	1.6	1.5	1.6	1.4	0	0	0	0	2.5	0.2	0.2	0.2	0.2	0.2	4.9				
REC	1.5	1.6	1.5	1.6	1.4	0	0	0	0	2.5	0.2	0.2	0.2	0.2	0.2	4.9				
Ref. No.	IC3010 (SCM-32)								IC3011 (SCM-32)				IC3012 (SCM-32)							
Mode	1	2	3	4	5	6	7	8	I	G	O	1	2	3	4	5	6	7	8	
STOP	2.9	3.6	2.8	0	0	4.7	2.1	0	11.6	0	5.1	2.0	1.2	1.2	-4.8	1.6	1.6	1.6	4.7	
REC	2.9	3.6	2.8	0	0	4.7	2.1	0	11.6	0	5.1	2.0	1.2	1.2	-4.8	1.6	1.6	1.6	4.7	
Ref. No.	IC3013 (SCM-32)																			
Mode	1	2	3	4	5	6	7	8												
STOP	3.6	0	0	-4.8	1.5	1.5	1.6	4.7												
REC	3.6	0	0	-4.8	1.5	1.5	1.6	4.7												
Ref. No.	IC3014 (SCM-32)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	3.0	4.7	4.7	3.0	0	3.2	0	0	4.6	4.7	1.7	0.1	0	4.6	4.7				
REC	0	3.0	4.7	4.7	3.0	0	3.2	0	0	4.6	4.7	1.7	0.1	0	4.6	4.7				
Ref. No.	IC3015 (SCM-32)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	4.6	2.9	5.1	1.9	1.6	2.1	2.9	0	2.9	5.1	2.7	3.0	2.9	1.6						
REC	4.6	2.9	5.1	1.9	1.6	2.1	2.9	0	2.9	5.1	2.7	3.0	2.9	1.6						
Ref. No.	IC3017 (SCM-34)					IC3018 (SCM-32)					IC3020 (SCM-31)									
Mode	1	2	3	4	5	1	2	3	4	5	I	G	O							
STOP	0.1	4.9	0	0	4.8	5.1	4.5	0	4.5	5.1	11.5	0	5.0							
REC	0.1	4.9	0	0	4.8	5.1	4.5	0	4.5	5.1	11.5	0	5.0							

Ref. No.	IC3153 (SCM-31)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	1.5	1.4	1.5	0.1	4.0	0	1.2	0	0.1	4.6	4.6	0.2	4.0	0	1.0	4.6				
REC	1.5	1.4	1.3	0.1	4.1	0	1.2	0	0.1	4.6	4.6	0.2	4.0	0	0.8	4.6				
Ref. No.	IC3201 (SCM-33)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	2.5	0.3	2.4	1.9	0	2.6	1.9	2.4	4.6	2.0	0.3	4.1	0.5	3.2	0.4	0				
REC	2.5	0.3	2.4	1.9	0	3.4	1.9	2.4	4.6	2.0	0	4.1	0.4	3.2	0.3	0				
Ref. No.	IC3202 (SCM-33)							IC3203 (SCM-33)												
Mode	1	2	3	4	5	6	7	1	2	3	4	5	6	7	8					
STOP	3.2	0	2.9	0	3.1	0.7	4.6	2.9	2.2	2.3	0	3.5	0	3.5	4.6					
REC	3.2	0	2.9	0	3.1	0.7	4.6	3.4	1.7	2.3	0	3.5	0	3.5	4.7					
Ref. No.	IC3204 (SCM-33)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	1.0	1.9	1.0	1.0	2.3	1.7	0.9	1.9	2.0	4.7	4.7	2.0	2.0	0	2.5	4.7	2.6	2.4	2.4	2.4
REC	1.0	2.0	1.0	1.0	2.3	1.7	0.9	1.9	2.0	4.7	4.7	2.0	2.0	0	2.3	4.7	2.6	2.3	2.4	2.4
Ref. No.	IC3204 (SCM-33)												IC3205 (SCM-33)							
Mode	21	22	23	24	25	26	27	28	29	30	31	32	1	2	3	4	5	6	7	8
STOP	3.1	3.0	2.2	2.2	4.7	2.1	0	3.1	2.4	2.4	2.3	4.7	-1.0	-1.7	-4.8	2.4	2.4	4.7	-1.7	-1.0
REC	3.1	3.0	2.2	4.7	1.7	2.1	0	3.1	2.3	2.3	2.3	4.7	-1.0	-1.7	-4.9	2.4	2.4	4.8	-1.7	-1.0
Ref. No.	IC3206 (SCM-33)																			
Mode	1	2	3	4	5	6	7	8	9											
STOP	2.6	3.3	7.4	4.2	0	0	0.2	0	8.2											
REC	2.6	3.3	7.3	4.2	0	0	0.2	0	8.2											
Ref. No.	IC3207 (SCM-33)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	3.6	4.9	0.1	4.2	0.1	4.9	0.9	0	0.1	4.9	0.3	4.2	0.1	4.9	0.8	4.9				
REC	3.6	4.9	0.1	4.2	0.1	4.9	0.9	0	0.1	4.9	0.1	4.2	0.1	4.9	0.8	4.9				
Ref. No.	IC3208 (SCM-33)					IC3209 (SCM-33)								IC3301 (SCM-34)						
Mode	1	2	3	4	5	1	2	3	4	5	6	7	8	1	2	3	4	5		
STOP	0	0.4	0	4.5	4.8	2.8	0	2.8	0	0	4.6	2.0	0	0	4.5	0	0.4	4.9		
REC	0	0.4	0	4.5	4.9	2.8	0	2.8	0	0	4.6	2.0	0	0	4.5	0	0.4	4.9		
Ref. No.	IC3302 (SCM-34)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	-0.1	0.9	0.9	0	4.9	0.4	0	2.5	3.2	2.8	3.2	0.2	0.1	4.9						
REC	-0.1	0.9	0.8	0.8	4.9	0.4	0	2.5	3.2	2.8	3.2	0.2	0.1	4.9						
Ref. No.	IC3303 (SCM-34)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	2.8	2.8	2.8	4.9	2.5	2.5	2.5	1.5	2.3	2.3	0	0.9	0.9	0.9						
REC	2.8	2.8	2.8	4.9	2.5	2.5	2.5	1.4	2.3	2.3	0	0.8	0.8	0.8						
Ref. No.	IC3304 (SCM-34)																			
Mode	1	2	3	4	5	6	7	8												
STOP	7.1	0.1	7.1	0	0	11.5	6.4	0												
REC	7.1	0.1	7.1	0	0	11.5	6.4	0												
Ref. No.	IC3305 (SCM-34)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	3.3	4.0	3.3	0.2	2.8	0	2.9	2.4	4.8	4.6	0.7	0.1	1.2	3.7	3.5				
REC	0	3.3	4.0	3.2	0.2	2.8	0	2.9	2.4	4.8	4.6	0.7	0.1	1.3	3.7	3.5				
Ref. No.	IC3306 (SCM-34)																			
Mode	1	2	3	4	5	6	7	8												
STOP	2.9	4.5	2.8	3.6	2.9	4.8	2.1	0												
REC	2.9	4.5	2.8	0.8	2.9	4.8	2.1	0												
Ref. No.	IC3307 (SCM-34)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	2.4	4.8	0	0.9	3.4	1.6	0	4.7	0.4	3.5	0	4.8	4.6	0	4.8				
REC	0	2.4	4.8	0	0.9	3.4	1.6	0	4.7	0.4	3.5	0	4.8	4.6	0	4.8				
Ref. No.	IC3308 (SCM-34)								IC3309 (SCM-34)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	4.8	4.5	2.4	2.4	0	2.4	0	2.4	0	0	0	-4.8	0	0	0	4.7				
REC	4.8	4.5	2.4	2.4	0	2.4	0	2.4	0	0	0	-4.8	0	0	0	4.7				

Ref. No.	IC3310 (SCM-34)								IC3311 (SCM-36) SUB					IC3312 (SCM-36) SUB						
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	1	2	3	4	5		
STOP	4.8	3.6	2.4	2.5	0	2.5	0	2.5	2.5	2.5	0	0	4.8	0	0.9	0	0	4.8		
REC	4.8	0	2.4	2.5	0	2.5	0	2.5	2.5	2.5	0	0	4.8	0	0.9	0	0.1	4.8		
Ref. No.	Q3001 (SCM-32) -								Q3004 (SCM-32)				Q3005 (SCM-32)			Q3006 (SCM-32)				
Mode	1	2	3	4	5	6	1	2	3	4	5	6	E	C	B	E	C	B		
STOP	5.1	2.4	3.1	0	3.0	2.4	3.1	0.1	3.1	4.1	0.1	4.1	1.9	9.7	2.6	1.9	5.3	0		
REC	5.1	2.4	3.1	0	3.0	2.4	3.1	0.1	3.1	4.1	0.1	4.1	1.9	9.6	2.6	1.9	5.4	0		
Ref. No.	Q3007 (SCM-32)			Q3008 (SCM-32)			Q3009 (SCM-32)						Q3010 (SCM-32)							
Mode	E	C	B	E	C	B	1	2	3	4	5	6	1	2	3	4	5	6		
STOP	10.3	5.4	9.7	6.0	0	5.4	4.7	3.4	3.0	4.7	2.9	2.3	11.4	4.1	3.5	11.4	3.5	2.9		
REC	10.3	5.4	9.6	6.0	0	5.4	4.7	3.4	3.0	4.7	2.9	2.3	11.4	4.1	3.5	11.4	3.5	2.9		
Ref. No.	Q3011 (SCM-32)			Q3012 (SCM-32)			Q3013 (SCM-32)						Q3017 (SCM-31)							
Mode	E	C	B	E	C	B	1	2	3	4	5	6	E	C	B					
STOP	3.5	-4.9	2.9	2.6	11.4	3.2	-4.9	2.6	3.2	-4.9	3.2	3.8	5.0	5.0	5.7					
REC	3.5	-4.9	2.9	2.6	11.4	3.2	-4.9	2.6	3.2	-4.9	3.2	3.8	0.3	5.0	0					
Ref. No.	Q3018 (SCM-32)			Q3019 (SCM-32)			Q3020 (SCM-31)			Q3021 (SCM-32)			Q3022 (SCM-32)			Q3024 (SCM-32)				
Mode	D	G	S	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	1.2	0	1.6	2.3	6.8	2.9	11.5	0	11.5	2.3	4.9	2.8	2.8	0	2.3	0	4.9	0		
REC	1.2	0	1.6	2.3	6.8	2.9	11.5	11.4	10.8	2.3	4.9	2.8	2.8	0	2.3	0	4.9	0		
Ref. No.	Q3025 (SCM-31)			Q3026 (SCM-31)			Q3027 (SCM-31)			Q3028 (SCM-32)			Q3029 (SCM-32)			Q3030 (SCM-31)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	5.0	0	0.9	2.7	1.6	1.6	3.0	2.3	4.7	0	4.7	2.1	4.7	1.9	1.7	2.9	2.4		
REC	0	4.6	0	0.9	2.7	1.6	0	3.0	2.3	4.7	0	4.7	2.1	4.7	1.9	1.7	2.9	2.4		
Ref. No.	Q3031 (SCM-31)			Q3032 (SCM-31)			Q3033 (SCM-31)			Q3034 (SCM-32)			Q3040 (SCM-32)			Q3201 (SCM-33)				
Mode	D	G	S	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	-0.7	0	2.3	0	1.7	1.6	4.6	2.3	2.0	5.1	2.7	0.9	4.7	1.5	-3.7	0.9	-2.9		
REC	0	-0.7	0	2.3	0	1.7	0	4.6	0	2.0	5.1	2.7	1.0	4.7	1.6	-3.7	0.9	-2.9		
Ref. No.	Q3202 (SCM-33)			Q3203 (SCM-33)			Q3204 (SCM-33)			Q3205 (SCM-33)			Q3206 (SCM-33)			Q3207 (SCM-33)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0.3	4.6	0.9	-1.6	1.5	-0.8	1.9	4.6	1.0	1.8	4.6	2.4	1.9	4.7	0.6	1.8	4.7	0.6		
REC	0.3	4.6	0.9	-1.6	1.5	-0.8	0.2	0	0.7	0.1	4.6	0.2	1.9	4.7	0.6	1.9	4.7	0.6		
Ref. No.	Q3208 (SCM-33)			Q3209 (SCM-33)			Q3210 (SCM-33)			Q3211 (SCM-33)			Q3212 (SCM-33)			Q3213 (SCM-33)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	1.8	7.7	2.5	7.4	11.5	7.7	0	2.2	0	-2.6	-0.1	-1.8	1.9	4.7	2.5	2.6	4.7	3.2		
REC	1.8	7.7	2.5	7.1	11.5	7.7	0	2.2	0	-2.6	0	-1.8	1.9	4.7	2.5	2.6	4.7	3.2		
Ref. No.	Q3214 (SCM-33)			Q3215 (SCM-33)			Q3216 (SCM-33)			Q3217 (SCM-33)			Q3218 (SCM-33)			Q3219 (SCM-33)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	-0.8	4.7	-0.2	1.6	1.5	-0.8	0	0	0.6	-0.6	4.7	0	-0.7	1.4	0	0.7	4.7	1.3		
REC	-0.8	4.7	-0.2	-1.5	1.5	-0.8	0	0	0.6	-0.6	4.7	0	-0.7	1.4	0	0.7	4.7	1.3		
Ref. No.	Q3220 (SCM-33)			Q3221 (SCM-33)			Q3222 (SCM-33)			Q3223 (SCM-33)			Q3224 (SCM-33)			Q3225 (SCM-33)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	-0.7	1.2	0	1.3	4.7	1.9	3.1	4.8	3.5	2.4	4.8	2.8	1.6	4.8	2.2	-0.8	0.7	-0.1		
REC	-0.7	1.2	0	1.3	4.7	1.9	3.1	4.8	3.5	2.4	4.8	2.8	1.6	4.8	2.2	-0.8	0.6	0		
Ref. No.	Q3226 (SCM-33)			Q3227 (SCM-33)			Q3228 (SCM-33)					Q3229 (SCM-33)			Q3230 (SCM-33)			Q3231 (SCM-33)		
Mode	E	C	B	E	C	B	1	2	3	4	5	E	C	B	E	C	B	E	C	B
STOP	-0.6	4.7	0	0	-0.1	0	0.1	0.3	0	0	0	-0.8	4.7	-0.2	-1.5	1.4	-0.8	0	-4.8	-1.6
REC	-0.6	4.7	0	0	-0.1	0	0	0.3	0	0	0	-0.8	4.7	-0.2	-1.5	1.4	-0.8	-0.9	-4.8	-1.5
Ref. No.	Q3232 (SCM-33)			Q3233 (SCM-33)			Q3234 (SCM-33)			Q3235 (SCM-33)					Q3236 (SCM-33)					
Mode	E	C	B	E	C	B	E	C	B	1	2	3	4	5	1	2	3	4	5	
STOP	-0.9	-4.8	-1.5	-0.9	-4.8	-1.6	8.2	11.5	8.8	0.4	0.4	1.8	0	2.0	-0.1	0.1	0.4	0	0.4	
REC	-0.8	-4.8	-1.5	-0.9	-4.8	-1.5	8.2	11.5	8.8	0.4	0.4	1.8	0	2.0	0	0	0.4	0	0.4	
Ref. No.	Q3301 (SCM-34)			Q3302 (SCM-34)			Q3306 (SCM-34)			Q3307 (SCM-34)			Q3308 (SCM-34)			Q3309 (SCM-34)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	4.9	0.2	4.8	3.2	4.9	3.8	3.7	3.7	3.0	-0.6	4.7	0	2.9	4.7	2.8	2.2	4.7	2.9		
REC	4.9	0.2	4.8	3.2	4.9	3.8	0.8	0.1	0.2	-0.6	4.7	0	2.9	4.7	2.9	2.2	4.7	2.9		
Ref. No.	Q3310 (SCM-34)			Q3311 (SCM-34)			Q3312 (SCM-34)			Q3313 (SCM-34)			Q3314 (SCM-34)			Q3315 (SCM-34)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	3.1	4.8	3.8	0.9	4.8	1.5	-2.7	2.6	-2.1	1.9	4.8	2.6	1.9	4.8	2.5	1.4	3.4	2.1		
REC	3.1	4.8	3.8	0.9	4.8	1.5	-2.7	2.6	-2.1	1.9	4.8	2.6	1.9	4.8	2.4	1.3	3.5	2.1		

Ref. No.	Q3316 (SCM-34)			Q3317 (SCM-34)			Q3318 (SCM-34)			Q3319 (SCM-34)			Q3320 (SCM-34)			Q3321 (SCM-34)				
	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
Mode																				
STOP	-0.5	4.8	0	-1.2	4.8	-0.6	-0.5	4.8	0	2.0	0	1.4	-0.8	1.4	0	1.1	4.7	1.7		
REC	-0.5	4.8	0	-1.2	4.8	-0.6	-0.5	4.8	0	2.0	0	1.4	-0.8	1.4	0	1.1	4.7	1.7		
Ref. No.	QR3002 (SCM-31)			QR3003 (SCM-31)			QR3005 (SCM-31)			QR3006 (SCM-31)			QR3007 (SCM-32)			QR3008 (SCM-32)				
	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
Mode																				
STOP	0	0	3.8	4.9	0	4.5	0	0	7.9	11.5	0	11.5	0	1.8	0	0	0	4.7		
REC	0	0	3.8	4.9	0	4.5	0	11.4	0.6	11.5	11.5	0	0	1.8	0	0	0	4.7		
Ref. No.	QR3009 (SCM-31)			QR3010 (SCM-31)			QR3011 (SCM-31)			QR3012 (SCM-31)			QR3013 (SCM-31)			QR3014 (SCM-31)				
	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
Mode																				
STOP	0	5.7	0	0	4.9	0	4.9	4.9	5.3	4.9	3.5	5.4	4.9	3.5	4.8	0	0	0		
REC	0	0	7.9	0	4.9	0	4.9	4.9	5.4	4.9	3.5	5.4	4.9	3.5	4.8	0	0	0		
Ref. No.	QR3015 (SCM-31)			QR3016 (SCM-32)			QR3017 (SCM-32)			QR3018 (SCM-32)			QR3201 (SCM-33)			QR3204 (SCM-33)				
	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
Mode																				
STOP	0	2.3	0.1	0	0.1	1.8	4.7	4.7	0.1	1.5	4.7	2.1	4.6	0	4.6	0	0	5.4		
REC	0	2.3	0.1	0	0.1	1.8	4.7	4.7	0.1	1.5	4.7	2.1	4.6	0	4.6	0	0	5.4		
Ref. No.	QR3205 (SCM-33)			QR3206 (SCM-33)			QR3209 (SCM-33)			QR3211 (SCM-33)			QR3212 (SCM-33)			QR3301 (SCM-34)				
	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
Mode																				
STOP	0	0	5.3	0	2.0	2.5	4.6	0	5.4	0	0	0	0	2.0	1.8	0	4.9	0.1		
REC	0	0	5.3	0	2.0	2.5	4.6	0	5.4	0	0	0	0	2.0	1.8	0	4.9	0.1		
Ref. No.	QR3213 (SCM-33)																			
	E	C	B																	
Mode																				
STOP	3.3	0.4	3.3																	
REC	3.4	0.4	3.4																	

TBC (1) C.B.A.

Ref. No.	IC8001 (SCM-56)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	0	1.5	1.5	2.6	1.1	2.8	2.1	1.6	1.4	4.9	1.1	4.9	4.9	4.9	2.6	2.6	4.9	1.3	0
REC	0	0	1.5	1.6	2.4	1.1	2.6	2.1	1.6	1.4	4.9	1.1	4.9	4.9	4.9	2.6	2.6	4.9	1.3	0
Ref. No.	IC8001 (SCM-56)																			
Mode	21	22	23	24																
STOP	0	0.6	0.6	0																
REC	0	0.6	0.6	0																
Ref. No.	IC8002 (SCM-56)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	1.4	1.6	2.1	2.8	1.1	2.6	1.5	1.5	0	1.1	2.3	2.3	3.1	1.4	2.9	2.2	1.7	1.4	5.1
REC	0	1.4	1.6	2.1	2.6	1.1	2.4	1.6	1.5	0	1.1	2.3	2.3	2.9	1.3	2.8	2.2	1.7	1.4	5.1
Ref. No.	IC8003 (SCM-56)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	0	0	0	0	0	0	0	4.6	5.1	2.3	0	2.3	3.1	1.3	3.4	2.2	1.7	1.5	1.3
REC	0	0	0	0	0	0	0	0	4.6	5.1	2.2	0	2.3	2.8	1.3	3.4	2.2	1.7	1.5	1.3
Ref. No.	IC8003 (SCM-56)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	1.4	1.9	3.0	1.1	2.6	2.0	2.0	0	0	0	0	0	5.1	0	0	0	0	1.5	1.7	2.2
REC	1.4	1.9	3.0	1.1	2.4	1.9	1.9	0	0	0	0	0	5.1	0	0	0	0	1.5	1.7	2.2
Ref. No.	IC8003 (SCM-56)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	3.4	1.3	3.0	2.3	2.3	1.5	1.7	2.2	3.4	1.3	3.1	0	2.3	5.1	2.3	0	0	0	0	0
REC	3.4	1.3	2.8	2.3	2.2	1.5	1.7	2.2	3.4	1.3	2.8	0	2.3	5.1	2.2	0	0	0	0	0
Ref. No.	IC8003 (SCM-56)																			
Mode	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80
STOP	0	0	0	0	0	0	5.1	1.2	5.1	1.2	0	0	5.1	5.1	0	4.6	0	0	0	0
REC	0	0	0	0	0	0	5.1	1.2	5.1	1.2	0	0	5.1	5.1	0	4.6	0	0	0	0
Ref. No.	IC8003 (SCM-56)																			
Mode	81	82	83	84																
STOP	0	0	0	0																
REC	0	0	0	0																
Ref. No.	IC8004 (SCM-56)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0.4	0.3	0	2.0	2.0	2.0	3.0	1.2	0	0	0	0	0	0	0	0	2.0	0	5.1	0
REC	0.4	0.3	0	2.0	1.9	1.8	2.6	1.1	0	0	0	0	0	0	0	0	2.0	0	5.1	0
Ref. No.	IC8004 (SCM-56)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38		
STOP	0	0	0	1.3	3.1	2.2	2.3	0	0	0	5.1	1.1	2.9	1.9	2.0	2.4	0.3	0		
REC	0	0	0	1.2	2.9	2.1	2.2	0	0	0	5.1	1.0	2.6	1.8	1.9	2.4	0.3	0		
Ref. No.	IC8005 (SCM-56)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0.4	0.3	0	2.0	3.1	2.0	1.5	1.2	0	0	0	0	0	0	0	0	2.0	0	5.1	0
REC	0.4	0.3	0	2.0	3.1	1.9	1.5	1.2	0	0	0	0	0	0	0	0	2.0	0	5.1	0
Ref. No.	IC8005 (SCM-56)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38		
STOP	0	0	0	1.5	1.7	2.3	3.4	0	0	0	5.1	1.3	1.5	2.0	3.1	2.4	0.3	0		
REC	0	0	0	1.5	1.7	2.3	3.4	0	0	0	5.1	1.3	1.5	2.0	3.1	2.4	0.3	0		
Ref. No.	IC8006 (SCM-56)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0.4	0.3	0	2.0	2.0	1.9	2.9	1.1	5.1	0	0	0	0	0	0	0	2.0	0	5.1	0
REC	0.4	0.3	0	2.0	2.0	1.8	2.6	1.1	5.1	0	0	0	0	0	0	0	2.0	0	5.1	0
Ref. No.	IC8006 (SCM-56)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38		
STOP	0	0	0	1.3	3.1	2.2	2.3	0	0	0	0	1.1	2.9	1.9	2.0	2.4	0.3	0		
REC	0	0	0	1.2	2.9	2.1	2.2	0	0	0	0	1.0	2.6	1.8	1.9	2.4	0.3	0		
Ref. No.	IC8007 (SCM-56)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0.4	0.3	0	2.0	3.1	2.0	1.5	1.2	5.1	0	0	0	0	0	0	0	2.0	0	5.1	0
REC	0.4	0.3	0	1.9	3.1	1.9	1.5	1.2	5.1	0	0	0	0	0	0	0	1.8	0	5.1	0

Ref. No.	IC8007 (SCM-56)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38		
STOP	0	0	0	1.5	1.7	2.3	3.4	0	0	0	0	1.3	1.5	2.0	3.1	2.4	0.3	0		
REC	0	0	0	1.5	1.7	2.2	3.4	0	0	0	0	1.3	1.5	2.0	3.1	2.4	0.3	0		
Ref. No.	IC8008 (SCM-56)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	2.0	2.3	2.8	1.4	3.2	2.0	1.5	1.3	0	2.4	1.5	1.7	2.2	3.5	1.6	3.0	2.5	2.3	5.1
REC	0	1.9	2.1	2.9	1.3	3.1	2.0	1.5	1.3	0	2.4	1.5	1.7	2.2	3.4	1.4	3.0	2.3	2.2	5.1
Ref. No.	IC8009 (SCM-56)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	0.9	5.1	1.5	1.7	2.2	3.4	1.3	3.0	2.3	2.3	0.1	4.0	0	4.0	4.0	1.9	1.9	2.5	1.1
REC	0	0.9	5.1	1.5	1.7	2.2	3.6	1.7	2.9	2.6	2.4	0.1	4.0	0	4.0	4.0	2.0	2.2	2.4	1.4
Ref. No.	IC8009 (SCM-56)																			
Mode	21	22	23	24	25	26	27	28												
STOP	2.9	2.0	1.4	1.3	0	3.9	0	5.1												
REC	3.0	1.9	1.4	1.3	0	3.9	0	5.1												
Ref. No.	IC8010 (SCM-56)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
REC	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Ref. No.	IC8010 (SCM-56)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	1.9	2.1	2.2	1.3	3.1	1.9	1.5	1.3	0	2.4	2.6	2.8	1.6	3.6	2.2	1.7	1.5	0	0	0
REC	2.0	2.2	2.4	1.4	3.0	1.9	1.4	1.3	0	2.4	2.6	2.9	1.7	3.6	2.2	1.7	1.5	0	0	0
Ref. No.	IC8010 (SCM-56)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	5.1	0	5.1	5.1	0	0	0	1.5	1.7	2.2	3.9	1.3	2.7	2.6	2.3	1.5	1.7	2.2	3.8	1.6
REC	5.1	0	5.1	5.1	0	0	0	1.5	1.7	2.2	3.4	1.2	3.1	2.2	2.2	1.5	1.7	2.2	3.4	1.3
Ref. No.	IC8010 (SCM-56)																			
Mode	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80
STOP	2.6	2.5	2.4	0	0	0	5.1	5.1	0	0	0	0	0	0	0	0	0	0	0	0
REC	3.0	2.2	2.3	0	0	0	5.1	5.1	0	0	0	0	0	0	0	0	0	0	0	0
Ref. No.	IC8010 (SCM-56)																			
Mode	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
STOP	0	0	0	0	0	0	0	0	0	0	5.1	0	0	5.1	0	1.2	5.1	5.1	5.1	5.4
REC	0	0	0	0	0	0	0	0	0	0	5.1	0	0	5.1	0	1.2	5.1	5.1	5.1	5.4
Ref. No.	IC8011 (SCM-62)(SCM-56)														IC8012 (SCM-56)					
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	G	V	O			
STOP	1.9	0	2.4	2.0	0	1.9	0	4.5	5.1	0	4.6	0	5.1	5.1	0	5.1	5.1			
REC	1.9	0	2.4	2.1	0	1.9	0	4.6	5.1	0	4.6	0	5.1	5.1	0	5.1	5.1			
Ref. No.	IC8013 (SCM-56)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	5.1	4.6	0.9	5.1	5.1	0	0	2.6	2.6	5.1	0	2.6	5.1	5.1						
REC	5.1	4.6	0.9	5.1	5.1	0	0	2.6	2.6	5.1	0	2.6	5.1	5.1						
Ref. No.	IC8014 (SCM-56)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	5.1	5.1	0.1	1.9	0	2.4	0	2.0	5.1	2.4	5.3	0	5.1	5.1						
REC	5.1	5.1	0.1	1.9	0	2.4	0	2.1	5.1	2.4	2.3	0	5.1	5.1						
Ref. No.	IC8015 (SCM-56)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	2.3	2.4	2.7	1.6	3.6	2.2	1.7	1.5	0	2.4	1.5	1.7	2.2	3.6	1.6	2.9	2.4	2.3	5.1
REC	0	2.3	2.4	2.8	1.6	3.5	2.2	1.7	1.5	0	2.4	1.5	1.7	2.2	3.4	1.6	3.0	2.3	2.2	5.1
Ref. No.	IC8016 (SCM-56)				IC8051 (SCM-57)				IC8052 (SCM-57)				IC8053 (SCM-57)							
Mode	I	G	O	I	G	O	I	G	O	I	G	O	1	2	3	4	5	6	7	8
STOP	11.6	0	4.9	11.6	0	9.1	11.6	0	5.1	0	0	0	-4.9	0	0	0	0	9.1		
REC	11.6	0	4.9	11.6	0	9.1	11.6	0	5.1	0	0	0	-4.9	0	0	0	0	9.1		
Ref. No.	IC8054 (SCM-57)								IC8055 (SCM-57)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	4.1	2.1	2.1	-4.9	0	0	0	9.1	3.6	0	0	-4.9	0	0	0	9.1				
REC	4.1	2.1	2.1	-4.9	0	0	0	9.1	3.6	0	0	-4.9	0	0	0	9.1				

Ref. No.	IC8056 (SCM-57)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	1.2	1.5	1.7	2.2	4.0	1.5	2.5	2.4	2.4	0	1.2	1.9	2.0	3.2	1.3	4.1	2.1	1.6	1.4	5.1
REC	1.2	1.5	1.7	2.2	3.4	1.3	2.8	2.3	2.3	0	1.2	1.9	2.0	3.7	1.2	3.5	2.1	1.6	1.4	5.1
Ref. No.	IC8057 (SCM-57)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	4.8	2.5	4.1	5.1	4.3	0	5.1	4.8	0	2.4	1.4	1.7	2.2	3.5	1.4	3.9	2.1	2.0	0
REC	0	4.8	2.5	4.1	5.1	4.3	0	5.1	4.8	0	2.4	1.4	1.7	2.2	3.5	1.3	3.8	1.9	2.0	0
Ref. No.	IC8101 (SCM-58)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0.4	0	1.7	1.5	2.3	0	1.7	1.6	2.4	2.5	2.4	0	2.5	2.4	2.3	1.4	1.0	0	5.0	5.1
REC	0	0	1.7	1.5	2.3	0	1.6	1.5	2.3	2.5	2.3	0	2.5	2.4	2.2	1.5	1.0	0	5.0	5.1
Ref. No.	IC8101 (SCM-58)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	4.9	5.0	0.2	5.0	0	0	0	0	0	2.5	0	0	0	0	5.0	0	1.0	0	5.0	2.3
REC	4.9	5.0	0.2	5.0	0	0	0	0	0	2.5	0	0	0	0	5.0	0	1.0	0	5.0	2.3
Ref. No.	IC8101 (SCM-58)																			
Mode	41	42	43	44	45	46	47	48												
STOP	0	0	5.0	0	5.0	2.5	0.4	0.4												
REC	0	0	5.0	0	5.0	2.5	0.4	0.4												
Ref. No.	IC8102 (SCM-58)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	5.1	5.1	4.5	0.1	0	1.3	0	0	5.0	5.1	4.4	0.1	0	1.6	5.1				
REC	0	5.1	5.1	4.5	0.1	0	1.3	0	0	5.0	5.1	4.4	0.1	0	1.6	5.1				
Ref. No.	IC8104 (SCM-58)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	0	0	0	0	0.4	1.6	0.3	5.1	3.5	2.1	0	5.1	5.1	0	0	4.3	0	0	0
REC	0	0	0	0	0	0.4	1.6	0.3	5.1	3.5	2.1	0	5.1	5.1	0	0	4.2	0	0	0
Ref. No.	IC8104 (SCM-58)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	0	0	2.2	5.1	4.2	1.7	5.1	1.6	5.1	1.6	0.2	5.1	5.1	5.1	0	5.1	0	0	0	0
REC	0	0	2.2	5.1	4.1	1.7	5.1	1.5	5.1	1.6	0.2	5.1	5.1	5.1	0	5.1	0	0	0	0
Ref. No.	IC8104 (SCM-58)																			
Mode	41	42	43	44	45	46	47	48												
STOP	0	5.1	0	0	0	0	0	4.0												
REC	0	5.1	0	0	0.1	0.1	1.6	4.0												
Ref. No.	IC8109 (SCM-61)(SCM-58)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	2.3	0	2.5	2.4	2.5	2.3	0	2.5	2.0	0	0	5.1	5.1	5.1						
REC	2.3	0	2.5	2.4	2.5	2.3	0	2.5	2.0	0	0	5.1	5.1	5.1						
Ref. No.	IC8110 (SCM-58)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	5.1	0.4	4.6	5.1	5.1	0	0	2.4	5.1	2.5	2.4	2.4	5.1	5.1						
REC	5.1	0.4	4.6	5.1	5.1	0	0	2.4	5.1	2.5	2.4	2.4	5.1	5.1						
Ref. No.	IC8112 (SCM-58)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0.4	5.1	4.2	0.2	4.9	1.1	0	0	4.2	5.1	4.2	0.2	4.9	1.0	5.1				
REC	0	0.4	5.1	4.2	0.2	4.9	1.1	0	0	4.2	5.1	4.2	0.2	4.9	1.0	5.1				
Ref. No.	IC8113 (SCM-58)(SCM-60)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0.4	5.1	1.3	4.4	0	1.2	0	1.4	5.1	5.1	0.2	3.2	0	1.5	5.1				
REC	0	0.4	5.1	1.4	4.4	0	1.2	0	1.4	5.1	5.1	0.2	3.2	0	1.5	5.1				
Ref. No.	IC8114 (SCM-58)										IC8115 (SCM-58)									
Mode	1	2	3	4	5	1	2	3	4	5										
STOP	0	4.6	0	0.4	5.1	0	0.4	0	5.0	5.1										
REC	0	4.6	0	0.4	5.1	0	0.4	0	5.0	5.1										
Ref. No.	IC8116 (SCM-58)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	5.4	5.4	5.4	0	2.5	0	0	0	0	5.1	5.1	0	0	0.4	2.6	4.9	0	0	0	0
REC	5.4	5.4	5.4	0	2.5	0	0	0	0	5.1	5.1	0	0	0.4	2.6	4.9	0	0	0	0

Ref. No.	IC8116 (SCM-58)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	5.1	0	0	0	0	2.6	0	5.1	0	0	5.1	5.1	1.6	4.5	2.5	5.1	2.3	4.4	2.7	0
REC	5.1	0	0	0	0	2.6	0	5.1	0	0	5.1	5.0	1.6	4.5	2.5	5.1	2.2	4.4	2.7	0
Ref. No.	IC8116 (SCM-58)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	0	5.1	0	0	0	4.6	5.0	5.1	4.6	0	0	0	0	0	0	1.8	0	0	0.1	2.4
REC	0	5.1	0	0	0	4.6	5.0	5.1	4.4	0	0	0	0	0	0	1.8	0	0	0.1	2.4
Ref. No.	IC8116 (SCM-58)										IC8118 (SCM-58)									
Mode	61	62	63	64	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
STOP	2.4	5.1	0	0	1.2	0.8	0.8	4.4	0.2	0	1.2	0	0	4.2	5.1	4.3	0.1	5.1	0.3	5.1
REC	2.4	5.1	0.1	0	1.2	0.8	0.8	4.4	0.2	4.9	1.2	0	0	4.2	5.1	4.2	0.1	5.1	0.1	5.1
Ref. No.	IC8119 (SCM-64) TBC SUB																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	5.1	4.5	0	2.7	2.7	0	0	0	0	4.5	0	5.0	5.0	5.0	5.1	5.1				
REC	5.1	4.6	0	2.7	2.7	0	0	0	0	4.5	0	5.0	5.0	5.0	5.1	5.1				
Ref. No.	IC8120 (SCM-64) TBC SUB														IC8201 (SCM-59)					
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	I	G	O			
STOP	0.1	0	0.1	0	0.1	0.1	0	0	0	0	0	0	0	5.1	11.6	0	9.2			
REC	0.1	0	0.1	0	0.1	0.1	0	0	0	0	0	0	0	5.1	11.6	0	9.2			
Ref. No.	IC8202 (SCM-59)								IC8203 (SCM-59)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	1.5	0.8	0.8	-4.8	0.7	0.7	0.7	4.7	0	0	0	-4.8	1.0	1.0	1.3	4.7				
REC	1.5	0.8	0.8	-4.8	0.7	0.7	0.7	4.7	0	0	0	-4.8	1.0	1.0	1.3	4.7				
Ref. No.	IC8204 (SCM-59)								IC8205 (SCM-59)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	4.0	3.5	3.5	-4.9	3.5	3.5	3.5	9.2	3.5	3.4	3.4	0	3.4	3.4	3.5	9.2				
REC	4.0	3.5	3.5	-4.9	3.5	3.5	3.5	9.2	3.5	3.4	3.4	0	3.4	3.4	3.5	9.2				
Ref. No.	IC8206 (SCM-59)								IC8207 (SCM-59)					IC8208 (SCM-59)						
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	1	2	3	4	5		
STOP	4.0	3.5	3.5	-4.9	0	0	0	9.2	3.5	3.5	0	0.1	4.7	1.3	0.8	0	0.1	4.7		
REC	4.0	3.5	3.5	-4.9	0	0	0	9.2	3.5	3.5	0	0.1	4.7	1.3	0.8	0	0.1	4.7		
Ref. No.	IC8210 (SCM-59)					IC8211 (SCM-58)(SCM-59)(SCM-62)														
Mode	1	2	3	4	5	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
STOP	3.5	3.5	0	0.1	4.7	0.4	0.4	0.2	5.0	0.4	0.4	0	0.1	0.1	5.1	0.1	5.1	0.1	5.1	
REC	3.5	3.5	0	0.1	4.7	0.4	0.4	0.2	5.0	0.4	0.4	0	0.1	0.1	5.1	0.1	5.1	0.1	5.1	
Ref. No.	IC8212 (SCM-64) TBC SUB																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	5.1	2.7	0	5.1	0	5.1	0	5.1	0	5.1	0.1	5.1	0	5.1						
REC	5.1	2.7	0	5.1	0	5.1	0	5.1	0	5.1	0.1	5.1	0	5.1						
Ref. No.	IC8301 (SCM-61)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	2.5	5.1	5.1	0	0	0	0	0	0	5.1	0	5.1	2.2	2.2	2.0	2.0	0	0.3	0	0
REC	2.5	5.1	5.1	0	0	0	0	0	0	5.1	0	5.1	2.3	2.2	2.0	1.9	4.6	0.3	0	0
Ref. No.	IC8301 (SCM-61)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	0	0	0	0	0	0	0	0	0	0	0	0	5.1	5.4	5.1	0	0	0	0	1.6
REC	0	0	0	0	0	0	0	0	0	0	0	0	5.1	5.4	5.1	0	0	0	0	1.6
Ref. No.	IC8301 (SCM-61)																			
Mode	41	42	43	44																
STOP	1.8	1.9	2.1	0																
REC	1.8	1.9	2.1	0																
Ref. No.	IC8302 (SCM-61)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	1.7	1.7	1.8	2.1	0	1.0	1.6	0.9	5.1	3.5	2.1	0	5.1	5.1	3.5	3.5	4.3	0	0	0
REC	1.6	1.8	1.9	2.1	0	1.0	1.6	0.9	5.1	3.5	2.1	0	5.1	5.1	3.5	3.5	4.3	0	0	0
Ref. No.	IC8302 (SCM-61)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	0	0	2.5	5.1	4.4	1.6	5.1	1.5	5.1	1.6	0.2	5.1	5.1	5.1	0	5.1	0	1.8	1.8	2.0
REC	0	0	2.5	5.1	4.4	1.6	5.1	1.5	5.1	1.5	0.3	5.1	5.1	5.1	0	5.1	0	1.8	1.8	2.1

Ref. No.	IC8302 (SCM-61)																			
Mode	41	42	43	44	45	46	47	48												
STOP	2.1	5.1	0	0	0.1	0.1	1.5	3.9												
REC	2.1	5.1	0	0	0.1	0.5	1.6	3.9												
Ref. No.	IC8303 (SCM-61)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0.4	0	0	0	4.3	4.3	0	4.3	0	0	0	0	0	0	0	0	2.5	0	5.1	0
REC	0.4	0	0	0	0	4.3	0	4.3	0	0	0	0	0	0	0	0	2.5	0	5.1	0
Ref. No.	IC8303 (SCM-61)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38		
STOP	0	0	0	1.9	2.0	2.2	2.3	0	0	0	5.1	1.8	1.8	2.0	2.1	1.9	0.3	0		
REC	0	0	0	1.9	2.0	2.3	2.4	0	0	0	5.1	1.8	1.8	2.0	2.1	1.9	0.3	0		
Ref. No.	IC8304 (SCM-61)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0.4	0	0	0	4.3	4.3	0	4.3	0	0	0	0	0	0	0	0	2.5	0	5.1	0
REC	0.4	0	0	0	0	0	0	4.3	0	0	0	0	0	0	0	0	2.5	0	5.1	0
Ref. No.	IC8304 (SCM-61)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38		
STOP	0	0	0	2.0	2.0	2.2	2.3	0	0	0	0	1.8	1.8	2.0	2.1	1.9	0.3	0		
REC	0	0	0	2.0	2.0	2.2	2.3	0	0	0	0	1.8	1.8	2.0	2.1	1.9	0.3	0		
Ref. No.	IC8306 (SCM-61)														IC8308 (SCM-61)					
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	I	G	O			
STOP	5.1	2.5	2.4	2.4	2.4	2.4	0	5.1	0	5.1	2.5	2.4	5.1	5.1	11.6	0	5.1			
REC	5.1	2.5	2.4	2.4	2.4	2.4	0	5.1	0	5.1	2.5	2.4	5.1	5.1	11.6	0	5.1			
Ref. No.	IC8309 (SCM-61)																IC8312 (SCM-61)			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	I	G	O	
STOP	1.0	1.0	0	0	0	0	0	0	0	1.0	1.0	0.9	0.9	0.9	1.0	5.1	11.6	0	5.1	
REC	1.0	1.0	0	0	0	0	0	0	0	1.0	1.0	0.9	0.9	0.9	1.0	5.1	11.6	0	5.1	
Ref. No.	IC8401 (SCM-62)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
EJECT	0	5.1	0	5.1	5.1	5.1	5.1	5.1	5.1	5.1	0	5.4	5.1	4.9	0	0	0	5.1	0.1	0.4
REC	0	5.1	0	5.1	5.1	5.1	5.1	5.1	5.1	5.1	0	5.4	5.1	4.9	0	0.1	0	5.1	0.1	0.4
Ref. No.	IC8401 (SCM-62)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
EJECT	0	5.1	5.1	1.0	0.2	0	5.1	0	0.1	0.1	5.1	5.1	5.1	0	0	0	5.1	0	5.1	5.1
REC	0	5.1	5.1	1.0	0.1	0	5.1	0	0.1	0.1	5.0	0	5.1	0	0	0	5.1	0	5.1	5.0
Ref. No.	IC8401 (SCM-62)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
EJECT	5.1	0.1	5.1	0	0	5.1	5.4	5.1	5.1	0	5.0	5.1	0	2.6	0	5.1	0	0	0	0
REC	5.1	0.1	5.1	0	0.1	0.1	5.4	5.0	5.1	0	5.0	5.1	0.2	2.5	0.2	5.1	0	0	0	0
Ref. No.	IC8401 (SCM-62)																			
Mode	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80
EJECT	2.9	0	0	0	0	1.3	5.4	2.3	5.1	0	3.0	0	1.9	2.4	1.7	1.2	5.4	0	5.1	0
REC	5.1	0	0	0	5.1	5.1	5.0	2.3	2.3	2.0	2.7	0	2.1	2.4	1.6	1.3	5.4	0	0.2	0
Ref. No.	IC8401 (SCM-62)																			
Mode	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
EJECT	1.9	1.9	1.9	1.8	0	2.9	2.4	1.7	1.3	0.1	5.1	0	0.1	4.0	1.9	0	5.1	2.6	0	5.1
REC	1.9	1.9	1.5	2.1	0	3.1	2.4	1.6	1.3	0.1	5.1	0	0.1	4.1	2.0	0.2	5.1	0.2	0	0.1
Ref. No.	IC8401 (SCM-62)																			
Mode	101	102	103	104	105	106	107	108	109	110	111	112	113	114	115	116	117	118	119	120
EJECT	0.5	0	0.4	0.1	0.4	2.6	0	0	0	0	0	0	0	5.1	0	0	0	0	0	0
REC	0.5	0	0.4	0.2	0.4	2.6	0	0	0	0	0	0	0	5.1	0	0	0	0	0	0
Ref. No.	IC8401 (SCM-62)																			
Mode	121	122	123	124	125	126	127	128	129	130	131	132	133	134	135	136	137	138	139	140
EJECT	0	0	0	0	0	0	0	0	0	0	5.1	0	5.1	0	0	0	0	5.1	5.1	0
REC	0	0	0	0	0	0	0	0	0	0	5.1	4.6	5.1	0	0	0	0	5.1	0	0
Ref. No.	IC8401 (SCM-62)																			
Mode	141	142	143	144	145	146	147	148	149	150	151	152	153	154	155	156	157	158	159	160
EJECT	0	0	0	0	5.1	0.1	5.1	0.1	0.1	5.1	5.1	5.1	5.1	0	5.1	0	1.0	0	0	1.0
REC	0	0	5.1	0	0	0.1	5.1	0.1	5.1	5.1	5.1	0	5.1	0	0	0	1.0	0	0	0

Ref. No.	IC8401 (SCM-62)																			
Mode	161	162	163	164	165	166	167	168	169	170	171	172	173	174	175	176	177	178	179	180
EJECT	0	0	0	0	5.1	0	5.1	0	0	0	0	0	0	0	0	2.7	2.0	1.4	1.1	0
REC	0	0	0	0	5.1	0	5.1	5.1	0	0	0	0	0	0	0	0	2.1	1.4	0	1.0
Ref. No.	IC8401 (SCM-62)																			
Mode	181	182	183	184	185	186	187	188	189	190	191	192	193	194	195	196	197	198	199	200
EJECT	0	5.1	5.1	5.1	5.1	0	0	0	0	0	0	0	0	0	0	5.3	5.2	5.2	5.4	5.1
REC	0	5.1	5.1	0	0	0	0	0	5.1	0	0	0	0	0	5.3	5.3	5.4	5.4	5.4	5.1
Ref. No.	IC8401 (SCM-62)																			
Mode	201	202	203	204	205	206	207	208												
EJECT	5.1	5.4	0	0	5.4	0	0	2.3												
REC	0	0	0	0	5.4	0	0	0												
Ref. No.	IC8402 (SCM-62)														IC8403 (SCM-62)					
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	1	2	3	4	5	
STOP	0	0	0	0	0	0	0	1.0	1.0	0	1.0	0	1.0	5.1	0	0	0	0	5.1	
REC	0	0	0	0	0	0	0	1.0	1.0	0	1.0	0	1.0	5.1	0	0	0	0	5.1	
Ref. No.	IC8404 (SCM-62)(SCM-58)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	0	0	0	0.2	0	0	0	0	0	5.1	0	0	5.1	5.1						
REC	0	0	0	0.2	0	0	0	0	0	5.1	0	0	5.1	5.1						
Ref. No.	IC8501 (SCM-60)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	5.3	5.5	5.4	0	0	0	5.5	0	5.3	5.5	0	5.4	0	5.4	5.5	4.4	0	0	5.5	5.4
REC	5.2	5.4	5.4	0	0	0	0	0	5.2	5.4	0	5.4	0	0	5.4	4.4	0	0	0	5.4
Ref. No.	IC8501 (SCM-60)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	5.4	0	2.2	0	4.7	0	0	5.4	5.4	5.4	0	0	0	5.4	5.4	5.4	5.4	2.6	2.6	0
REC	5.4	0	2.2	0	4.7	0	0	5.4	5.4	5.4	0	0	5.1	0.3	0	0	0.3	2.6	2.6	0
Ref. No.	IC8501 (SCM-60)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	2.6	2.4	0	0	0	0	0	0	0.3	0.3	0.3	0.3	4.7	5.0	0	0	0.3	0.3	0.3	2.7
REC	0	0	0	5.4	5.4	5.4	5.4	5.4	5.4	5.4	4.9	0	4.7	5.0	0	0	0	0	0	2.7
Ref. No.	IC8501 (SCM-60)																			
Mode	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80
STOP	2.7	0	2.7	0	2.7	0	5.4	0	0	5.4	3.7	0	0	0.1	4.5	4.5	1.1	0	2.7	2.7
REC	2.7	0	2.7	0	2.7	0	5.4	0	0	5.4	3.7	0	0	2.3	2.3	1.1	0	0	2.7	2.7
Ref. No.	IC8501 (SCM-60)																			
Mode	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
STOP	1.1	1.1	0	5.4	0	0	0	0	0	2.9	0	5.4	5.4	5.4	5.4	0	0	2.5	2.6	0
REC	1.2	1.2	0	5.4	0	0	0	0	0	2.9	0	5.4	5.4	5.4	5.4	0	0	2.5	2.6	0
Ref. No.	IC8501 (SCM-60)																			
Mode	101	102	103	104	105	106	107	108	109	110	111	112	113	114	115	116	117	118	119	120
STOP	2.7	4.0	0	5.1	0	0	0	0	5.4	5.4	5.4	0	0	5.4	0	0	5.4	5.4	0	0
REC	2.7	4.0	0	5.1	0	0	0	0	0	0	0	0	0	0	0	0	5.4	0	0	0
Ref. No.	IC8501 (SCM-60)								IC8502 (SCM-60)											
Mode	121	122	123	124	125	126	127	128	1	2	3	4	5	6	7	8				
STOP	0	0	0	0	0	5.4	0	0	2.7	2.7	2.7	0	0	0	0	5.4				
REC	0	0	5.4	0	0	0	5.4	0	2.7	2.7	2.7	0	0	0	0	5.4				
Ref. No.	IC8503 (SCM-60)														IC8504 (SCM-60)					
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	G	V	O			
STOP	5.1	5.4	0	2.7	0	2.5	0	2.7	2.7	0.6	2.7	2.7	5.4	5.4	0	4.7	4.7			
REC	5.1	5.4	0	2.7	0	2.5	0	2.7	2.7	0.6	2.7	2.7	5.4	5.4	0	4.7	4.7			
Ref. No.	IC8506 (SCM-60)																			
Mode	1	2	3	4	5	6	7	8												
STOP	4.0	0.9	0.6	0	0	5.4	0	5.4												
REC	4.0	0.9	0.6	0	0	5.4	0	5.4												
Ref. No.	Q8101 (SCM-58)				Q8102 (SCM-58)				Q8103 (SCM-58)				Q8201 (SCM-59)				Q8202 (SCM-59)			
Mode	E	C	B		E	C	B		E	C	B		E	C	B		E	C	B	
STOP	9.0	11.5	9.6		9.6	0	9.0	2.3	2.4	0		-1.0	4.7	-0.4	0.9	4.7	1.5	-0.7	9.2	-0.1
REC	9.0	11.5	9.6		9.6	0	9.0	2.3	2.4	0		-1.0	4.7	-0.4	0.9	4.7	1.5	-0.7	9.2	-0.1

Ref. No. Mode	Q8204 (SCM-59)			Q8205 (SCM-59)			Q8206 (SCM-59)			Q8207 (SCM-59)									
	E	C	B	E	C	B	E	C	B	E	C	B							
STOP	3.4	9.2	4.0	-0.7	9.2	-0.1	3.4	9.2	4.0	-1.0	4.7	-0.4							
REC	3.4	9.2	4.0	-0.7	9.2	-0.1	3.4	9.2	4.0	-1.0	4.7	-0.4							
Ref. No. Mode	QR8101 (SCM-58)			QR8102 (SCM-64)			QR8501 (SCM-60)			QR8502 (SCM-60)			QR8503 (SCM-60)						
	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B				
STOP	0	5.0	0	0	0	0	0	0.1	4.1	0	5.4	0	0	2.3	0				
REC	0	5.0	0	0	0	0	0	5.4	0	0	5.4	0	0	2.3	0				

TBC (2) C.B.A.

Ref. No.	IC8601 (SCM-65)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	3.8	4.3	4.5	5.2	5.2	4.5	4.5	4.5	4.3	9.0	5.1	0	0	8.6	8.9	0.4	6.7	2.4	5.2	0
REC	4.0	4.5	4.6	5.4	5.3	4.6	4.6	4.6	4.4	9.2	5.3	0	0	8.8	9.1	0.4	6.9	2.5	5.3	0
Ref. No.	IC8602 (SCM-65)(SCM-66)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	0.1	0.1	0	4.2	0	5.1	0	0	4.0	0	-0.5	0	-5.0	5.1						
REC	0.1	0.1	0	4.4	0	5.1	0	0	4.0	0	-0.5	0	-5.0	5.1						
Ref. No.	IC8603 (SCM-65)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	5.1	5.1	5.1	5.1	0	0	5.1	0	0	5.1	5.0	5.1	0	0	5.1	5.1				
REC	5.1	5.1	5.1	5.1	0	0	5.1	0	0	5.1	5.0	5.1	0	0	5.1	5.1				
Ref. No.	IC8604 (SCM-65)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	5.1	5.0	5.1	0	0	5.0	0	0	5.1	5.0	5.1	0	0	5.1	5.1				
REC	0	5.3	5.1	5.3	0	0	5.3	0	0	5.3	5.2	5.4	0	0	5.3	5.3				
Ref. No.	IC8605 (SCM-65)																			
Mode	1	2	3	4	5	6	7	8												
STOP	0	0	0	-5.0	0	0	0	11.6												
REC	0	0	0	-5.0	0	0	0	11.6												
Ref. No.	IC8606 (SCM-65)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	5.1	4.9	4.9	5.1	2.4	0	3.2	0	0	1.3	4.9	1.8	0	0	4.9	5.1				
REC	5.2	5.0	5.0	5.2	2.3	0	3.2	0	0	1.2	4.9	1.7	0	0	4.9	5.1				
Ref. No.	IC8607 (SCM-65)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	0.3	5.1	0	5.1	5.1	0	0	5.0	0.2	0	5.1	5.1	0	5.1						
REC	0.4	5.1	0	5.1	5.1	0	0	5.0	0.2	0	5.3	5.3	0	5.3						
Ref. No.	IC8608 (SCM-65)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	0	2.7	2.7	5.1	2.5	0.4	0	1.9	0	3.8	0	0	0	5.1						
REC	0	2.8	2.8	5.2	2.5	0.5	0	1.9	0	3.8	0	0	0	5.1						
Ref. No.	IC8609 (SCM-65)								IC8613 (SCM-65)											
Mode	1	2	3	4	5	6	7	8	1	2	3									
STOP	2.3	2.7	2.7	-5.0	0	0	0	4.9	9.1	0	11.6									
REC	2.3	2.7	2.7	-5.0	0	0	0	4.9	9.1	0	11.6									
Ref. No.	IC8671 (SCM-66)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0	0	0	0	0	-5.0	0	0	0	0	0	0	0	0	4.9				
REC	0	0	0	0	0	0	-5.0	0	0	0	0	0	0	0	0	4.9				
Ref. No.	IC8672 (SCM-66)																			
Mode	1	2	3	4	5	6	7	8												
STOP	0	0	0	-5.0	0	0.4	0	9.1												
REC	0	0	0	-5.0	0	0.4	0	9.1												
Ref. No.	IC8673 (SCM-66)														IC8674 (SCM-66)					
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	1	2	3			
STOP	0	0	0	2.2	5.1	5.1	0	3.8	2.2	0	2.2	1.9	-5.0	5.1	9.2	0	11.6			
REC	0	0	0	2.2	5.1	5.1	0	3.8	2.1	0	2.2	1.9	-5.0	5.1	9.2	0	11.6			
Ref. No.	IC8701 (SCM-67)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	5.1	0	5.1	0	0	0	0	0	0	3.4	3.4	0	0	0	0	2.6	5.1	0	2.6	5.1
REC	5.1	0	5.1	0	0	0	0	0	0	3.4	3.4	0	0	0	0	2.6	5.1	0	2.6	5.1
Ref. No.	IC8701 (SCM-67)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	2.6	5.1	0	5.1	0.5	0	0	0	0	0	5.1	2.5	5.1	5.1	0	5.1	0	0	0	5.1
REC	2.6	5.1	0	5.1	0.5	0	0	0	0	0	5.1	2.5	5.1	5.1	0	5.1	0	0	0	5.1
Ref. No.	IC8701 (SCM-67)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	2.6	5.1	0	0	0	1.4	2.7	2.5	0	2.7	5.1	2.5	2.5	2.4	2.5	0	2.6	2.6	5.1	0
REC	2.5	5.1	0	0	0	1.4	2.7	2.5	0	2.7	5.1	2.5	2.5	2.4	2.5	0	2.6	2.6	5.1	0

Ref. No.	IC8701 (SCM-67)																			
Mode	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80
STOP	2.5	5.1	5.1	5.1	5.1	5.1	2.4	0	4.2	5.1	0	0	5.1	1.8	1.8	3.8	0	0	3.4	2.6
REC	2.5	5.1	5.1	5.1	5.1	5.1	2.4	0	4.2	5.1	0	0	5.1	1.8	1.8	3.8	0	0	3.4	2.6
Ref. No.	IC8701 (SCM-67)																			
Mode	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
STOP	2.6	5.1	5.1	0.4	5.1	0	0	0	0	5.1	5.1	0	5.1	0	0	5.1	3.4	5.1	0	0
REC	2.6	5.1	5.1	0.4	5.1	0	0	0	0	5.1	5.1	5.1	0	5.1	0	5.1	3.4	5.1	0	0
Ref. No.	IC8701 (SCM-67)																			
Mode	101	102	103	104	105	106	107	108	109	110	111	112	113	114	115	116	117	118	119	120
STOP	5.1	0.8	5.1	0	0	5.1	0	5.1	0	0	0	0	0.4	0.4	2.6	0.2	5.1	0.2	0	0.1
REC	5.1	0.8	5.1	0	0	5.1	5.1	5.1	0	0	0	0	0.4	2.6	0.2	1.0	0.4	0.2	0	0.1
Ref. No.	IC8701 (SCM-67)																			
Mode	121	122	123	124	125	126	127	128	129	130	131	132	133	134	135	136	137	138	139	140
STOP	1.0	1.2	5.1	5.1	0.2	0.2	5.1	5.1	5.1	3.4	5.1	0	5.1	0	5.1	5.1	5.1	0	5.1	5.1
REC	1.0	1.2	0.8	5.1	0.2	5.1	5.1	5.1	5.1	3.4	5.1	0	5.1	0	5.1	5.1	0	0	5.1	5.1
Ref. No.	IC8701 (SCM-67)										IC8702 (SCM-67)									
Mode	141	142	143	144	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
STOP	5.1	5.1	0	0	5.2	5.2	5.2	5.2	0	0	5.2	0	0	5.2	5.2	5.2	0	0	3.6	5.2
REC	5.1	5.1	0	0	5.1	5.1	5.1	5.1	0	0	5.1	0	0	5.1	5.1	5.1	0	0	3.6	5.1
Ref. No.	IC8703 (SCM-67)										IC8704 (SCM-67)									
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	1	2	3	4	5	
STOP	1.0	4.1	2.5	2.7	2.5	2.5	0	2.6	2.6	2.4	2.7	2.5	2.5	5.1	0.2	0.2	0	0.1	5.2	
REC	1.0	4.1	2.5	2.6	2.5	2.5	0	2.6	2.6	2.4	2.6	2.5	2.5	5.1	0.2	0.2	0	0.1	5.1	
Ref. No.	IC8705 (SCM-67)								IC8706 (SCM-67)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	0	0	0	-5.1	0	0	0	9.2	0.4	4.9	0.4	0	4.5	0	4.5	4.9				
REC	0	0	0	-5.1	0	0	0	9.1	0.4	4.9	0.4	0	4.5	0	4.5	4.9				
Ref. No.	IC8801 (SCM-68)								IC8802 (SCM-68)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	0	0	0	-4.8	0	0	0.1	4.8	2.7	3.4	2.1	0	2.1	3.4	2.7	4.8				
REC	0	0	0	-4.8	0	0	0.1	4.8	2.7	3.4	2.1	0	2.1	3.4	2.8	4.8				
Ref. No.	IC8803 (SCM-68)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0.2	5.3	5.2	0.2	0	4.9	0	0.1	5.3	5.3	5.1	0.1	0	5.1	5.3				
REC	0	0.2	5.3	5.2	0.2	0	4.9	0	0.1	5.3	5.3	5.1	0.1	0	5.1	5.3				
Ref. No.	IC8804 (SCM-68)								IC8805 (SCM-68)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	0.3	0	0	-4.8	0	0	-0.5	-4.8	0.5	0	0	-4.8	0	0	0	4.8				
REC	0.4	0	0	-4.8	0	0	0	4.8	0.5	0	0	-4.8	0	0	0	4.8				
Ref. No.	IC8806 (SCM-68)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	2.2	1.7	2.8	2.9	3.5	2.9	4.8	2.2	1.7	2.9	0	1.8	1.4	1.4	4.8	4.1	5.1	3.0	0	3.5
REC	2.2	1.7	2.8	2.9	3.5	2.9	4.8	2.2	1.7	2.9	0	1.8	1.4	1.4	4.8	4.1	5.1	5.0	0	3.5
Ref. No.	IC8806 (SCM-68)					IC8807 (SCM-68)														
Mode	21	22	23	24	1	2	3	4	5											
STOP	2.9	2.8	1.7	2.2	0	0.1	0	5.1	5.3											
REC	3.2	2.8	1.7	2.2	0	0.1	0	5.1	5.3											
Ref. No.	IC8808 (SCM-68)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0.1	-2.9	-3.1	-3.0	0	-4.9	0	2.6	1.0	4.8	0	0	0	0	4.8				
REC	0	0.1	-2.9	-3.1	-3.0	0	-4.9	0	2.6	1.0	4.8	0	0	0	0	4.8				
Ref. No.	IC8809 (SCM-68)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	0.2	5.1	1.0	0.5	5.3	0	0	0.2	0	0	5.1	4.3	1.0	5.3						
REC	0.2	5.1	1.0	0.4	5.3	0	0	0.2	0	0	5.1	4.3	1.0	5.3						
Ref. No.	IC8810 (SCM-68)								IC8811 (SCM-68)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5							
STOP	3.5	1.0	1.0	-5.0	0	0	0	11.6	0.3	0	0	0.1	4.8							
REC	3.5	1.0	1.0	-5.0	0	0	0	11.6	0.3	0	0	0.1	4.8							

Ref. No.	IC8812 (SCM-68)																	
Mode	1	2	3	4	5	6	7	8										
STOP	0.1	0.1	0.1	-5.0	0.2	0.2	0.2	11.6										
REC	0.1	0.1	0.1	-5.0	0.2	0.2	0.2	11.6										
Ref. No.	Q8671 (SCM-66)			Q8672 (SCM-66)			Q8673 (SCM-66)			Q8701 (SCM-67)			Q8801 (SCM-68)			Q8802 (SCM-68)		
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B
STOP	3.2	0	2.6	4.8	7.0	9.2	7.9	4.8	9.1	-0.4	4.9	0	0.7	4.8	1.3	-0.6	4.8	0.1
REC	3.2	0	2.6	4.8	7.0	9.2	7.9	4.8	9.1	-0.4	5.0	0	0.7	4.8	1.3	-0.6	4.8	0.1
Ref. No.	Q8803 (SCM-68)			Q8804 (SCM-68)			Q8805 (SCM-68)			Q8806 (SCM-68)			Q8808 (SCM-68)			Q8809 (SCM-68)		
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B
STOP	-0.6	4.8	0	0	-4.8	-0.6	-0.4	4.8	0.2	-0.1	4.8	0.5	-0.5	4.9	0.1	-0.5	4.9	0.1
REC	-0.6	4.8	0	0	-4.8	-0.6	-0.4	4.8	0.2	-0.1	4.8	0.5	-0.5	4.9	0.1	-0.5	4.9	0.1
Ref. No.	Q8810 (SCM-68)			Q8811 (SCM-68)			Q8812 (SCM-68)			Q8813 (SCM-68)			Q8814 (SCM-68)			Q8815 (SCM-68)		
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B
STOP	0.8	-1.8	0	0.2	4.9	0.8	0.8	-1.8	0	0.2	4.9	0.8	-0.4	4.8	0	-0.3	4.8	0
REC	0.8	-1.8	0	-0.5	4.9	0.1	0.8	-1.8	0	0.2	4.9	0.8	-0.4	4.9	0	-0.3	4.9	0
Ref. No.	Q8816 (SCM-68)			Q8817 (SCM-68)			Q8818 (SCM-68)			Q8819 (SCM-68)			Q8820 (SCM-68)			Q8821 (SCM-68)		
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B
STOP	-0.2	-4.9	0	0.6	2.7	0.1	0.2	-4.9	-0.1	0.1	-4.9	0	0.5	2.7	0.1	0.1	-4.9	-0.1
REC	-0.2	-4.9	0	0.6	2.7	0.1	0.2	-0.1	-4.9	0.1	-4.9	0	0.5	2.7	0.1	0.1	-4.9	-0.1
Ref. No.	Q8822 (SCM-68)			Q8823 (SCM-68)			Q8824 (SCM-68)			Q8825 (SCM-68)			Q8827 (SCM-68)			Q8828 (SCM-68)		
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B
STOP	0.6	2.7	0.3	0.4	-4.9	0.1	2.6	11.6	3.3	0.3	10.6	0.9	0.4	11.6	1.0	0.1	11.6	-0.1
REC	0.6	2.7	0.3	0.4	-4.9	0.1	2.7	11.6	3.3	0.3	11.6	0.9	0.4	11.6	1.0	0.1	11.6	-0.1
Ref. No.	Q8832 (SCM-68)																	
Mode	1	2	3	4	5													
STOP	0	0	5.1	0	5.1													
REC	0	0	5.1	0	5.1													

AUDIO (1) C.B.A.

Ref. No.	IC40001 (SCM-37)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	4.8	4.9	4.9	4.9	4.9	10.3	4.9	4.9	4.9	9.8	4.8	4.9	-0.1	-0.2	8.9				
REC	0	4.8	4.9	4.9	4.9	4.9	10.3	4.9	4.9	4.9	9.8	4.8	4.9	0	0	8.9				
Ref. No.	IC40002 (SCM-37)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	5.3	5.3	5.4	5.3	5.3	5.3	5.1	0	0	5.3	5.4	5.3	0	8.1	7.9	10.6				
REC	5.3	5.3	5.4	5.3	5.2	5.3	5.1	0	0	5.3	5.4	5.3	0	8.1	7.9	10.6				
Ref. No.	IC40003 (SCM-37)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	4.8	4.9	4.9	4.9	4.9	10.3	4.9	4.9	4.9	9.8	4.9	4.9	-0.1	-0.1	8.9				
REC	0	4.8	4.9	4.9	4.9	4.9	10.3	4.9	4.9	4.9	9.8	4.9	4.9	0	0	8.9				
Ref. No.	IC40004 (SCM-37)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	5.3	5.3	5.4	5.3	5.3	5.3	5.1	0	0	5.3	5.4	5.3	0	8.1	7.9	0				
REC	5.3	5.3	5.4	5.3	5.2	5.3	5.1	0	0	5.3	5.4	5.3	0	8.1	7.9	10.6				
Ref. No.	IC40005 (SCM-37)								IC40006 (SCM-38)				IC40007 (SCM-38)							
Mode	1	2	3	4	5	6	7	8	1	2	3	1	2	3						
STOP	0.1	0	0	-12.1	0	0	0	0.1	11.5	4.7	4.7	0	5.1	5.1	0					
REC	0	0	0	-12.1	0	0	0	0	11.5	4.7	4.7	0	5.1	5.1	0					
Ref. No.	IC40008 (SCM-38)																			
Mode	1	2	3	4	5	6	7													
STOP	2.5	0.6	0.1	0	1.1	4.8	10.0													
REC	2.5	0.7	0.1	0	1.1	4.8	9.8													
Ref. No.	IC40009 (SCM-38)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0.5	0	0	0	0	0	-6.2	0	0	5.5	5.5	0	0.1	0	0	6.0				
REC	0	0	0	0	0	0	-6.2	0	0	0.1	0.1	0	0	0	0	5.9				
Ref. No.	IC40010 (SCM-38)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0	0	5.1	0	0	0	0	0	5.2	5.1	4.2	0	0.5	5.1	5.2				
REC	0	5.1	5.1	5.1	0	5.1	5.1	0	5.1	5.1	5.0	4.3	0	0.4	5.1	5.1				
Ref. No.	IC40011 (SCM-38)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	5.1	0	0	0	0	5.2	0	0	0	5.2	5.1	4.2	0	0	0	5.2				
REC	5.1	0	0	5.1	0	5.1	5.1	0	5.1	5.1	5.0	4.3	0	5.1	0	5.1				
Ref. No.	IC40012 (SCM-38)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	5.1	0	0	0	0	5.2	0	0	0.1	5.2	5.1	4.3	0	0	0	5.2				
REC	5.1	5.1	0	0	0	5.1	0	0	0.1	5.1	5.0	4.3	0	5.1	0	5.1				
Ref. No.	IC40013 (SCM-38)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0	0	5.1	0	0	0	0	0	11.6	11.1	11.6	0	11.6	11.1	11.6				
REC	5.1	5.1	0	5.1	5.1	5.1	0	0	0	11.5	0	0	0	11.5	0	0				
Ref. No.	IC40014 (SCM-38)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0	0	0	0	5.2	5.2	0	0	0	0	9.9	9.9	11.7	3.7	10.3				
REC	0	5.1	5.1	0	0	5.1	5.1	0	0	0	0	9.8	9.7	0	0.1	10.2				
Ref. No.	IC40015 (SCM-38)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0	0	0	0	0	5.2	0	0	0	5.5	11.6	0.7	11.3	11.6	0.1				
REC	0	0	0	0	0	5.1	5.1	0	0.1	0	0.1	11.5	0.7	11.2	11.5	0.3				
Ref. No.	IC40016 (SCM-39)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	5.6	5.6	5.6	5.4	0	0	0	5.6	5.4	5.6	5.6	9.8	9.8	10.9						
REC	5.6	5.6	5.6	5.4	0	0	0	5.6	5.4	5.6	5.6	9.8	9.8	10.8						
Ref. No.	IC40017 (SCM-39)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	5.4	5.6	5.5	5.7	5.7	5.6	0	0	0	0	0	5.6	5.4	5.6	5.6	10.9				
REC	5.4	5.6	5.5	5.6	5.6	0	0	0	0	0	0	5.6	5.4	5.6	5.6	10.8				

Ref. No.	IC40018 (SCM-39)								IC40019 (SCM-39)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	5.7	5.7	5.6	0	5.6	5.7	5.7	10.9	5.7	5.7	5.6	0	5.6	5.7	5.7	10.9				
REC	5.6	5.6	5.6	0	5.6	5.6	5.6	10.8	5.6	5.6	5.6	0	5.6	5.6	5.6	10.8				
Ref. No.	IC40020 (SCM-39)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	10.8	4.8	4.3	5.5	10.7	0	0	2.7	0	2.7	0	0	4.3	4.8						
REC	10.8	4.8	4.2	5.5	10.6	0	0	2.7	0	2.7	0	0	4.3	4.8						
Ref. No.	IC40021 (SCM-38)																			
Mode	1	2	3	4	5															
STOP	4.8	4.7	0	5.1	5.2															
REC	4.8	4.7	0	5.1	5.1															
Ref. No.	Q40001 (SCM-37)			Q40002 (SCM-37)			Q40003 (SCM-37)			Q40004 (SCM-37)			Q40005 (SCM-37)			Q40006 (SCM-37)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	0	0	0	0.7	0	0	0.7	9.9	9.9	9.2	0	0	0	0	0.1	0		
REC	0	0	0.7	-5.4	0	-24.2	-5.2	0	-24.3	9.9	-25.6	9.9	0	0	0	0	0.3	0		
Ref. No.	Q40007 (SCM-37)			Q40008 (SCM-37)			Q40009 (SCM-37)			Q40010 (SCM-37)			Q40011 (SCM-37)			Q40012 (SCM-37)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	5.3	0	4.7	10.6	11.6	11.3	0	0	0	11.6	0	11.6	0.2	0	0	11.6	0	11.6		
REC	5.3	0	4.7	10.6	11.5	11.3	0.8	10.9	1.3	11.1	11.0	10.4	-4.1	1.2	-5.7	11.5	-6.1	11.5		
Ref. No.	Q40013 (SCM-37)			Q40014 (SCM-37)			Q40015 (SCM-37)			Q40016 (SCM-37)			Q40017 (SCM-37)			Q40018 (SCM-37)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0.2	0	0	0	0.3	0.3	0	0.3	0.3	11.6	0.3	11.6	11.6	0	11.6	0	0	0		
REC	-4.1	0	-5.7	0.3	0.1	11.2	0.3	11.2	0.1	11.3	11.2	10.6	11.0	10.8	10.3	0.6	10.7	1.0		
Ref. No.	Q40019 (SCM-37)			Q40020 (SCM-37)			Q40021 (SCM-37)			Q40022 (SCM-37)			Q40023 (SCM-37)			Q40024 (SCM-37)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	-0.2	0	0	0	0	-0.1	0	0	0	0.2	7.8	0.7	0.2	7.8	0.7	0	0	0		
REC	10.8	10.8	10.1	0	0	0.4	0	0	0.4	0.2	7.7	0.7	0.2	7.7	0.7	0	0	-0.1		
Ref. No.	Q40025 (SCM-37)			Q40026 (SCM-37)			Q40027 (SCM-37)			Q40028 (SCM-37)			Q40029 (SCM-37)			Q40030 (SCM-37)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	0	0	0	0.7	9.8	9.8	9.1	0	0	0.7	0	0	0	0	0.1	0		
REC	0	0	0.7	-3.7	0	-22.7	9.8	-22.5	9.8	-3.7	0	-22.3	0	0	0	0	0.2	0		
Ref. No.	Q40031 (SCM-37)			Q40032 (SCM-37)			Q40033 (SCM-37)			Q40034 (SCM-37)			Q40035 (SCM-37)			Q40036 (SCM-37)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	5.3	0	4.7	10.6	11.6	11.3	0.3	0	0	11.6	0	11.6	11.6	0	11.6	0	0	0		
REC	5.3	0	4.6	10.6	11.6	11.3	-4.3	0.7	-5.9	11.5	-5.8	11.5	11.1	11.0	10.4	0.8	10.9	1.3		
Ref. No.	Q40037 (SCM-37)			Q40038 (SCM-37)			Q40039 (SCM-37)			Q40040 (SCM-37)			Q40041 (SCM-37)			Q40042 (SCM-37)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	-0.1	0	0	0	0	-0.1	0	0	-0.1	11.6	0	11.6	0.2	7.7	0.7	0.2	7.7	0.7		
REC	10.8	10.8	10.1	0	0	0.3	0	0	0.3	11.0	10.8	10.2	0.2	7.7	0.7	0.2	7.7	0.7		
Ref. No.	Q40043 (SCM-37)			Q40044 (SCM-37)			Q40045 (SCM-38)			Q40046 (SCM-38)			Q40047 (SCM-39)			Q40048 (SCM-39)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	-0.1	0.3	0	0	5.1	-0.1	5.0	11.6	0	11.6	10.9	11.6	11.6	4.9	10.9	5.5		
REC	0	0	-0.1	-4.3	0	-5.8	5.1	-0.2	5.0	11.5	0	11.5	10.9	11.6	11.6	4.8	10.8	5.5		
Ref. No.	Q40049 (SCM-37)																			
Mode	E	C	B																	
STOP	0	0	0																	
REC	0.7	10.7	1.0																	
Ref. No.	QR40001 (SCM-37)			QR40002 (SCM-37)			QR40003 (SCM-37)			QR40004 (SCM-37)			QR40005 (SCM-37)			QR40006 (SCM-37)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	6.9	0	6.9	0	0	0	6.9	9.8	0	10.9	0	9.5	0	0	0	0		
REC	0	5.3	0	0	0	9.2	0	9.8	0	9.8	9.8	4.7	0	0	9.8	0	0	9.8		
Ref. No.	QR40007 (SCM-37)			QR40008 (SCM-37)			QR40009 (SCM-37)			QR40010 (SCM-37)			QR40011 (SCM-37)			QR40012 (SCM-37)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	3.9	11.6	11.6	0	11.6	-0.1	11.6	11.6	0	11.6	0	0	0	0	0	0		
REC	0	0	3.8	11.5	11.5	0	11.5	0	11.5	11.5	0	11.5	0	0	0	0	0	0		
Ref. No.	QR40013 (SCM-37)			QR40014 (SCM-37)			QR40015 (SCM-37)			QR40016 (SCM-37)			QR40017 (SCM-37)			QR40018 (SCM-37)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	0.9	0	0	0.7	0	0	6.9	0	6.9	0	0	0	6.9	9.8	0	10.9		
REC	0	0	0.3	0	0	0.6	0	5.2	0	0	0	9.2	0	9.8	0	9.8	9.8	4.9		

Ref. No.	QR40019 (SCM-37)			QR40020 (SCM-37)			QR40021 (SCM-37)			QR40022 (SCM-37)			QR40023 (SCM-37)			QR40024 (SCM-37)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	9.5	0	11.6	11.6	0	11.6	0	11.5	11.6	0	11.5	0	0	0	0	0	0		
REC	0	0	9.8	11.5	11.5	0	11.5	0	11.5	11.5	0	11.5	0	0	0	0	0	0		
Ref. No.	QR40025 (SCM-37)			QR40026 (SCM-37)			QR40027 (SCM-37)			QR40028 (SCM-37)			QR40029 (SCM-39)			QR40030 (SCM-39)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	11.6	0.7	0	0	0.7	0	0	0.9	0	0	0	9.9	0	9.8	9.9	0	9.8		
REC	0	11.5	0.7	0	0	0.6	0	0	0	0	0	9.8	9.9	0	9.8	9.8	0	9.7		
Ref. No.	QR40031 (SCM-39)			QR40032 (SCM-39)																
Mode	E	C	B	E	C	B														
STOP	9.9	0	9.8	9.9	0	9.8														
REC	9.8	0	9.8	9.9	0	9.8														

AUDIO (2) C.B.A.

Ref. No.	IC41001 (SCM-40)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	4.6	4.6	4.6	4.6	0	4.6	4.6	4.6	4.6	0.2	4.6	4.6	4.6	0	4.6	4.5	4.6	4.6	2.5	0
REC	4.6	4.6	4.6	4.6	0	4.6	4.6	4.6	4.6	0.2	4.6	4.6	4.6	0	4.6	2.5	4.6	4.6	2.5	0
Ref. No.	IC41001 (SCM-40)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	2.5	2.5	5.0	2.6	0	3.2	5.0	5.0	3.0	4.5	0	4.5	0	0	2.5	2.7	3.4	0	3.2	0
REC	2.5	2.5	5.0	2.6	0	3.2	5.0	5.0	3.0	4.5	0	4.5	0	0	2.5	2.7	3.4	0	3.2	0
Ref. No.	IC41001 (SCM-40)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	2.6	5.0	2.5	2.5	0	2.5	4.6	4.6	4.5	4.6	0	4.6	4.6	4.6	0.2	4.6	4.6	4.6	4.6	0
REC	2.6	5.0	2.5	2.5	0	2.5	4.6	4.6	4.5	4.6	0	4.6	4.6	4.6	0.2	4.6	4.6	4.6	4.6	0
Ref. No.	IC41001 (SCM-40)																			
Mode	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80
STOP	4.6	4.6	5.9	5.9	0	5.9	0.1	5.9	5.9	0.4	5.2	5.3	0	0	0.1	9.0	11.6	9.0	4.6	5.0
REC	4.6	4.6	5.9	5.9	0	5.9	-0.1	5.9	5.9	0.5	5.2	5.3	0	0	0.1	8.9	11.5	9.0	4.6	5.0
Ref. No.	IC41002 (SCM-40)								IC41003 (SCM-40)								IC41004 (SCM-41)			
Mode	1	2	3	1	2	3	4	5	6	7	1	2	3	4	5	6	7	8		
STOP	5.0	0	11.6	0	5.0	2.5	0	1.4	2.0	0	0	0	0	-6.3	0.8	0.7	5.8	6.3		
REC	5.0	0	11.5	0	5.0	2.5	0	1.4	2.0	0	0	0	0	-6.3	0.8	0.7	5.8	6.3		
Ref. No.	IC41005 (SCM-41)																			
Mode	1	2	3	4	5	6	7	8												
STOP	0	3.0	2.9	0	3.0	3.0	0	6.0												
REC	0.5	3.0	2.9	0	2.9	3.0	0	5.9												
Ref. No.	IC41006 (SCM-41)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0	0	0	0	0	-6.1	0	0	0	0	0	0	0	0	6.0				
REC	0	0	0	0	0	0	-6.1	0	0	0	0	0.5	0	0	0	5.9				
Ref. No.	IC41007 (SCM-41)								IC41008 (SCM-41)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	0	0	0	-6.3	0	0	0	6.3	0.1	0	0	-6.1	0	0	0	6.0				
REC	0	0	0	-6.3	0	0	0	6.3	0	0	0	-6.1	0	0	0.1	5.9				
Ref. No.	IC41009 (SCM-41)																			
Mode	1	2	3	4	5	6	7	8												
STOP	0	0	0	-6.1	0	0	0.1	6.0												
REC	0	0	0	-6.1	0	0	0.2	5.9												
Ref. No.	IC41010 (SCM-41)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0.1	0	0	0	0	0	-6.1	0	0	6.0	0	0.1	0	0.1	0.1	6.0				
REC	0	0	0	0	0	0	-6.1	0	0	5.9	0	0	0	0	0	5.9				
Ref. No.	IC41011 (SCM-41)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0	0	0	0	0	-6.3	0	6.3	0	0	0	0	0	0	6.3				
REC	0	0	0	0	0	0	-6.3	0	6.3	0	0	0	0	0	0	6.3				
Ref. No.	IC41012 (SCM-41)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0	0	0	0	0	-6.3	0	6.3	6.3	6.3	0	0	0	0	6.3				
REC	0	0	0	0	0	0	-6.3	0	6.3	6.3	6.3	0	0	0	0	6.3				
Ref. No.	IC41013 (SCM-41)																			
Mode	1	2	3	4	5	6	7	8												
STOP	0	0	0	-6.3	0	0	0	6.3												
REC	0	0	0	-6.3	0	0	0	6.3												
Ref. No.	IC41014 (SCM-42)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0	0	0	0	0	-6.3	0	0	6.3	6.3	0	0	0	0	6.3				
REC	0	0	0	0	0	0	-6.3	0	0	6.3	6.3	0	0	0	0	6.3				
Ref. No.	IC41015 (SCM-42)								IC41016 (SCM-44)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	0	0	0	-6.3	0	0	0	6.3	0	0	0	-11.5	0	0	0	10.9				
REC	0	0	0	-6.3	0	0	0	6.3	0	0	0	-11.5	0	0	0	10.8				

Ref. No.	IC41017 (SCM-44)																			
Mode	1	2	3	4	5	6	7	8												
STOP	0	0	0	-11.5	0	0	0	10.9												
REC	0	0	0	-11.5	0	0	0	10.8												
Ref. No.	Q41001 (SCM-40)			Q41002 (SCM-40)			Q41003 (SCM-40)			Q41004 (SCM-40)			Q41005 (SCM-40)					Q41006 (SCM-40)		
Mode	E	C	B	E	C	B	E	C	B	E	C	B	1	2	3	4	5	E	C	B
STOP	11.6	0	11.6	0	0	-0.3	0	0	-0.2	5.0	11.6	5.6	11.6	5.6	5.0	4.4	5.0	1.3	5.0	2.0
REC	11.6	11.4	10.7	0	0	-0.2	0	0	-0.2	4.9	11.5	5.5	11.5	5.5	4.9	4.3	4.9	2.4	5.0	3.0
Ref. No.	Q41007 (SCM-40)			Q41008 (SCM-41)			Q41009 (SCM-41)			Q41010 (SCM-41)			Q41011 (SCM-41)			Q41012 (SCM-41)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0.4	5.0	0.9	0	0	-0.4	6.3	10.9	6.9	-6.3	-12.2	-7.0	0	0	0.7	-0.6	6.0	0		
REC	0.4	5.0	0.9	0	0	-0.4	6.3	10.8	6.9	-6.3	-12.2	-7.0	0	0	0	-0.7	5.9	0		
Ref. No.	Q41013 (SCM-41)			Q41014 (SCM-41)			Q41015 (SCM-41)			Q41016 (SCM-42)			Q41017 (SCM-42)			Q41018 (SCM-42)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	-0.3	0	0	0.7	0	0	0.7	6.3	11.6	6.9	0	0	-0.1	0	0	-0.3		
REC	0	0	-0.4	0	0	0.7	0	0	0.7	6.3	11.5	6.9	0	0	-0.3	0	0	-0.2		
Ref. No.	Q41019 (SCM-43)			Q41020 (SCM-43)			Q41021 (SCM-43)			Q41022 (SCM-43)			Q41023 (SCM-43)			Q41024 (SCM-43)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
REC	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
Ref. No.	Q41025 (SCM-43)			Q41026 (SCM-43)			Q41027 (SCM-43)			Q41028 (SCM-43)			Q41029 (SCM-43)			Q41030 (SCM-43)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	0	0	0	0	0	0	0.8	0	0	0	0	0	0	0	0	0		
REC	0	0	0	0	0	0	0	0	0.3	0	0	0	0	0	0	0	0	0		
Ref. No.	Q41031 (SCM-43)			Q41032 (SCM-43)			Q41033 (SCM-43)			Q41034 (SCM-43)			Q41035 (SCM-43)			Q41036 (SCM-44)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	0	0	0	0	0	0	0.8	0	0	0	11.6	0	11.6	-11.5	-12.2	-12.2		
REC	0	0	0	0	0	0	0	0	0.3	0	0	0	11.5	0	11.5	-11.5	-12.2	-12.2		
Ref. No.	Q41037 (SCM-44)			Q41038 (SCM-44)			Q41039 (SCM-44)			Q41040 (SCM-44)			Q41041 (SCM-44)			Q41042 (SCM-44)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	-0.2	0	0	0.7	0	0	-11.5	0	0	0	0	0	0.7	0	0	-11.5		
REC	0	0	-0.2	0	0	0.7	0	0	-11.5	0	0	-0.1	0	0	0.7	0	0	-11.5		
Ref. No.	Q41043 (SCM-44)			Q41044 (SCM-44)			Q41045 (SCM-44)			Q41046 (SCM-44)			Q41047 (SCM-44)			Q41048 (SCM-44)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	-0.2	0	0	0.7	0	0	-11.5	0	0	-0.2	0	0	0.7	0	0	-11.5		
REC	0	0	-0.2	0	0	0.7	0	0	-11.5	0	0	0	0	0	0.7	0	0	-11.5		
Ref. No.	Q41049 (SCM-44)			Q41050 (SCM-43)			Q41051 (SCM-41)			Q41052 (SCM-41)			Q41053 (SCM-41)							
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B					
STOP	10.9	11.6	11.6	-12.2	0	-12.2	0	0.2	-0.4	0	0.1	-0.3	11.2	-0.2	11.4					
REC	10.8	11.5	11.5	-12.2	0	-12.2	0	0.2	-0.2	0	0.1	-0.1	11.1	-0.4	11.4					
Ref. No.	QR41002 (SCM-40)			QR41004 (SCM-40)			QR41005 (SCM-40)			QR41006 (SCM-41)			QR41007 (SCM-41)			QR41008 (SCM-43)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	5.0	-0.1	5.2	0	5.1	0	0	0	3.9	0	6.3	0	0	0.7	0	0	11.6	0		
REC	5.0	-0.1	5.1	0	5.1	0	0	0	3.8	0	6.3	0	0	0.7	0	0	11.5	0		
Ref. No.	QR41009 (SCM-43)			QR41010 (SCM-43)			QR41011 (SCM-43)			QR41012 (SCM-40)			QR41003 (SCM-40)							
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B					
STOP	11.6	-12.2	11.6	0	8.2	0	0	8.2	0	0	0	5.2	5.0	5.0	0					
REC	11.5	-12.2	11.5	0	2.8	3.2	0	2.8	3.2	0	0	5.1	5.0	5.0	0					

INTERFACE C.B.A.

Ref. No.	IC61001 (SCM-45)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	5.1	0.1	5.1	5.1	3.7	2.3	2.9	2.6	3.1	0	2.6	1.7	3.0	3.2	1.8	0.7	0.4	0.4	0.7	0.7
REC	5.1	0.1	5.1	5.1	3.7	2.3	2.9	2.6	3.1	0	2.6	1.7	3.0	3.2	1.8	0.7	0.4	0.4	0.7	0.7
Ref. No.	IC61001 (SCM-45)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	0.7	4.5	0	0.7	0	2.6	5.1	0	0	2.1	2.2	1.8	2.6	2.2	2.7	2.2	2.3	0	5.1	2.6
REC	0.7	4.5	0	0.7	0	2.6	5.1	0	0	2.1	2.2	1.8	2.7	2.1	2.2	2.1	2.1	0	0.1	2.6
Ref. No.	IC61001 (SCM-45)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	0.1	5.4	5.4	5.1	0	0	0	5.1	4.6	2.5	0	0	0	5.1	5.1	0	5.1	4.9	4.8	0
REC	0.1	5.4	5.4	5.1	0	0	0	5.1	4.6	2.5	0	0	0	5.1	5.1	0	5.1	4.9	4.8	0
Ref. No.	IC61001 (SCM-45)																			
Mode	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80
STOP	0	5.1	5.1	4.9	2.1	2.2	4.8	4.8	2.2	0	2.3	0	5.1	2.1	2.1	5.1	5.1	5.1	5.1	5.1
REC	0	5.1	5.1	4.9	2.1	2.2	4.8	4.8	2.2	0	2.3	0	5.1	2.1	2.1	5.1	5.1	5.0	5.1	5.1
Ref. No.	IC61002 (SCM-45)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0.7	2.2	4.1	2.6	2.0	2.5	2.7	2.7	2.5	2.4	2.1	2.6	1.9	0	2.9	1.9	2.5	2.0	2.0	0.6
REC	0.7	2.2	4.1	2.7	2.0	2.5	2.7	2.7	2.5	2.4	2.1	2.6	2.0	0	2.9	1.9	2.5	2.0	2.0	0.6
Ref. No.	IC61002 (SCM-45)																			
Mode	21	22	23	24	25	26	27	28												
STOP	0.9	2.1	0.9	4.3	3.4	0.9	0.8	5.1												
REC	1.0	2.1	1.0	4.3	3.4	0.9	0.8	5.1												
Ref. No.	IC61003 (SCM-45)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18		
STOP	4.1	2.5	2.7	2.7	2.5	2.4	5.1	0	5.1	5.1	5.1	2.1	2.6	1.9	2.9	2.0	2.6	5.1		
REC	4.1	2.5	2.7	2.7	2.5	2.4	5.1	0	5.1	5.1	5.1	2.1	2.6	1.9	2.9	2.0	2.6	5.1		
Ref. No.	IC61004 (SCM-45)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	0	0	0	0	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	2.2	5.1	0
REC	0	5.1	0	0	5.0	5.0	5.0	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	2.2	5.1	0
Ref. No.	IC61004 (SCM-45)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	0	0	5.1	0	0	0	5.1	0	0	0	0	0	0	5.1	5.1	5.1	5.1	5.1	5.1	2.7
REC	0	0	5.1	0	0	0	5.1	0	0	0	0	0	0	5.1	5.1	5.1	5.1	5.1	5.1	2.7
Ref. No.	IC61004 (SCM-45)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	5.1	0	0	0	5.1	0.6	2.5	5.1	0	5.1	5.2	5.1	5.1	5.1	0.3	2.4	2.5	0	5.1	5.1
REC	5.1	0	3.2	0.1	0	0.6	2.5	5.1	0	5.1	5.2	5.1	5.1	5.1	0.3	2.4	2.5	0	5.1	5.1
Ref. No.	IC61004 (SCM-45)																			
Mode	61	62	63	64	1	2	3	4	5	6	7	8								
STOP	5.1	5.1	0	5.1	2.5	5.1	3.1	0	5.1	3.3	5.1	5.1								
REC	5.1	0	0	5.1	2.6	5.3	3.3	0	5.4	0.4	5.3	5.3								
Ref. No.	IC61006 (SCM-45)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	5.0	5.0	0	5.1	0	5.1	0	5.1	0	5.0	5.1	5.1	5.0	0	5.1				
REC	0	9.1	8.8	0	5.9	0	5.1	0	5.1	0	5.0	5.1	5.1	6.1	0	6.5				
Ref. No.	IC61007 (SCM-45)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	4.9	4.8	5.1	2.2	2.1	2.5	0	4.9	2.1	4.8	5.0	4.9	2.2	5.1						
REC	4.8	4.8	5.1	2.2	2.1	2.5	0	4.9	2.1	4.8	5.0	4.9	2.2	5.1						
Ref. No.	IC61008 (SCM-46)(SCM-45)																			
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	3.4	0.1	5.1	0	4.1	0.6	5.1	5.1	4.9	4.7	0	0	5.1	0.4	0.2	5.1				
REC	3.4	0.1	5.1	0	4.1	0.6	5.1	5.1	4.9	4.7	0	0	5.1	0.4	0.2	5.1				
Ref. No.	IC61010 (SCM-45)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14						
STOP	1.0	5.1	5.1	0	5.1	0	0	5.1	1.0	5.1	0	0	5.1	5.1						
REC	1.1	5.0	5.0	0.1	5.0	0.1	0	5.0	1.1	5.1	0	0	5.1	5.1						

Ref. No.	IC61011 (SCM-45)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	0	0.1	0	4.5	2.6	2.5	0	5.1	3.3	0.3	5.1	0.4	0.4	0	5.1				
REC	0	0	0.1	0	4.5	2.6	2.5	0	5.1	3.3	0.3	5.1	0.4	0.4	0	5.1				
Ref. No.	IC61013 (SCM-46)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	3.0	2.8	1.7	2.6	2.9	2.6	2.6	2.1	0	2.2	2.7	2.7	3.2	2.7	1.7	3.0	3.2	0	5.1
REC	0	3.0	2.8	1.7	2.6	2.9	2.4	2.7	2.1	0	2.2	2.8	2.5	3.0	2.7	1.7	2.9	3.0	0	5.1
Ref. No.	IC61014 (SCM-46)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	2.5	1.8	1.9	2.2	2.1	2.5	1.6	2.1	1.7	0	3.9	3.9	3.9	3.9	4.6	4.6	4.6	4.6	4.8	5.1
REC	2.5	1.8	1.9	2.2	2.1	2.5	1.6	2.1	1.7	0	3.8	3.8	3.9	3.9	4.6	4.6	4.6	4.6	4.8	5.1
Ref. No.	IC61015 (SCM-46)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	0	0	0	0.2	0.2	4.9	2.5	4.8	0	4.8	2.5	4.9	0	0	0	0	0	0	5.1
REC	0	0	0	0	0	0	4.9	2.5	4.8	0	4.8	2.5	4.9	0	0	0	0	0	0	5.1
Ref. No.	IC61016 (SCM-46)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	2.4	2.9	2.6	0.4	1.6	0.7	5.1	0	5.1	5.1	4.9	5.1	5.1	5.1	5.0	5.1				
REC	2.4	2.9	2.6	0.4	1.6	0.7	5.1	0	5.1	5.1	4.9	5.1	5.1	5.1	5.0	5.1				
Ref. No.	IC61017 (SCM-48)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	0.4	5.1	5.1	5.1	5.1	0	0	0	0	5.1	2.2	2.6	2.0	3.0	1.9	2.5	2.0	2.0	0
REC	4.4	0	0	0	5.1	5.1	0	0	0	0	5.1	2.2	2.7	2.0	3.0	1.9	2.6	2.0	2.0	0
Ref. No.	IC61017 (SCM-48)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	0	5.1	0	0	5.1	5.1	0	0	5.0	0	2.4	2.4	0	0	5.1	5.1	5.1	0.2	0	0.2
REC	0	5.1	0	0	5.1	5.1	0	0	5.0	0	2.5	2.4	0	0	0.8	5.1	5.1	1.0	0.1	0.1
Ref. No.	IC61017 (SCM-48)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	0	0	5.1	0	0	0	5.1	0	0	0	0	0	5.1	0	0	0	0	5.1	5.1	5.1
REC	0	0	5.1	0	0	0	5.1	0	0	0	0	0	5.1	0	0	0	0	5.1	5.1	5.1
Ref. No.	IC61017 (SCM-48)																			
Mode	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80
STOP	5.1	0	0	0	0	0	4.8	0	0	5.1	0	0	0	0	4.6	5.1	5.1	5.1	5.1	0
REC	5.1	0	0	0	0	0	4.8	0	0	5.1	0	0	0	0	5.0	5.0	2.6	2.5	2.5	2.5
Ref. No.	IC61018 (SCM-47)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	2.2	2.6	2.0	3.0	1.9	2.5	2.0	2.0	2.4	2.5	5.1	5.0	0	0	-5.0	0	0	0.2	0	2.5
REC	2.1	2.6	2.0	3.0	1.9	2.5	2.0	2.0	2.4	2.5	5.1	5.0	0	0	-5.0	0	0	0.2	0	2.5
Ref. No.	IC61018 (SCM-47)																			
Mode	21	22	23	24																
STOP	0	4.9	5.1	5.1																
REC	0	4.9	5.1	5.1																
Ref. No.	IC61019 (SCM-47)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	2.2	2.6	2.0	3.0	1.9	2.5	2.0	2.0	2.4	2.5	5.1	5.0	0	0	-5.0	0	0	2.2	1.9	2.5
REC	2.1	2.6	2.0	2.9	1.9	2.5	2.0	2.0	2.4	2.5	5.1	5.0	0	0	-5.0	0	0	2.2	1.9	2.5
Ref. No.	IC61019 (SCM-47)																IC61020 (SCM-47)			
Mode	21	22	23	24	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
STOP	0	4.9	5.1	5.1	0	0	0	0.2	0.2	0	-5.0	0	0	0	0	0	0	0	0	4.9
REC	0	4.9	5.1	5.1	0	0	0	0	0	0	-4.9	0	0	0	0	0	0	0	0	4.9
Ref. No.	IC61021 (SCM-47)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	0	2.2	0	1.9	1.9	0	-5.0	0	0	0	0	0	0	0	2.2	4.9				
REC	0	2.2	0	1.9	2.0	0	-5.1	0	0	0.4	0.4	0	0	0	2.2	4.9				
Ref. No.	IC61022 (SCM-47)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
STOP	2.0	5.1	0	0	0	0	-5.0	0	0	0.2	0.2	5.1	2.1	5.1	5.1	4.9				
REC	1.6	5.1	0	0	0	0	-5.0	0	0	0.4	0.4	5.6	1.7	5.6	5.8	5.6				

Ref. No.	IC61023 (SCM-48)																				
Mode	1	2	3	4	5	6	7	8													
STOP	2.9	0	2.9	0	0	4.9	2.1	0													
REC	2.9	0	2.9	0	0	5.6	2.4	0													
Ref. No.	Q61001 (SCM-45)			Q61002 (SCM-48)			Q61003 (SCM-48)														
Mode	E	C	B	E	C	B	E	C	B												
STOP	5.1	5.0	4.3	2.0	4.9	2.6	2.0	4.9	2.6												
REC	5.1	5.0	4.3	2.0	4.9	2.6	2.0	4.9	2.6												

FRONT C.B.A.

Ref. No.	IC62001 (SCM-50)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	2.1	5.1	5.1	5.1	5.1	2.6	2.5	0	5.2	0	0	0	0	0	0	0	0	0	0	-28.7
REC	2.0	5.1	5.1	5.1	5.1	2.6	2.5	0	5.1	0	0	0	1.2	0	1.2	0	0	0	0	-9.1
Ref. No.	IC62001 (SCM-50)																			
Mode	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
STOP	-28.7	-28.7	-28.7	-28.7	-28.7	-28.7	-28.7	-28.7	-0.1	5.2	-29.0	0	0	0	0	0	0	-28.9	-28.9	-28.9
REC	-9.3	-8.7	-12.1	-13.8	-13.7	-16.1	-26.4	-18.0	-3.3	5.1	-26.7	0	0	0	0	0	0	-24.1	-24.0	-24.0
Ref. No.	IC62001 (SCM-50)																			
Mode	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60
STOP	-28.9	-28.9	-28.9	-28.9	-28.9	-28.9	-28.9	5.2	5.1	0	0	5.2	0	0	0	0	0	0	0	0
REC	-24.0	-24.0	-24.0	-24.0	-23.8	-23.8	-24.3	5.1	5.1	1.0	4.7	5.1	0	2.4	0	0	0	0	0	0
Ref. No.	IC62001 (SCM-50)																			
Mode	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80
STOP	0	0	0	0	0	0.2	0.1	0.1	0.1	5.1	5.1	0	5.1	0	0	0	0	0	0	0
REC	4.7	0	0	0	0	3.8	3.8	3.8	3.8	5.1	0	0	5.1	0	2.5	0	0	0	0	0
Ref. No.	IC62001 (SCM-50)																			
Mode	81	82	83	84	85	86	87	88	89	90	91	92	93	94						
STOP	0	0	0	0	5.2	5.2	0	5.1	5.1	5.1	5.1	0	0	0						
REC	0	5.1	3.8	5.1	5.1	5.1	0	5.1	5.1	5.1	5.1	0	0	0						
Ref. No.	IC62002 (SCM-50)										IC62003 (SCM-50)									
Mode	1	2	3	4	5	6	7	8	1	2	3									
STOP	0	2.5	0.2	0	4.6	2.5	5.1	5.1	5.1	5.1	0									
REC	0	2.5	0.2	0	4.6	2.5	5.1	5.1	5.1	5.1	0									
Ref. No.	Q62002 (SCM-51)			Q62003 (SCM-51)			Q62004 (SCM-51)			Q62005 (SCM-51)			Q62006 (SCM-51)			Q62007 (SCM-51)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	2.9	0.2	0	3.8	0	0	3.7	0	0	3.5	0	5.1	3.0	4.9	5.1	2.9	4.9		
REC	0	3.7	0	0	2.8	0.2	0	3.7	0	0	2.5	0.2	5.1	2.1	4.9	5.1	2.8	4.9		
Ref. No.	Q62008 (SCM-51)			Q62009 (SCM-51)																
Mode	E	C	B	E	C	B														
STOP	5.2	2.8	4.9	5.1	2.1	4.9														
REC	5.1	2.8	4.9	5.1	2.0	4.9														
Ref. No.	QR62001 (SCM-50)																			
Mode	E	C	B																	
STOP	0	0	4.6																	
REC	0	0	4.6																	

REAR AMP C.B.A.

Ref. No.	IC4001 (SCM-74)								IC4002 (SCM-74)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	0	0	0	-11.4	0	0	0	10.9	0	0	0	-11.4	0	0	0	10.9				
REC	0	0	0	-11.4	0	0	0	10.9	0	0	0	-11.4	0	0	0	10.9				
Ref. No.	IC4003 (SCM-74)								IC4004 (SCM-74)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	0	0	0	-11.4	0	0	0	10.9	0	0	0	-11.4	0	0	0	10.9				
REC	0	0	0	-11.4	0	0	0	10.9	0	0	0	-11.4	0	0	0	10.9				
Ref. No.	IC4005 (SCM-74)								IC4006 (SCM-74)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	0	0	0	-11.4	0	0	0	10.9	0	0	0	-11.4	0	0	0	10.9				
REC	0	0	0	-11.4	0	0	0	10.9	0	0	0	-11.4	0	0	0	10.9				
Ref. No.	IC4007 (SCM-74)								IC4008 (SCM-74)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	0	0	0	-11.4	0	0	0	10.9	0	0	0	-11.4	0	0	0	10.9				
REC	0	0	0	-11.5	0	0	0	10.9	0	0	0	-11.5	0	0	0	10.9				
Ref. No.	IC4014 (SCM-73)								IC4015 (SCM-73)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	0	0	0	-11.4	0	0	0	10.9	0	0	0	-11.4	0	0	0	10.9				
REC	0	0	0	-11.5	0	0	0	10.9	0	0	0	-11.5	0	0	0	10.9				
Ref. No.	IC4016 (SCM-73)								IC4017 (SCM-73)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	0	0	0	-11.4	0	0	0	10.9	0	0	0	-11.4	0	0	0	10.9				
REC	0	0	0	-11.5	0	0	0	10.9	0	0	0	-11.5	0	0	0	10.9				
Ref. No.	IC6601 (SCM-72)								IC6605 (SCM-72)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	7.2	3.6	7.1	0	0	11.5	6.4	0	0	0	0	-4.4	0	0	0	4.4				
REC	7.2	3.6	7.1	0	0	11.5	6.4	0	0	0	0	-4.4	0	0	0	4.4				
Ref. No.	IC6606 (SCM-72)								IC6607 (SCM-72)											
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8				
STOP	0	0	0	-4.4	0	0	0	4.4	0	0	0	-4.4	0	0	0	4.4				
REC	0	0	0	-4.4	0	0	0	4.4	0	0	0	-4.4	0	0	0	4.4				
Ref. No.	IC6608 (SCM-72)								IC6609 (SCM-72)								IC6610 (SCM-72)			
Mode	1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8	1	2	3	
STOP	3.2	0	0	-4.4	0	0	0	4.4	0	0	0	-4.4	0	0	0	4.4	0	4.9	4.9	
REC	3.2	0	0	-4.4	0	0	0	4.4	0	0	0	-4.4	0	0	0	4.4	0	4.9	4.9	
Ref. No.	IC6611 (SCM-72)																			
Mode	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
STOP	0	5.0	4.9	2.2	2.1	4.8	4.1	0.1	0.5	4.8	0	1.1	1.1	0.7	2.0	0.6	0.8	4.8	0.3	0.2
REC	0	5.0	4.9	2.2	2.1	4.8	4.1	0.1	0.5	4.8	0	1.1	1.1	0.7	2.0	0.6	0.9	4.8	0	0
Ref. No.	IC6611 (SCM-72)												IC6612 (SCM-72)							
Mode	21	22	23	24	25	26	27	28	29	30	31	32	1	2	3	4	5			
STOP	0	0.1	0.1	0	0	0	4.7	2.3	2.3	4.5	4.9	4.9	0	4.5	0	0.1	4.9			
REC	0	0.1	0	0	0	0	4.7	2.3	2.3	4.5	4.9	4.9	0	4.5	0	0.1	4.9			
Ref. No.	Q4001 (SCM-74)			Q4002 (SCM-74)			Q4003 (SCM-74)			Q4004 (SCM-74)			Q4005 (SCM-74)			Q4006 (SCM-74)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
REC	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
Ref. No.	Q4007 (SCM-74)			Q4008 (SCM-74)			Q4010 (SCM-73)			Q4011 (SCM-73)			Q4015 (SCM-73)			Q4016 (SCM-73)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	0	0	0	0	10.9	11.6	11.6	-11.5	-12.2	-12.1	0	0	-0.1	0	0	-0.1		
REC	0	0	0	0	0	0	10.8	11.6	11.6	-11.5	-12.2	-12.1	0	0	-0.1	0.1	0	-0.1		
Ref. No.	Q4017 (SCM-73)			Q4021 (SCM-73)			Q4022 (SCM-73)			Q4023 (SCM-73)			Q4027 (SCM-73)			Q4028 (SCM-73)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0	0	-0.1	0	0	-0.1	0	0	-0.1	0	0	-0.1	-0.2	0	-0.2	0	0	-0.2		
REC	0	0	-0.1	0	0	-0.1	0	0	-0.1	0	0	-0.1	0	0	-0.2	0.1	0	-0.2		
Ref. No.	Q4029 (SCM-73)			Q4033 (SCM-73)			Q4034 (SCM-73)			Q4035 (SCM-73)			Q4036 (SCM-73)			Q4037 (SCM-74)				
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B		
STOP	0.1	0	-0.2	0	0	-0.1	0	0	-0.1	0	0	-0.1	11.2	-0.1	11.4	-11.5	-12.2	-12.1		
REC	0	0	-0.3	0	0	-0.1	0	0	-0.1	0	0	-0.1	11.2	-0.2	11.4	-11.5	-12.2	-12.1		

Ref. No.	Q4038 (SCM-74)			Q6601 (SCM-72)			Q6602 (SCM-72)			Q6603 (SCM-72)			Q6606 (SCM-72)							
Mode	E	C	B	E	C	B	E	C	B	E	C	B	E	C	B					
STOP	10.9	11.6	11.6	-0.7	4.9	0	0	4.9	0	0	5.1	0	4.9	-4.7	4.2					
REC	10.9	11.6	11.5	-0.7	4.9	0	0	4.9	0	0	5.1	0	4.9	-4.7	4.2					
Ref. No.	Q6609 (SCM-72)						Q6610 (SCM-72)						Q6611 (SCM-72)							
Mode	1	2	3	4	5	6	1	2	3	4	5	6	E	C	B					
STOP	4.8	1.7	1.1	4.8	1.3	1.7	0.5	0.5	-0.2	4.8	0.5	-0.2	-0.8	4.8	-0.2					
REC	4.8	1.7	1.1	4.8	1.3	1.7	0.4	0.4	-0.2	4.8	0.4	-0.2	-0.8	4.8	-0.2					
Ref. No.	Q6612 (SCM-72)						Q6613 (SCM-72)													
Mode	1	2	3	4	5	6	E	C	B											
STOP	-4.9	-0.8	-0.2	-4.9	-0.8	-0.2	0.8	-4.2	0.2											
REC	-4.9	-0.8	-0.2	-4.9	-0.8	-0.2	0.8	-4.2	0.2											
Ref. No.	QR6603 (SCM-72)			QR6605 (SCM-72)			QR6606 (SCM-72)			QR6607 (SCM-72)										
Mode	E	C	B	E	C	B	E	C	B	E	C	B								
STOP	0	0	3.6	4.4	0.3	4.8	0	4.8	0	0	4.8	0.1								
REC	0	0	3.6	4.4	0.5	4.8	0	4.8	0	0	4.9	0.1								

Panasonic®